



Main

| | |
|---------------------------|--------------------|
| Range of product | Vivace |
| Device short name | KB33 |
| Product or component type | TV/FM/SAT socket |
| Device presentation | Complete mechanism |

Complementary

| | |
|------------------------|--|
| Colour tint | White |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Maximum insertion loss | 2 dB (+/- 1.5 dB) at 88...125 MHz (IN-FM) 1 dB (+/- 1.5 dB) at 40...70 MHz (IN-TV) 2 dB (+/- 1.5 dB) at 174...862 MHz (IN-TV) 2 dB (+/- 1.5 dB) at 950...2150 MHz (IN-SAT) 2 dB (+/- 1.5 dB) at 2150...2400 MHz (IN-SAT) |
| Minimum return loss | 5 dB 40...2400 MHz IN 8 dB 87.5...125 MHz FM-SAT 5 dB 40...862 MHz TV 5 dB |
| Isolation | 20 dB at 88...108 MHz (TV-FM) 6 dB at 40...2400 MHz (TV-SAT) 30 dB at 40...860 MHz (FM-SAT) |
| TV connector | Male IEC |
| Radio connector | Male IEC |
| SAT connector | Female F type |
| Average impedance | 75 Ohm |
| Projecting depth | 36.2 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |
| Fixing mode | By screw M3.5 |
| Fixing center | 60.3 mm |

| | |
|-------------------------|----------------|
| Embedding depth | 35 mm |
| Connections - terminals | Cable terminal |
| Tightening torque | 0.4 N.m |
| Width | 86 mm |
| Height | 86 mm |
| Net weight | 110 g |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | No exposure to direct radiation from sunlight |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|