



### Main

Range	Vivace
Product or component type	Switch
Device short name	KB34
Device application	Lighting
Device presentation	Complete mechanism

### Complementary

Switch function	2-way
Actuator	Rocker
Number of gangs	4 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base Polycarbonate: dolly Nylon: actuator Silver plated copper: bridge Brass: terminal cover
Surface finish	Glossy
Surface treatment	Untreated
Type of packing	Box
Quantity per set	8
Sale per indivisible quantity	1
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Embedding depth	24 mm
Rated current	10 AX at 250 V AC, inductive 10 AX at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	12 screw terminals
Terminal identifier	L1 COM L2
Tightening torque	0.4 N.m
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for rigid or stranded cable(s)
Wire stripping length	12 mm
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un
Width	86 mm
Height	86 mm
Depth	36.5 mm
Net weight	0.0829 kg

## Environment

Standards	IEC 60669
Product certifications	SNI SIRIM
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
IP degree of protection	IP20

## Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------