



### Main

|                               |                  |
|-------------------------------|------------------|
| Range                         | Vivace           |
| Product or component type     | Switch           |
| Device short name             | KB34             |
| Device application            | Lighting         |
| Device presentation           | Complete product |
| Additional switch application | Switch           |

### Complementary

|                                |   |
|--------------------------------|---|
| Switch function                | 1-way   |
| Actuator                       | Rocker  |
| Number of gangs                | 4 gangs   |
| Colour tint                    | White   |
| Material                       | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Nylon: base |
| Surface finish                 | Glossy  |
| Surface treatment              | Untreated   |
| Type of packing                | Plastic bag   |
| Quantity per set               | 1   |
| Projecting depth               | 8 mm  |
| Device mounting                | Flush   |
| Mounting support               | Wall mounted  |
| Fixing mode                    | By screw M3.5   |
| Fixing center                  | 120.6 mm  |
| Embedding depth                | 35 mm   |
| Rated current                  | 16 AX at 250 V AC, inductive<br>16 AX at 250 V AC, fluorescent      |
| [Ue] rated operational voltage | 250 V AC  |
| Network frequency              | 50/60 Hz  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |   |
|------------------------------|---|
| Connections - terminals      | 8 pillar terminal                                     |
| Terminal identifier          | COM<br>L1   |
| Tightening torque            | 0.4 N.m   |
| Clamping connection capacity | <= 2.5 mm <sup>2</sup> for rigid or stranded cable(s) |
| Wire stripping length        | 12 mm   |
| Width                        | 146 mm  |
| Height                       | 86 mm   |
| Depth                        | 36 mm   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 60669-1<br>SS 227<br>MS IEC 60669-1 |
| Ambient air temperature for operation | -5...40 °C                              |
| Relative humidity                     | 0...95 %                                |
| Operating altitude                    | 0...2000 m                              |
| Environmental characteristic          | Indoor use                              |
| IP degree of protection               | IP20                                    |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |