

# Product datasheet

Specifications



## Wiser Multifunction Interface

CCT501402

### Main

Range	Wiser
Product name	Wiser Multifunction Interface
Product or component type	Hub
Device application	Zigbee/RS485 network interface

### Complementary

Range compatibility	Wiser Zigbee/IP gateway Wiser
Colour	White
Communication network type	RS485 ZigBee - 2.4 GHz conforming to IEEE 802.15.4
Connector type	connector(s)3 x 2-pin terminal block for RS485 network connector(s)1 x 2-pin terminal block for external supply
[Us] rated supply voltage	12 V DC, <100 mA 24 V DC, <100 mA
Realtime clock	With RTC-battery set
Local signalling	4 LEDs (green/red/orange)
Width	46 mm
Height	77 mm
Depth	41 mm

### Environment

Ambient air temperature for operation	-10...45 °C
Relative humidity	10...90 %
Environmental characteristic	Indoor use
IP degree of protection	IP20
Standards	EN/IEC 60669-2-4 EN/IEC 60730-2-13
Product certifications	CE

### Packing Units

Unit Type of Package 1	PCE
------------------------	-----

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.7 cm
<b>Package 1 Width</b>	6.8 cm
<b>Package 1 Length</b>	9.2 cm
<b>Package 1 Weight</b>	85.0 g

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>