

Product datasheet

Specifications



Wiser Hub

CCT501900

Main

Range	Wiser
Product or component type	Hub
Device application	Zigbee/IP network interface

Complementary

Colour	White
Communication network type	Ethernet conforming to IEEE 802.3 WLAN - 2.4 GHz conforming to IEEE 802.11 b/g/n ZigBee - 2.4 GHz conforming to IEEE 802.15.4
Port Ethernet	10/100BASE
Connector type	connector(s)1 x micro USB port female for adaptor connector(s)1 x 2-pin terminal block for 12 V DC power supply
Electrical connection	Cable, 0.25...1.5 mm ² / AWG 24...AWG 16 (terminal)
[Us] rated supply voltage	5 V DC, <1 A 12 V DC, <0.5 A
Realtime clock	With RTC-battery set
Local signalling	Indicator: 3 LEDs (white)
Width	86 mm
Height	86 mm
Depth	34 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	10...90 %
Environmental characteristic	Indoor use
IP degree of protection	IP20
Standards	EN 62368-1 IEC 62368-1
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	6.9 cm
Package 1 Width	13.4 cm
Package 1 Length	18.7 cm
Package 1 Weight	372.0 g
Unit Type of Package 2	P12
Number of Units in Package 2	320
Package 2 Height	105.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	154.64 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	8
Package 3 Height	16.5 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	3.491 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information