Wiser Window/Door Sensor



CCT591011_AS

viaii i

Range compatibility	Wiser hub
Range	Wiser
Product or component type	Window/door contact
Colour tint	White
Supply	Battery3 V / CR2450

Complementary

Device application	Security
Battery life	5 year(s)
Communication port protocol	Zigbee at 2.4 GHz conforming to IEEE 802.15.4
Device composition	sensor 50 mm x 33 mm x 16.3 mm magnet 50 mm x 9 mm x 9 mm
Alive signal	48/day
Magnet gap	< 18 mm on wood and plastic surface < 10 mm on metallic surface
Type of operator	Trigger action wood opening contact 32 mm Trigger action wood closing contact 30 mm Trigger action metal opening contact 20 mm Trigger action metal closing contact 18 mm
Local signalling	1 orange LED blinking , function: battery needs replacing LED, function: programming indication
Standards	IEC 60669-2-5 EN 60669-2-5
Product certifications	CE Zigbee 3.0 CB RCM EAC
Market segment	Residential

Environment

IP degree of protection	IP20
Relative humidity	1095 %
Ambient air temperature for operation	-1050 °C
Operating altitude	<= 2000 m

Environmental above stariation	Indooruge
Environmental characteristic	mador use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	84.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.875 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration