

Product datasheet

Specifications

Wiser Water Leakage Sensor

CCT592011_AS



Main

Range compatibility	Wiser hub
Range	Wiser
Product or component type	Water leakage sensor
Sensor type	Flow sensor

Complementary

Colour tint	White
Material	Thermoplastic
[Ue] rated operational voltage	3 V
Supply	Battery: alkaline 2 x 1.5 V / LR03 AAA
Battery life	5 year(s)
Local signalling	1 orange LED blinking , function: battery needs replacing
Sound signalling	Alarm: siren 70 dB
Communication port protocol	Zigbee at 2.4 GHz conforming to IEEE 802.15.4
Depth	18.96 mm
Height	70.8 mm
Alive signal	144/day
Width	68.68 mm
Standards	EN 60669-2-5 IEC 60669-2-5
Product certifications	CE Zigbee 3.0

Environment

Ambient air temperature for operation	-10...50 °C
Relative humidity	10...95 %
IP degree of protection	IP44
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	114.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.075 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration