

## NEP POLY 1X28 W EZ

NEPTUNE T8 POLY | Damp-proof luminaires

### Areas of application

- Damp and dusty environment with normal corrosion levels
- Difficult application conditions with humidity or dust
- Functional lighting in wet or damp and dusty rooms
- Ideal for industrial and storage facilities
- Indoor or outdoor (only roofed areas)
- Car parks and underpasses
- Ceiling surface-mounting and suspended mounting
- Not suitable for harsh environments

### Product family benefits

- Easy to install and use

### Product family features

- Jet-proof luminaires
- Connection with 3-pin screw terminal
- Polycarbonate casing with polyurethane seal
- Ceiling mounting with clips
- Impact resistance: IK08
- Sealing for protection against dust
- Type of protection: IP65



## Product datasheet

### Technical data

#### Product information

Order reference	NEP POLY GR 1X2
-----------------	-----------------

#### Electrical data

Operating mode	ECG
Lamp wattage	28 W
Nominal voltage	220...230 V
Supply voltage	220...230 V
Mains frequency	50...60 Hz

#### Light technical data

Beam angle	wide distribution °
Light distribution	symmetric

#### Dimensions & weight



Length	1210 mm
Width	80.0 mm
Height	90.0 mm
Product weight	1.7 kg

#### Colors & materials

Body material	PC
Product color	grey
Cover material	PC

#### Temperatures & operating conditions

Ambient temperature range	0...+25 °C
---------------------------	------------

## Product datasheet

### Additional product data

Number of lighting outlets	1
Type of cover	enclosure

### Capabilities

Type of installation	surface-mounted
Type of connection	terminal, 3-pole, max. 2.5mm <sup>2</sup>
Holder designation	G5

### Certificates & standards

Protection class	insulation class I (protective earthing)
Type of protection	IP65
Protection against ignition and fire	F
Protection class IK (shock resistance)	IK10

### Country specific categorizations

Order reference	NEP POLY GR 1X2
-----------------	-----------------

## Product datasheet

---

### Equipment / Accessories

- Suitable for LUMILUX T8 fluorescent lamps
  - Integrated electronic control gear QT-FIT8 (EEI: A2)
- 

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321540089	NEP POLY 1X28 W EZ	Folding carton box 1	- x - x -		
4008321540096	NEP POLY 1X28 W EZ	Shipping carton box 9	1242 mm x 206 mm x 298 mm	76.24 dm <sup>3</sup>	17900.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---