

DIM MCU G2

DIM MCU G2 | Light management systems



Product family features

- Switching load contact: 250 V/6 A (10 1-lamp or 5 2-lamp ECGs)
- Cover and rotary knob in cream white

Product family benefits

- Intuitive manual dimming and switching
- Individual setting of minimal brightness level

Areas of application

- Conference rooms
- Restaurants
- Shop lighting


Page 1 of 4


Product datasheet

Technical data


Electrical data


Dimensions & weight











Length	71.0 mm
Width	71.0 mm
Height	40.0 mm
Product weight	88.00 g
Mounting hole spacing, length	60.0 mm

Colors & materials

Product color	White

Temperatures & operating conditions

Ambient temperature range	-20+50 °C
---------------------------	-----------

Capabilities

Dimmable	Yes

Product datasheet

Dimming interface	110 V
Number of control outputs	1
Load contact	6 A
Type of installation	Integrated in flush device box

Certificates & standards

Type of protection	IP20
Protection class	Ш
Approval marks – approval	CE / UKCA / EAC

Logistical data

Commodity code	85365080900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	21-07-2023		
Primary Article Identifier	4062172224642		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	609e61c5-928a-44fb-a14b-13f6e2061dd9		

Equipment / Accessories

- Suitable for up to 50 electronic control gears (external load contact required)
- Flexible expansion via external load contact and via signal amplifier DIM SA
- Cover and rotary knob included

Download Data

	File
<u> </u>	User instruction DIM MCU G2

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172224642	DIM MCU G2	Shipping carton box 48	362 mm x 270 mm x 288 mm	28.15 dm³	6820.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.