



## LED Waterproof Utility

### Features

- Optimal heat management, 30Khrs
- IP65 protection rating
- IK08 Anti-shock enclosure
- Anti-UV polycarbonate cover

### Benefits

- Lasts 4 times longer than fluorescent waterproof
- Water and dust proof, suitable for outdoor use
- Impact resistant
- Prevent cover yellowing , ensures long product lifespan

### Application



Parking



Warehouse



Tunnel



Hospital

### Specification

Item Code	Item Description	Power (W)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Input Current (mA)	Lifetime (L70B50)	MOQ (pcs)
140056002	LEDWaterproof-U L 600-10W-4000-FR-GP	10	0.5	900	90	74	30000	492
140056003	LEDWaterproof-U L 600-10W-6000-FR-GP	10	0.5	900	90	74	30000	492
140056004	LEDWaterproof-U L 1200-20W-4000-FR-GP	20	0.5	1800	90	148	30000	492
140056005	LEDWaterproof-U L 1200-20W-6000-FR-GP	20	0.5	1800	90	148	30000	492

Technical Specifications	
CRI	≥ 80
Colour Consistency (SDCM)	6
Dimmable	No
Housing Colour	Grey
IP	IP65
IK	IK08
Driver integrated (Yes/No)	Yes
Glow wire test	650°C
Driver failure rate	1% at 5000h
Weight (kg/pc)	0.50/ 0.87

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Mechanical Properties	
Housing Material	PC
Optical Material	PC

Application Conditions	
Operating Temperature	-25-50°C
Application Temperature	+25°C
Storage Environment	-25-50°C

