



Tornado High Lumen

EHL TWISTER 65W 865 E27 220-240V 1CT/6

Energy saving lamp in spiral shape, with superior performance (long life, high switching) and high lumen warm bright light. Perfectly suitable to be used in places where high lumen is required, and the lamp is directly visible.

Product data

General Information	
Cap base	E27 [E27]
Nominal lifetime (nom.)	10000 h
Switching cycle	10000X
Light Technical	
Colour Code	865 [CCT of 6,500 K]
Lamp Luminous Flux 25°C EL (Nom)	4000 lm
Lamp Luminous Flux (Nom)	4000 lm
Colour Designation	Cool Daylight
Lumen maintenance 2,000 hours (nom.)	85 %
Chromaticity coordinate X (nom.)	313
Chromaticity coordinate Y (nom.)	337
Colour Temperature, horizontal (Nom)	6500 K
Lamp Luminous Efficacy EM (Nom)	62 lm/W
Colour Rendering Index,horiz (Nom)	80
LLMF at end of nominal lifetime (nom.)	65 %
Operating and Electrical	
Input frequency	50 or 60 Hz
Power (Rated) (Nom)	65.0 W
Lamp current (nom.)	270 mA
Wattage equivalent	250 W
Starting time (nom.)	1.5 s

Warm-up time to 60% light (min.)	5 s
Warm-up time to 60% light (max.)	40 s
Power factor (nom.)	0.95
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	no
Approval and Application	
Energy efficiency label (EEL)	А
Mercury (Hg) content (max.)	5 mg
Energy Consumption kWh/1000 h	65 kWh
Product Data	
Full product code	871829179464600
Order product name	EHL TWISTER 65W 865 E27 220-240V 1CT/6
EAN/UPC – product	8718291794646
Order code	79464600
Numerator – quantity per pack	1
Numerator – packs per outer box	6
Material no. (12NC)	929676011406
Net weight (piece)	0.330 kg

Datasheet, 2019, June 28 data subject to change

Tornado High Lumen

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product

Dimensional drawing



EHL TWISTER 65W 865 E27 220-240V 1CT/6 98 mm 226 mm 80.3 mm

D (max) C (max) F (max)

EcoHL Twist 65W CDL E27 220-240V 50/60Hz

