

Eaton 235429

Catalog Number: 235429

Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB. PFIM, 2 pole, In: 40 A, Icn: 10 kA, IΔN: 0.3 A, residential and commercial



General specifications

| | |
|--|----------------|
| Product Name | Catalog Number |
| Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB | 235429 |
| | EAN |
| | 4015082354299 |
| Product Length/Depth | Product Height |
| 80 mm | 76 mm |
| Product Width | Product Weight |
| 35 mm | 0.184 kg |
| Compliances | Certifications |
| RoHS conform | IEC/EN 61008 |
| Model Code | |
| PFIM-40/2/03-A-MW | |

Delivery program

Application

Residual current circuit breaker for residential and commercial applications

xPole - Switchgear for residential and commercial applications

Number of poles

Two-pole

Tripping time

Non-delayed

Amperage Rating

40 A

Rated short-circuit strength

10 kA

Fault current rating

300 mA

Sensitivity type

Pulse-current sensitive

Impulse withstand current

Partly surge-proof 250 A

Type

PFIM

Residual current circuit breakers

Type A

Technical data - electrical

Voltage rating

230 V AC

Rated operational voltage (U_e) - max

230 V

Rated insulation voltage (U_i)

440 V

Rated impulse withstand voltage (U_{imp})

4 kV

Rated fault current - min

0.3 A

Rated fault current - max

0.3 A

Frequency rating

50 Hz

Short-circuit rating

63 A (max. admissible back-up fuse)

Leakage current type

A

Rated residual making and breaking capacity

500 A

Admissible back-up fuse overload - max

25 A gG/gL

Rated short-time withstand current (I_{cw})

10 kA

Surge current capacity

0.25 kA

Test circuit range

196 V AC - 264 V AC

Pollution degree

2

Lifespan, electrical

4000 operations

Technical data - mechanical

Design verification as per IEC/EN 61439 - technical data

Frame
45 mm

Width in number of modular spacings
2

Built-in width (number of units)
35 mm (2 SU)

Built-in depth
70.5 mm

Mounting Method
DIN rail
Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715

Degree of protection
IP20
IP20, IP40 with suitable enclosure

Terminals (top and bottom)
Open mouthed/lift terminals

Terminal capacity (solid wire)
1.5 mm² - 35 mm²

Connectable conductor cross section (solid-core) - min
1.5 mm²

Connectable conductor cross section (solid-core) - max
35 mm²

Terminal capacity (stranded cable)
16 mm² (2x)

Connectable conductor cross section (multi-wired) - min
1.5 mm²

Connectable conductor cross section (multi-wired) - max
16 mm²

Terminal protection
Finger and hand touch safe, DGUV VS3, EN 50274

Busbar material thickness
0.8 mm - 2 mm

Lifespan, mechanical
20000 operations

Permitted storage and transport temperature - min
-35 °C

Rated operational current for specified heat dissipation (In)
40 A

Heat dissipation per pole, current-dependent
0 W

Equipment heat dissipation, current-dependent
5.4 W

Static heat dissipation, non-current-dependent
0 W

Heat dissipation capacity
0 W

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
60 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be

Permitted storage and transport temperature - max

60 °C

Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Accessories required

Z-HK 248432

Features

Residual current circuit breaker

Resources

3D models

[DA-CD-pfi_2p](#)

[DA-CS-pfi_2p](#)

[Application notes](#)

Additional equipment possible

Fitted with:

Interlocking device

Special features

Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 2.5% for every 1 °C

Tripping signal contact for subsequent installation Z-NHK 248434

Used with

KLV-TC-2 276240 (Compact enclosure)

Z-FW/LP 248296 (Remote control and automatic switching device)

Z-RC/AK-2MU 285385 (sealing cover set)

[eaton-rcd-application-guide-br019003en-en-us.pdf](#)

Catalogs

[eaton-xpole-pfim-x-rccb-catalog-ca019029en-en-us.pdf](#)

[eaton-xpole-pfim-u-rccb-catalog-ca019028en-en-us.pdf](#)

User guides

[IL019140ZU](#)