

# MA4200

ORDER CODE: PA-MA4200

## 2.1 CHANNEL MULTIMEDIA MIXER AMPLIFIER



### Features

- High powered, efficient Class D audio amplifiers built in.
- Compact all-in-one design in a professional 1RU 19" metal chassis.
- No noisy cooling fans.
- Bass, treble and balance control.
- L&R and SUBWOOFER volume controls.
- Low-pass control (50-150Hz) and tone control for subwoofer.
- TWO AUX inputs with individual volume control (1 x RCA stereo and 1 x Phone jack 3,5mm stereo).
- MIC IN ( XLR or Phone jack 6,3mm).
- AUX OUT (RCA stereo connector, line level).
- Assistive listening device (ALD) output (Phone jack 3.5mm) with volume control.
- DC power output 12V/200mA x 1, 5VDC output (USB A) for supplying low power accessories x 1.
- VOICE PRIORITY & LOW CUT (switchable) for all MIC inputs.
- Inputs matched for smart-phone audio outputs.
- Easy-to-use design, no technical background needed.
- Plug and play without special connectors or tools, USER-friendly!
- Available optional modules: RX8D, RX8TD, DPR5, BT5.

### Specifications

Model	MA4200
<b>Supply voltage</b>	18~24VDC / 5A min. (by external switching power supply)
<b>Power output</b>	All in all about 200W RMS
<b>Frequency response</b>	L&R: 20~20,000Hz±3dB Subwoofer: 20~250Hz±3dB
<b>Input wired microphone</b>	1 x XLR phantom powered 1 x Phone jack 6.3mm
<b>All microphone inputs</b>	Voice priority and low cut switch on front panel
<b>Input AUX 1</b>	RCA (stereo) line level
<b>Input AUX 2</b>	Phone jack 3.5mm (stereo) line level
<b>Output AUX</b>	RCA (stereo) line level (output of mixed signal)
<b>Outputs L&amp;R</b>	Phone jack 6.3mm (mono) & screw terminals 5,08mm
<b>Output subwoofer</b>	Phone jack 6.3mm (mono) & screw terminals 5,08mm 0°/180° phase switch provided on the rear side
<b>Output ALD</b>	Phone jack 3.5mm (stereo) line level
<b>Output USB</b>	Socket type A, for external low power devices (200mA max.)
<b>Output DC</b>	About 12VDC/200mA for external low power devices
<b>Dimensions (mm)</b>	482 (W) x 200 (D) x 44 (H)
<b>Weight (kg)</b>	2.06

\* NOTE: The above specifications are subject to change without prior notice.