



COVENANT

Security Equipment



BALLISTIC



BLAST



STORM IMPACT





FORCED ENTRY

RESPONSIVE. ETHICAL. EFFICIENT.

HIGH SECURITY DOORS

Our high security aluminum doors are designed to provide all types of protection while offering a modern and aesthetically pleasing appearance and long-lasting durability with a light-weight composition for easier handling. Our doors incorporate top quality hardware and a reinforced heavyweight hinge to ensure your door will be reliable and easy to operate and maintain.



USAD 1000 ALUMINUM DOOR

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL752 Levels 1-8, NIJ I, II-A, II, III-A, III
- **BLAST:** Calculations to be provided per UFC / ISC criteria
- **STORM IMPACT & FEMA:** FEMA 361-15 & tested to ICC500-14 Standards
- **FRAME SIZE:** 2.5"W x 4.5"D
- **DOOR SIZE:** 3' x 7' with custom sizes available
- **DOOR THICKNESS:** 2-3/4"
- **STILES:** Monumental (5-5/16") or Narrow (3")
- **FULL, HALF, DOUBLE OR OPAQUE**
- **GLAZING THICKNESS:** 1" – 2-3/16"

DOOR OPTIONS:

- The USAD 1000 door is available as single or double doors swinging or sliding configuration. Glass side lites and / or transoms are available.
- Standard finish on all aluminum products is clear or dark bronze anodized. Custom color, Kynar paint, brass and stainless steel cladding are also available.
- All doors are custom made and can be designed to interface with any building automation and electronic security system.

USAD 1000 15R ALUMINUM DOOR

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL752 Levels 1-8, NIJ I, II-A, II, III-A, III, Department of State Rifle Ratings (7.62 and 5.56)
- **BLAST:** Calculations to be provided per UFC / ISC criteria
- **FORCED ENTRY:** DOS STD SD 01.01 Rev G
- **FRAME SIZE:** 3"W x 5"D
- **DOOR SIZE:** 3' x 7' with custom sizes available
- **DOOR THICKNESS:** 2.5"
- **GLAZING THICKNESS:** 1-1/2"

Ask about the patented **Quick-Throw Thumb Turn** available on all USAD 1000 15R doors, which provides a fast and intuitive locking mechanism for emergency situations.

- Available with a wide range of hardware options including commercial mortise locksets, rim mounted exit devices, magnetic locks and automatic operators.

NOTE All doors shipped factory assembled and finished with ballistic glazing. Single doors are shipped pre-hung in security frames.

HIGH SECURITY WINDOWS

Our high security aluminum windows use an industry-proven pressure plate design and are engineered to provide all types of security for our customers including simultaneous bullet and blast protection. We also have a select line of products that offer a full thermal break so you don't have to sacrifice energy conservation for protection in your building.



USAW 100

SLIDING INTERIOR/EXTERIOR ALUMINUM WINDOW

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL752 Levels 1-3



USAW 200

OPERABLE INSWING INTERIOR ALUMINUM WINDOW

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL752 Levels 1-8, NIJ I, II-A, II, III-A, III
- **FRAME SIZE:** 1-1/2"W x 4-1/8"D
- **GLAZING THICKNESS:** 1/4" to 2-1/4"
- **APPLICATIONS:** Back-glaze system to protect specific area of a building without affecting exterior architectural appearance.



USAW 300

FIXED INTERIOR ALUMINUM WINDOW

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL 752 Levels 1-8, NIJ I, II-A, II, III-A, III
- **FRAME SIZE:** 1-1/4"W x 3-3/4"D with custom sizes available
- **GLAZING THICKNESS:** 1" to 2-1/4"
- **APPLICATIONS:** Ideal for transaction window in secure office within a building



USAW 400

FIXED EXTERIOR ALUMINUM WINDOW

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** UL 752 Levels 1-8, NIJ I, II-A, II, III-A, III
- **BLAST:** Calculations to be provided per UFC / ISC criteria
- **STORM IMPACT & FEMA:** Tested to FEMA 361 and ICC500
- **FORCED ENTRY:** ASTM F1233 and F588
- **FRAME SIZE:** 2-1/2"W x 4-1/2"D with custom sizes available
- **GLAZING THICKNESS:** 1 to 2-3/8"
- **APPLICATIONS:** Ribbon, store front, curtain wall and punched openings

Available with thermally enhanced or full 1" thermally broken frame for optimal energy conservation.



USAW 800

HIGH LEVEL SECURITY - FIXED EXTERIOR ALUMINUM WINDOW

USBP CERTIFICATION OR TESTING STANDARDS

(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS:** Department of State Rifle Ratings (7.62 and 5.56) UL 752 Level 1-8, NIJ I, II-A, II, III-A, III
- **BLAST:** Calculations to be provided per UFC / ISC criteria, DOS STD SD 01.01 Rev G
- **FORCED ENTRY:** Department of State 5 and 15 minutes ratings and ASTM F1233
- **ENERGY EFFICIENT:** ASTM E283, ASTM 330, ASTM 331 AND AAMA 501.1, NFRC 100/200/500 AND AAMA 501.5
- **SOUND TESTING:** ASTM E90, E413, E1332 AND E2235



- **FRAME SIZE:** 2-1/2"W x 6"D
- **GLAZING THICKNESS:** 1" to 2-3/8"
- **APPLICATION:** Any location where an extremely high level of forced entry protection is required

Full Thermally Broken Frame System for optimal energy conservation


WINDOWS OPTIONS:

1. We have extensive experience in security glass laminates and can assist you in determining the appropriate level of glazing required for your project at a very competitive price.
2. Standard finish on all aluminum products is clear or dark bronze anodized. Custom color, Kynar paint and brass and stainless steel cladding are also available.
3. Standard finish on all steel products is prime paint. Custom color, paint, aluminum, brass and stainless steel cladding are also available.
4. **ACCESSORIES:** Select products are available with built-in accessories such as deal trays, communication devices or transaction drawers. Contact us or refer to our accessories section for more details.

WALL ARMOR

We offer a complete line of fiberglass and steel wall armor to ensure the walls of your facility are fully protected.

Wall armor is ideal for all of the walls which surround bullet resistant curtain walls, storefront or transaction systems to ensure you have a complete and formidable protective barrier for your facility.



FIBERGLASS

USBP CERTIFICATION OR TESTING STANDARDS

- **BALLISTICS:** UL 752 Levels 1-8 and NIJ I,II-A, II, III-A, III
- **STANDARD PANEL SIZE:** 48" x 96" with custom sizes available



BALLISTIC STEEL

HIGH SECURITY LOUVERS

ALUMINUM LOUVERS

USBP CERTIFICATION OR TESTING STANDARDS
(TESTED TO LISTED OR EQUIVALENT STANDARD)

- **BALLISTICS AND FORCED ENTRY:** DOS STD SD 01.01 Rev G, High Power Ballistics 15 FE/BR



HIGH SECURITY ACCESSORIES

VOICE COMMUNICATIONS

USST



NATURAL VOICE COMMUNICATION DEVICE

- Stainless steel, evenly spaced, concentric louvers
- UL 752 Level 1-3 Ballistic Protection

UST 3



ELECTRONIC COUNTERTOP COMMUNICATION DEVICE

- Through countertop wiring eliminates hole in protective glazing
- Ballistic rating not required since not part of ballistic protection system

UST 1



THROUGH GLASS ELECTRONIC COMMUNICATION DEVICE

- Provides amplified clear voice communications
- UL 752 Levels 1-3 Ballistic Protection

TRAYS + DRAWERS

USDT 100



RECESSED DEAL TRAY

- 12" W x 10" L x 1-5/8" D, large size transfer area
- Optional surface mount and counter available
- Custom sizes available
- Stainless steel or brass finish
- UL 752 Level 1-3 Ballistic Protection

USDT 94



SLIDING RECESSED DEAL TRAY

- 7-3/4" W x 6-1/4" L x 1-1/4" D transfer area
- Optional surface mount and counter available
- Custom sizes available
- Stainless steel or brass finish
- UL 752 Level 1-3 Ballistic Protection

USDT 150



PASS-THRU DRAWER

- 13-3/4" W x 20" L x 4" D transfer area
- 4 sizes available
- Stainless steel finish
- UL 752 Level 1-3 Ballistic Protection

USDD 300



PASS-THRU DRAWER WITH INTEGRATED COMMUNICATIONS

- 13-3/4" W x 6-1/8" H x 10-3/8" L transfer area
- Stainless steel
- UL 752 Level 1-3 Ballistic Protection

USDD 198



PASS-THRU DRAWER WITH DEAL TRAY

- Removable deal tray allows for passing large objects
- 4 sizes available
- Stainless steel
- UL 752 Level 1-8 Ballistic Protection

USCPR



CLEAR PACKAGE RECEIVER

- 16" W x 16" H x 16" D
- Interlock prevents opening of both doors simultaneously
- UL 752 Levels 1-3 Ballistic Protection

SECURITY RATINGS AND TESTING

BALLISTIC STANDARDS

The most common ballistic standards are UL 752 and the National Institute of Justice (NIJ). Both are summarized below. When ordering products, please specify the required level of ballistic and/or blast protection.

UL 752 RATINGS OF BULLET RESISTANT MATERIALS

PROTECTION LEVEL	AMMUNITION	NO. OF SHOTS
Level 1	9mm Full Metal Copper Jacket with Lead Core	3
Level 2	.357 Magnum Jacketed Lead Soft Point	3
Level 3	.44 Magnum Lead Semi-Wadcutter Gas Checked	3
Level 4	.30 Caliber Rifle Lead Core Soft Point (.30-06 caliber)	1
Level 5	7.62mm Rifle Lead Core Full Metal Copper Jacket, Military Ball (.308 caliber)	1
Level 6	9mm Full Metal Copper Jacket with Lead Core	5
Level 7	5.56mm Rifle Full Metal Copper Jacket with Lead Core (.223 caliber)	5
Level 8	7.62 Rifle Lead Core Full Metal Copper Jacket, Military Ball (.308 caliber)	5
Level 9	.30-06 AP	1

NIJ STANDARD 0801.01 BALLISTIC RESISTANT PROTECTIVE MATERIALS

ARMOR TYPE	TEST AMMUNITION	REQ HITS PER SPECIMAN
I	22 LRHV LEAD 38 Special RN Lead	5
II-A	357 Magnum JSP 9mm FMJ	5
II	357 Magnum JSP (higher velocity round) 9mm FMJ (higher velocity round)	5
IIIA	44 Magnum, Lead SWC Gas Checked 9mm FMJ	5
III	7.62mm, 308 Winchester FMJ	5
IV	.30-06 AP	1


AP – Armor Piercing **LRHV** – Long Rifle High Velocity
FMJ – Full Metal Jacket **RN** – Round Noise
JSP – Jacketed Soft Point **SWC** – Semi-Wadcutter

BLAST RESISTANT STANDARDS

The graphic and table show the performance criteria for blast resistant products.

Specify **performance condition** and **impulse** when ordering a blast resistant product.

NOTE That ballistic and forced entry protection can also be specified and achieved in a blast resistant product.



$$\text{IMPULSE} = \frac{1}{2} \times \text{Pressure (psi)} \times \text{Duration (msec)}$$

NOTE our products meet and/or exceed UL 752 Ballistic Standards, ForcedProtection/Anti-Terrorism Criteria. Test reports are available upon request.

PERFORMANCE CONDITION

PROTECTION LEVEL	HAZARD LEVEL	GLAZING SYSTEM RESPONSE	
1	Safe	None	Glazing does not break. No visible damage to glazing or frame.
2	Very High	None	Glazing cracks but is retained by the frame. Dusting or very small fragments near sill or on floor acceptable.
3A	High	Very Low	Glazing cracks. Fragments enter space and land on floor no further than 3.3 ft from the window.
3B	High	Low	Glazing cracks. Fragments enter space and land on floor no further than 10 ft. from the window.
4	Medium	Medium	Glazing cracks. Fragments enter space and land on floor and impact a vertical witness panel at a distance of no more than 10 ft. from the window at a height no greater than 2 ft. above the floor.
5	Low	High	Glazing cracks and window system fails catastrophically. Fragments enter space impacting a vertical witness panel at a distance of no more than 10 ft. from the window at a height greater than 2 ft. above the floor.



COVENANT

Security Equipment



WWW.COVENANTSECURITYEQUIPMENT.COM



SALES@ COVENANTSECURITYEQUIPMENT.COM



866.286.4400



RESPONSIVE. ETHICAL. EFFICIENT.



MADE IN THE USA