



COVENANT

Security Equipment

UL752 Level 1

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 2.6 lbs per square foot

NOMINAL THICKNESS: 1/4"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 1 Paragraph 4.3
- One Hour Fire Rating Per ASTM E119-98

AMMUNITION TESTED:

9mm full metal copper jacket with lead core – 124 grain, 8 grams, minimum 1175 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



COVENANT

Security Equipment

UL752 Level 2

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOM. WEIGHT: 3.6 lbs per square foot

NOM. THICKNESS: 5/16"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 2 Paragraph 4.4
- National Institute of Ballistic Standards NIJ0108.01 – Level II-A
- One Hour Fire Rating Per ASTM E119-98

AMMUNITION TESTED:

.357 magnum jacketed lead soft point – 158 grain, 10.2 grams, minimum 1250 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



COVENANT

Security Equipment

UL752 Level 3

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 4.8 lbs per square foot

NOMINAL THICKNESS: 7/16"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 3 Paragraph 4.5
- National Institute of Ballistic Standards NIJ0108.01– Level IIIA
- One Hour Fire Rating Per ASTM E119-98
- Class IV Forced Entry Protection Rating Per ASTM F1233-98

AMMUNITION TESTED:

.44 magnum lead semi-wadcutter gas checked – 240 grain, 15.6 grams, minimum 1350 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



COVENANT

Security Equipment

UL752 Level 4

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 13.9 lbs per square foot

NOMINAL THICKNESS: 1-3/8"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 4 Paragraph 4.6
- One Hour Fire Rating Per ASTM E119-98
- Class IV Forced Entry Protection Rating Per ASTM F1233-98
- Sound Insulation Rating Per ASTM E413-87

AMMUNITION TESTED:

.30 caliber rifle lead core – 180 grain, 11.7 grams, minimum 2450 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



UL752 Level 5

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 14.8 lbs per square foot

NOMINAL THICKNESS: 1-7/16"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 5 Paragraph 4.7
- One Hour Fire Rating Per ASTM E119-98
- Class IV Forced Entry Protection Rating Per ASTM F1233-98
- Sound Insulation Rating Per ASTM E413-87

AMMUNITION TESTED:

7.62mm rifle lead core full copper jacket, military ball – 150 grain, 9.7 grams, minimum 2750 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



COVENANT

Security Equipment

UL752 Level 6

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOM. WEIGHT: 3.9 lbs per square foot

NOM. THICKNESS: 3/8"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 6 Paragraph 4.8
- National Institute of Ballistic Standards NIJ0108.01 – Level II
- One Hour Fire Rating Per ASTM E119-98

AMMUNITION TESTED:

9mm full metal copper jacket with lead core – 124 grain, 8 grams, minimum 1400 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



COVENANT

Security Equipment

UL752 Level 7

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 11.7 lbs per square foot

NOMINAL THICKNESS: 1-1/8"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 7 Paragraph 4.9
- One Hour Fire Rating Per ASTM E119-98
- Class IV Forced Entry Protection Rating Per ASTM F1233-98
- Sound Insulation Rating Per ASTM E413-87

AMMUNITION TESTED:

5.56mm rifle full copper jacket, lead core – 55 grain, 3.56 grams, minimum 3080 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO Interbankx COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace Panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.



UL752 Level 8

PANEL SIZES: 3' x 8', 3' x 9', 3' x 10'
4' x 8', 4' x 9', 4' x 10'
5' x 8', 5' x 9', 5' x 10'
Custom sizes available

NOMINAL WEIGHT: 15.2 lbs per square foot

NOMINAL THICKNESS: 1-7/16"

PRODUCT APPLICATIONS:

Interbankx Bullet Resistant Panels can be used in walls, furniture, doors, vehicles and as blast protection barriers. They can be covered with drywall or laminate so as not to impact aesthetics.

Commercial

- Banks and credit unions
- Convenience stores
- Check cashing facilities
- Data centers

Government

- Courthouses/courtrooms
- Prisons
- Administrative offices
- Public safety facilities

Healthcare

- Hospitals and clinics
- Pharmacies

Residential

- Safe rooms
- Storm shelters

Military

- Transport vehicles
- Housing
- Base entrances

OTHER PRODUCTS AVAILABLE: Interbankx Bullet Resistant Fiberglass Panels are manufactured at all 8 Levels of UL752 Standards and NIJ0108.01 specifications.

SUBMITTALS:

Submittals and samples are available upon request.

PERFORMANCE LEVEL:

- UL752 Standard for Bullet Resisting Equipment – Level 8 Paragraph 4.10
- National Institute of Ballistic Standards NIJ0108.01 – Level III
- One Hour Fire Rating Per ASTM E119-98
- Class IV Forced Entry Protection Rating Per ASTM F1233-98
- Sound Insulation Rating Per ASTM E413-87

AMMUNITION TESTED:

7.62mm rifle lead core full metal copper jacket, military ball – 150 grain, 9.7 grams, minimum 2750 feet per second.

PRODUCT INFORMATION:

The panels are made of multiple layers of woven roving ballistic grade fiberglass cloth impregnated with a thermoset polyester resin and compressed into flat rigid sheets. The production technique and materials used provide the controlled internal delamination to permit the capture of a penetrating projectile.

PRODUCT BENEFITS:

- Easy to install
- Effective delay against forced entry
- Low wicking – preventing buildup of mold
- Nontoxic materials – no formaldehyde

UNIQUE TO INTERBANK COMPOSITES:

- ISO 9001-2000 registered
- Superior customer service
- Continuous product testing to ensure ballistic integrity
- Factory CNC water jet cutting

PRODUCT INSTALLATION:

We suggest using a diamond-grit blade for cutting the material. A TSD180D 7" Tenryu circular blade is available for purchase through our office. Panels may be attached using self-tapping drywall screws or construction adhesive. Pre-drilling may be required for thicknesses 1.125" or greater. With proper pre-preparation, panels can be painted with oil or water based paints. Installation instructions are available upon request.

All joints need to be reinforced by a 4" batten strip.

WARRANTY POLICY:

All materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site. We will repair or replace panels at our discretion, found upon our inspection, to be defective in material or our workmanship for up to two (2) years from the date of receipt at the project site.