

# LED Type C Tubes Retrofit

## CERTIFICATIONS



## PRODUCT FEATURES



### Construction

- Shatterproof, frosted glass
- Double-end input

### Applications

- Retail
- Office
- Healthcare
- Education
- Various commercial applications

### Warranty

7-Year Limited Warranty  
(Optional 10-Year Warranty available)

## BENEFITS

- Ideal for customers with older fluorescent ballasts who want to maximize efficiency, but don't want to install Type B linear voltage retrofit lamps.
- Our External Drive LED system can be integrated with robust dimming and control functionality.
- Offers high system efficacy, guaranteed system compatibility, and the greatest overall performance. Best of all, Type C LED tubes are eligible for unique rebate opportunities.



SPECIFICATIONS	
Available Wattage	13W - 60W
Available CCT	4000K - 5000K
Efficacy Average	138 LM/W - 140 LM/W
Lumen Output	1,800 LM - 8,400 LM
Input Voltage	AC100-277V
Input Frequency	50/60HZ
CRI	>80
Power Factor	0.9
THD	> 16%
Working Temp	-20F to 113F (-20C to 45C)
Lens	Frosted
IP Rating	IP20
Dimming	Yes w/Driver
Life Span (Hours)	>70,000



# LED Type C Tubes Retrofit

Order Code	DLC Model #	Wattage	Number of Tubes	CCT	LM/Watt	Total LM	Voltage
<b>4 FOOT - NON-DIMMABLE</b>							
13940	MES-RTC113D-40	13W	1 Tube	4000K	138 LM/W	1,800 LM	100-277V
13941	MES-RTC113D-50	13W	1 Tube	5000K	138 LM/W	1,800 LM	100-277V
13942	MES-RTC115D-40	15W	1 Tube	4000K	140 LM/W	2,100 LM	100-277V
13943	MES-RTC115D-50	15W	1 Tube	5000K	140 LM/W	2,100 LM	100-277V
13944	MES-RTC226D-40	26W	2 Tube	4000K	138 LM/W	3,600 LM	100-277V
13945	MES-RTC226D-50	26W	2 Tube	5000K	138 LM/W	3,600 LM	100-277V
03909	MES-RTC230D-40	30W	2 Tube	4000K	140 LM/W	4,200 LM	100-277V
03910	MES-RTC230D-50	30W	2 Tube	5000K	140 LM/W	4,200 LM	100-277V
03948	MES-RTC452D-40	52W	4 Tube	4000K	138 LM/W	7,200 LM	100-277V
03949	MES-RTC452D-50	52W	4 Tube	5000K	138 LM/W	7,200 LM	100-277V
03918	MES-RTC460D-40	60W	4 Tube	4000K	140 LM/W	8,400 LM	100-277V
03919	MES-RTC460D-50	60W	4 Tube	5000K	140 LM/W	8,400 LM	100-277V



## 4 FOOT - DIMMABLE

13965	MES-RTC113D-40	13W	1 Tube	4000K	138 LM/W	1,800 LM	100-277V
13966	MES-RTC113D-50	13W	1 Tube	5000K	138 LM/W	1,800 LM	100-277V
13967	MES-RTC115D-40	15W	1 Tube	4000K	140 LM/W	2,100 LM	100-277V
13968	MES-RTC115D-50	15W	1 Tube	5000K	140 LM/W	2,100 LM	100-277V
13969	MES-RTC226D-40	26W	2 Tube	4000K	138 LM/W	3,600 LM	100-277V
13970	MES-RTC226D-50	26W	2 Tube	5000K	138 LM/W	3,600 LM	100-277V
13971	MES-RTC230D-40	30W	2 Tube	4000K	140 LM/W	4,200 LM	100-277V
13972	MES-RTC230D-50	30W	2 Tube	5000K	140 LM/W	4,200 LM	100-277V
13973	MES-RTC452D-40	52W	4 Tube	4000K	138 LM/W	7,200 LM	100-277V
13974	MES-RTC452D-50	52W	4 Tube	5000K	138 LM/W	7,200 LM	100-277V
13975	MES-RTC460D-40	60W	4 Tube	4000K	140 LM/W	8,400 LM	100-277V
13976	MES-RTC460D-50	60W	4 Tube	5000K	140 LM/W	8,400 LM	100-277V

↑ When placing your order, please use **Order Code**.



# LED Type C Tubes Retrofit

## DIMENSIONS



SIZE	A	B	C
2 FT	23.7"	19.7"	1.0"
4 FT	47.2"	43.2"	1.0"

## CONTROLS

Order Code	Description	Height	Voltage	Color	Version	Function
06210	3-in-1 Microwave Fixture Embedded w/ Detachable Sensor	19ft	120-277V	White	Standard	3-in-1
06278	LED Intelligent Remote Control	-	-	White	Standard	LCD Display

