

LED Vapor Tight Fixture

CERTIFICATIONS







PRODUCT FEATURES









Construction

Fully gasketed polycarbonate housing with captive stainless steel latches

Applications

- Gym
- Warehouse
- Parking garage
- Damp locations

Mounting

- Cable suspension
- Surface mounting

Warranty

7-Year Limited Product Warranty (Optional 10-Year Warranty available)

BENEFITS

- Designed to be used in moisture-filled or harsh settings, durable housing that resists warping, fading, corrosion, and rust.
- Impact resistant lens
- Use half the energy of fluorescents, lowering energy cost.



SPECIFICATIONS			
Available Wattage	32W		
Available CCT	3000K, 4000K, 5000K		
Efficacy Average	130 LM/W		
Lumen Output	4,160 LM		
Input Voltage	AC100-277V		
Input Frequency	50/60HZ		
CRI	>80		
Power Factor	0.9		
THD	>15%		
Working Temp	-22F TO 122F (-22C TO 50C)		
Lens	Frosted		
IP Rating	IP65		
Dimming	Yes		
Life Span (Hours)	>70,000		




LED Vapor Tight Fixture


Order Code	DLC Model #	Wattage	ССТ	LM/Watt	Total LM	Voltage
DIMMABLE						
02521	MES-VAP-4FT-32W-40	32W	4000K	130 LM/W	4,160 LM	100-277V
02522	MES-VAP-4FT-32W-50	32W	5000K	130 LM/W	4,160 LM	100-277V
DIMMABLE	CCT TUNABLE					
02523*	MES-VAP-4FT-32W-50	32W	3000K 4000K 5000K	130 LM/W	4,160 LM	100-277V

When placing your order, please use **Order Code**.

PHOTOMETRIC DATA



Cone Chart





Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



LED Vapor Tight Fixture

DIMENSIONS





A	В	С	D
49.8"	33.9"	3.3"	3.1"

LIGHTING CONTROLS

Order Code	Description	Height	Voltage	Color	Version	Function
06450	LED PIR Fixture Mounted Sensor	49ft	120-277V	White	Standard	Simple On/Off
06221	LED Microwave Fixture Mounted Sensor	19ft	120-277V	White	Standard	3-in-I
06222	LED Microwave Fixture Mounted Sensor	49ft	120-277V	White	Standard	3-in-l
06225	LED Microwave Fixture Mounted Sensor	49ft	347-480V	White	Standard	3-in-l
06278	LED Intelligent Remote Control	-	-	White	Standard	LCD Display

