



MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

PRODUCT: VF-220
MANUFACTURER: VIBRA FINISH CO. VIBRA FINISH CO.
ADDRESS: 2220 N. Shasta Way 8411 Seward Road
 Simi Valley, CA 93065 Hamilton, OH 45011
TELEPHONE: (800) 635-0259 (800) 253-1941

DESCRIPTION: Burnishing Compound
CHEMICAL FAMILY: NA
FORMULA: Proprietary mixture
EMERGENCY TELEPHONE NUMBER: CHEMTREC (800) 424-9300 or (800) 635-0259
NFPA RATING: Health: 1 Fire: 1 Reactivity: 0
 NFPA Hazard Rating: Extreme: 4 High: 3 Moderate: 2 Slight: 1 Insignificant: 0
MSDS ORINATION DATE: 10/23/2002 **REVISION DATE:** 12/04/2008

SECTION II - HAZARDOUS INGREDIENTS/MIXTURES

<u>MATERIAL or COMPONENT</u>	<u>CAS No.</u>	<u>PERCENT</u>	<u>TLV/ACGIH</u>
Sodium dodecyl benzene sulfonic acid	25155-30-0	< 5	10 mg/m ³

SECTION III - PHYSICAL DATA

BOILING POINT:.....ND
 MELTING POINT:ND
 VAPOR PRESSURE (mm Hg):.....NA
 VAPOR DENSITY (Air = 1):.....NA
 PERCENT VOLATILE BY VOLUME:.....NA
 AUTOIGNITION TEMPERATURE:.....NA
 FORM.....Solid
 SOLUBILITY IN WATER:.....Completely
 BULK DENSITY (g/mL).....0.7 – 0.8
 APPEARANCE:.....Off-white free flowing powder
 ODOR:.....Odorless

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (TEST METHOD): NA

EXTINGUISHING MEDIA: Product will smolder and slowly burn if ignited. Use standard fire fighting media, including foam, carbon dioxide, water spray, or dry chemical extinguishers.

SPECIAL FIRE FIGHTING PROCEDURES: When this product is involved in a fire, firefighters should wear protective clothing and self-contained breathing apparatus to avoid exposure to vapors or products of combustion.

UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers may develop explosive pressures under fire conditions. Use a water spray to cool.

SECTION V - HEALTH HAZARD INFORMATION

EFFECTS OF OVEREXPOSURE:

SKIN: Prolonged contact with the skin may be irritating.

EYES: Contact with the dust can be irritating to the eyes.

INGESTION: This product is an irritant to the gastrointestinal system and may cause nausea and vomiting.

INHALATION: Breathing of dust may cause irritation to the upper respiratory tract and the lungs.

EMERGENCY AND FIRST AID PROCEDURES:

SKIN: Flush the skin with flowing water and discontinue exposure. Remove contaminated clothing and launder before reuse.

EYES: Flush the eyes with plenty of water for 15 minutes, alternately lifting the upper and lower eyelids. After 5 minutes, if appropriate, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Get medical attention if irritation develops or persists.

INGESTION: Rinse mouth and drink several glasses of water. Induce vomiting and get medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove victim to fresh air. If breathing is difficult, have a trained person administer oxygen. Get immediate medical attention.

SECTION VI - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: High temperatures, fires, and incompatibles.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: High temperatures and flames may form toxic oxides of carbon, boron and sulfur.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate respirator, clothing and gloves. Small spill: sweep, scoop or vacuum spilled material into approved containers. Large spill: scooped into approved containers for reuse or disposal.

WASTE DISPOSAL METHOD: Dispose of waste in approved containers according to Federal, State, and Local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type): NIOSH/MSHA approved respirator where dust, mist, or spray may exist.

VENTILATION: Not required under normal use.

PROTECTIVE GLOVES: Natural or butyl rubber gloves are recommended for sensitive individuals or those experiencing long contact.

EYE PROTECTION: Wear chemical goggles or full-face shield.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep in cool place away from strong oxidizing agents. Keep containers dry and sealed to avoid caking.

OTHER PRECAUTIONS: Because of dust formation, use grounded explosion proof equipment during bulk transfers. Solutions formed from this product can be very slippery. Use caution to avoid slipping hazard.

SECTION X – REGULATORY INFORMATION

This product is not considered carcinogen or cancer suspect under NTP, IARC and OSHA.

SARA Title III Section 313 (Toxic Chemicals): None listed.

SARA Title III Section 302 (Extremely Hazardous Substances): None listed

SUPERFUND REPORTABLE QUANTITY CHEMICAL: Sodium dodecylbenzene sulfonate (CAS# 25155-30-0) (RQ = 1,000 lb)

CAL-OSHA Directors List of Hazardous Materials: Sodium dodecylbenzene sulfonate (CAS# 25155-30-0)

SUPERFUND “REPORTABLE QUANTITY” CHEMICALS: Sodium dodecyl benzene sulfonic acid (CAS 25155-30-0)

SARA Title III Section 302 (Extremely Hazardous Substances): None listed.

U.S. DOT PROPER SHIPPING NAME: Not regulated.

LABEL: NA

NA: not applicable ND: not determined

VIBRA FINISH company cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information, either alone in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.