

T3 / T4 / T5

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T4 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity of the chassis and gives an outstanding appearance.



MAXIMUM UPTIME

Quality Permco hydraulic spinner motors and 2000 series conveyor motor drive the productivity and simplicity of this machine. Hydraulic drive translates to more flexibility and reliability thanks to less moving parts allowing the operator to get on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce positive and consistent product feed of all materials in all conditions, while the simplicity renders to less maintenance.



EASE OF USE

The Hansa H5 controller does all the work, simply enter the desired rate, bout width and spinner speed from the comfort of your cab and let the computer do the rest, say goodbye to the ways of jockey wheels, complicated charts and guess work.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	12.5/80-18 Industrial tyres ● 550/60 22.5 Flotation tyres ○
TARP	900 grade rollover ○
LOAD CELLS	When selected with ISOBUS rate controller auto rate calibration is enabled ○
RATE CONTROLLER	HANSA H5 controller (5" Touch screen) ● ISOBUS (auto rate calibration) ○ HANSA H7 controller (7" Touch screen) ○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers) ○
SIDE DELIVERY CONVEYOR	Single or dual delivery ○
AXLE	Single Series 80 BPW 8/285 ● (track options of 1600 or 1800mm)

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
5500 kg

 **SPREAD WIDTH**
Urea 24m / SSP 30m

T3	T4	T5
CAPACITY		
3,000L	4,000L	5,000L
TARE WEIGHT		
1,680kg	1,740kg	1,800kg
LOADING HEIGHT		
1,810mm	1,980mm	2,150mm
UREA CAPACITY		
2,250kg	3,000kg	3,750kg
LIME CAPACITY		
4,000kg	5,000kg	5,500kg

BIN LENGTH
2,950mm

OVERALL LENGTH
5,150mm

BIN WIDTH
1,800mm

STANDARD WHEEL TRACK
1,600mm

CONVEYER WIDTH
750mm wide

OIL FLOW
40L/min

WARRANTY
3 years