

L SERIES

Features and Benefits



WEIGHT DISTRIBUTION

The Hansa L series features a unique connection that allows the spreader to sit much closer to the tractor aiding in weight distribution and essentially allowing larger payloads to be carried with less front weight on the tractor.



BUILT FOR THE LONGHAUL

The one piece stainless steel body is integrated with its frame, eliminating the chance of corrosion and extending the overall life of the spreader unit.



SPREAD IT ALL

The unique design of the Hansa L series uses a conveyor to deliver the product to the spinners, a lot of R&D has gone into the bin shape to ensure that bridging does not occur with the wide range of products the unit is able to spread, ranging from urea to lime.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TARP	900 gsm rollover tarp	○
RATE CONTROLLER	ISOBUS Hansa H5 controller (5" Touch screen) Hansa H7 controller (7" Touch screen)	○ ○ ○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS)	○
MUDGUARDS	Detachable 2 ply	○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
8,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

	L2	L2.5	L3
CAPACITY	2,000L	2,500L	3,000L

LOADING HEIGHT	1,680mm	1,750mm	1,850mm
-----------------------	---------	---------	---------

UREA CAPACITY	1,500kg	1,800kg	2,250kg
----------------------	---------	---------	---------

LIME CAPACITY	2,500kg	3,200kg	4,000kg
----------------------	---------	---------	---------

	L4	L5	L6
CAPACITY	4,000L	5,000L	6,000L

LOADING HEIGHT	2,000mm	2,150mm	2,300mm
-----------------------	---------	---------	---------

UREA CAPACITY	3,000kg	3,750kg	4,500kg
----------------------	---------	---------	---------

LIME CAPACITY	5,000kg	6,000kg	7,500kg
----------------------	---------	---------	---------

BIN LENGTH
1,700mm

OVERALL LENGTH
2,300mm

BIN WIDTH
2,800mm

CONVEYER WIDTH
750mm wide

OIL FLOW
80L/min

WARRANTY
12 months