

# T10

## Features and Benefits




### BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T10 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T10 outperforms expectations.



### BUILT FOR COMFORT

The T10 is built for comfort and ease of use, with a rubber cushioned drawbar suspension as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



### PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



### ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



## Inclusions & Options

Inclusions ●  
Optional ○

<b>TYRES</b>	Harvest 23.1/26 Trojan tyres	●
	Michelin or Harvest 650/65 R30.5 tyres	○
	Harvest 650/65 R42 HR45 R1 tyres	○
	Mitas 480/80 R34 tyres	○
<b>TARP</b>	900 gsm rollover tarp	○
<b>LOAD CELLS</b>	When selected with ISOBUS rate controller auto rate control is enabled	○
<b>RATE CONTROLLER</b>	ISOBUS (auto rate calibration)	○
	Hansa H7 controller (7" Touch screen)	○
<b>SECTION CONTROL</b>	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
<b>AXLE</b>	Single series 150 ADR 10/335 (track options of 2,000mm, 2,200mm & 3,000mm)	●
<b>BRAKES</b>	Hydraulic	○

## Specifications

 **MAX PAYLOAD**  
12,000 kg

 **SPREAD WIDTH**  
Urea 36m / SSP 50m

**CAPACITY**  
9,500L

**TARE WEIGHT**  
4,150kg

**LOADING HEIGHT**  
2,800mm

**UREA CAPACITY**  
7,000kg

**LIME CAPACITY**  
12,000kg

**BIN LENGTH**  
4,000mm

**OVERALL LENGTH**  
6,850mm

**BIN WIDTH**  
2,300mm

**STANDARD WHEEL TRACK**  
2,000mm

**CONVEYER WIDTH**  
750mm wide

**OIL FLOW**  
130L/min

**WARRANTY**  
12 months

A full range of options are available upon request