

T8

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T8 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T8 outperforms expectations.



MAXIMUM UPTIME

The full hydraulic drive system featuring quality Permco Spinner motors and 2000 series conveyor motor means simply plugging in and going to work. Minimal grease points and required maintenance translates to simply getting on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

		Inclusions <input checked="" type="radio"/>	Optional <input type="radio"/>
TYRES	Harvest 23.1/26 R1 tractor tyres	<input checked="" type="radio"/>	<input type="radio"/>
	Harvest 600/60 R26.5 floatation tyre	<input type="radio"/>	<input type="radio"/>
	Michelin 600/55 R30.5 CargoBib flotation tyre	<input type="radio"/>	<input type="radio"/>
TARP	900 gsm rollover tarp	<input type="radio"/>	<input type="radio"/>
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	<input type="radio"/>	<input type="radio"/>
RATE CONTROLLER	ISOBUS (auto rate calibration)	<input type="radio"/>	<input type="radio"/>
	Hansa H5 controller (5" Touch screen)	<input type="radio"/>	<input type="radio"/>
	Hansa H7 controller (7" Touch screen)	<input type="radio"/>	<input type="radio"/>
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	<input type="radio"/>	<input type="radio"/>
AXLE	Single series 100 ADR 10/335 (track options of 1,600mm, 1,800mm, 2,000mm, 2,200mm & 3,000mm)	<input checked="" type="radio"/>	<input type="radio"/>
BRAKES	Hydraulic	<input type="radio"/>	<input type="radio"/>

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
10,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY
8,000L

TARE WEIGHT
2,450kg

LOADING HEIGHT
2,450mm

UREA CAPACITY
6,000kg

LIME CAPACITY
10,000kg

BIN LENGTH
3,800mm

OVERALL LENGTH
6,350mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
1,800mm

CONVEYER WIDTH
750mm wide

OIL FLOW
95L/min

WARRANTY
2 years