

# T15

## Features and Benefits



### BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T15 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T15 outperforms expectations.



### BUILT FOR COMFORT

The T15 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



### PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



### ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



## Inclusions & Options

		Inclusions ●	Optional ○
<b>TYRES</b>	Alliance 331 600/60 R30.5 floatation tyre	<input type="radio"/>	<input type="radio"/>
	Harvest 600/65 R28 tractor tyre	<input checked="" type="radio"/>	<input type="radio"/>
	Michelin VF CFO+ 520/80 R26 tractor tyre	<input type="radio"/>	<input type="radio"/>
	Michelin CARGOXBIB 650/60 R30.5 floatation tyre	<input type="radio"/>	<input type="radio"/>
	Michelin MACHXBIB 600/70 R28 tractor tyre	<input type="radio"/>	<input type="radio"/>
<b>TARP</b>	900 gsm rollover tarp	<input type="radio"/>	<input type="radio"/>
<b>LOAD CELLS</b>	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	<input type="radio"/>	<input type="radio"/>
<b>RATE CONTROLLER</b>	ISOBUS (auto rate calibration)	<input type="radio"/>	<input type="radio"/>
	Hansa H7 controller (7" Touch screen)	<input type="radio"/>	<input type="radio"/>
<b>SECTION CONTROL</b>	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	<input type="radio"/>	<input type="radio"/>
<b>AXLE</b>	Tandem 150mm Square Axle Beam, with Rear Steerable Axle (track options of 2,500mm & 3,000mm)	<input checked="" type="radio"/>	<input type="radio"/>
<b>BRAKES</b>	Hydraulic	<input type="radio"/>	<input type="radio"/>

A full range of options are available upon request

## Specifications

 **MAX PAYLOAD**  
20,000 kg

 **SPREAD WIDTH**  
Urea 36m / SSP 50m

**CAPACITY**  
14,000L

**TARE WEIGHT**  
6,200kg

**LOADING HEIGHT**  
3,000mm

**UREA CAPACITY**  
11,000kg

**LIME CAPACITY**  
18,000kg

**BIN LENGTH**  
5,100mm

**OVERALL LENGTH**  
7,900mm

**BIN WIDTH**  
2,400mm

**STANDARD WHEEL TRACK**  
2,400mm

**CONVEYER WIDTH**  
750mm wide

**OIL FLOW**  
140L/min

**WARRANTY**  
12 months