

SERIES/MODEL	LENGTH (CM)	TIP	WIDTH	TAIL	RADIUS	TIP ROCKER	CAMBER	TAIL ROCKER	TIP HEIGHT (MM)	TAIL HEIGHT (MM)	WEIGHT SKI (G)	BMP	BMP DISTANCE FROM TRUE CENTER (MM)	BMP NEW SCHOOL	BMP PROGRESSIVE	BMP CLASSIC	DRILL SPECIFICATION
<b>PRODIGY 0.0</b>	150	117	85	109	R 12m	T 285	C 3	T 230	63	50	1610	692	58	+30	+15	0	4.1 x 9mm
	157	117	85	109	R 13m	T 300	C 3	T 240	63	50	1660	724	61	+30	+15	0	4.1 x 9mm
	164	117	85	109	R 15m	T 310	C 3	T 250	63	50	1710	757	63	+30	+15	0	4.1 x 9mm
	171	117	85	109	R 16m	T 325	C 3	T 260	63	50	1760	789	66	+30	+15	0	4.1 x 9mm
<b>PRODIGY 1.0</b>	164	120	88	112	R 15m	T 290	C 3	T 230	64	50	1580	755	65	+30	+15	0	4.1 x 9mm
	171	120	88	112	R 16m	T 300	C 3	T 240	64	50	1640	788	67	+30	+15	0	4.1 x 9mm
	178	120	88	112	R 17m	T 315	C 3	T 250	64	50	1750	820	70	+30	+15	0	4.1 x 9mm
	184	120	88	112	R 19m	T 325	C 3	T 260	64	50	1800	848	72	+30	+15	0	4.1 x 9mm
<b>PRODIGY 2.0</b>	159	127	98	119	R 12m	T 320	C 3	T 255	70	56	1600	728	67	+30	+15	0	4.1 x 9mm
	165	127	98	119	R 14m	T 330	C 3	T 265	70	56	1690	755	70	+30	+15	0	4.1 x 9mm
	171	127	98	119	R 16m	T 340	C 3	T 275	70	56	1750	783	72	+30	+15	0	4.1 x 9mm
	177	127	98	119	R 18m	T 355	C 3	T 285	70	56	1810	810	75	+30	+15	0	4.1 x 9mm
	183	127	98	119	R 20m	T 365	C 3	T 295	70	56	1860	838	77	+30	+15	0	4.1 x 9mm
	189	127	98	119	R 21m	T 380	C 3	T 300	70	56	1950	866	79	+30	+15	0	4.1 x 9mm
<b>PRODIGY 3.0</b>	172	133	106	125	R 17m	T 380	C 3	T 300	72	57	1910	782	78	+30	+15	0	4.1 x 9mm
	178	133	106	125	R 19m	T 390	C 3	T 310	72	57	1970	809	81	+30	+15	0	4.1 x 9mm
	184	133	106	125	R 20m	T 405	C 3	T 325	72	57	2100	836	84	+30	+15	0	4.1 x 9mm
	190	133	106	125	R 22m	T 420	C 3	T 335	72	57	2200	864	86	+30	+15	0	4.1 x 9mm
<b>PRODIGY 4.0</b>	179	140	116	132	R 20m	T 430	C 3	T 345	74	58	2050	805	90	+30	+15	0	4.1 x 9mm
	185	140	116	132	R 22m	T 445	C 3	T 355	74	58	2200	832	93	+30	+15	0	4.1 x 9mm
	191	140	116	132	R 24m	T 460	C 3	T 370	74	58	2280	860	95	+30	+15	0	4.1 x 9mm
<b>PRODIGY 0.0X</b>	143	117	85	109	R 11m	T 270	C 3	T 220	63	50	1560	659	56	+30	+15	0	4.1 x 9mm
	150	117	85	109	R 12m	T 285	C 3	T 230	63	50	1610	692	58	+30	+15	0	4.1 x 9mm
	157	117	85	109	R 13m	T 300	C 3	T 240	63	50	1660	724	61	+30	+15	0	4.1 x 9mm
	164	117	85	109	R 15m	T 310	C 3	T 250	63	50	1710	757	63	+30	+15	0	4.1 x 9mm
<b>PRODIGY 1.0X</b>	158	120	88	112	R 13m	T 280	C 3	T 220	64	50	1500	729	61	+30	+15	0	4.1 x 9mm
	164	120	88	112	R 15m	T 290	C 3	T 230	64	50	1580	755	65	+30	+15	0	4.1 x 9mm
	171	120	88	112	R 17m	T 300	C 3	T 240	64	50	1640	788	67	+30	+15	0	4.1 x 9mm
<b>PRODIGY 2.0X</b>	159	127	98	119	R 12m	T 320	C 3	T 255	70	56	1600	727	68	+30	+15	0	4.1 x 9mm
	165	127	98	119	R 14m	T 330	C 3	T 265	70	56	1690	755	70	+30	+15	0	4.1 x 9mm
	171	127	98	119	R 16m	T 340	C 3	T 275	70	56	1750	783	72	+30	+15	0	4.1 x 9mm
<b>PRODIGY 3.0X</b>	164	133	106	125	R 15m	T 370	C 3	T 370	72	57	1750	746	74	+30	+15	0	4.1 x 9mm
	172	133	106	125	R 17m	T 380	C 3	T 380	72	57	1840	782	78	+30	+15	0	4.1 x 9mm
	178	133	106	125	R 19m	T 390	C 3	T 390	72	57	1910	809	81	+30	+15	0	4.1 x 9mm
<b>PRODIGY 0.0 JR 0.0X JR</b>	113	110	78	102	R 7m	T 215	C 2	T 215	50	38	1410	520	45	+30	+15	0	3.6 x 7mm
	123	112	80	104	R 8m	T 235	C 2	T 235	50	38	1460	564	51	+30	+15	0	3.6 x 7mm
	133	114	82	106	R 10m	T 255	C 2	T 255	50	38	1510	610	55	+30	+15	0	3.6 x 7mm
<b>PRODIGY 1.0 JR</b>	125	115	84	111	R 9m	T 220	C 2	T 200	46	40	1140	602	23	0	-15	-30	3.6 x 7mm
	135	115	84	111	R 10m	T 220	C 2	T 200	46	40	1190	650	25	0	-15	-30	3.6 x 7mm
	145	115	84	111	R 12m	T 250	C 2	T 230	46	40	1250	699	26	0	-15	-30	3.6 x 7mm
	155	115	84	111	R 14m	T 250	C 2	T 230	46	40	1310	747	28	0	-15	-30	4.1 x 9mm
<b>PRODIGY 2.0 YTH</b>	139	125	94	121	R 11m	T 270	C 2	T 250	56	50	1290	669	26	0	-15	-30	3.6 x 7mm
	149	127	96	123	R 12m	T 270	C 2	T 250	56	50	1350	718	27	0	-15	-30	3.6 x 7mm
	159	129	98	125	R 14m	T 300	C 2	T 280	62	50	1410	766	29	0	-15	-30	4.1 x 9mm

SERIES/MODEL	LENGTH (CM)	TIP	WIDTH	TAIL	RADIUS	TIP ROCKER	CAMBER	TAIL ROCKER	TIP HEIGHT (MM)	TAIL HEIGHT (MM)	WEIGHT SKI (G)	BMP	BMP DISTANCE FROM TRUE CENTER (MM)	BMP NEW SCHOOL	BMP PROGRESSIVE	BMP CLASSIC	DRILL SPECIFICATION
<b>CT 1.0</b>	164	120	88	112	R 15m	T 290	C 3	T 230	66	60	1580	772	18	0	-15	-30	4.1 x 9mm
	171	120	88	112	R 16m	T 300	C 3	T 240	66	60	1640	806	19	0	-15	-30	4.1 x 9mm
	178	120	88	112	R 17m	T 315	C3	T 250	66	60	1750	841	19	0	-15	-30	4.1 x 9mm
	184	120	88	112	R 19m	T 325	C 3	T 260	66	60	1800	870	20	0	-15	-30	4.1 x 9mm
<b>CT 2.0</b>	166	131	102	127	R 16m	T 330	C 2	T 295	68	62	1690	798	32	0	-15	-30	4.1 x 9mm
	173	131	102	127	R 18m	T 340	C 2	T 305	68	62	1750	831	34	0	-15	-30	4.1 x 9mm
	178	131	102	127	R 19m	T 350	C 2	T 315	68	62	1800	856	34	0	-15	-30	4.1 x 9mm
	183	131	102	127	R 20m	T 360	C 2	T 325	68	62	1880	880	35	0	-15	-30	4.1 x 9mm
	188	131	102	127	R 21m	T 370	C 2	T 335	68	62	1950	904	36	0	-15	-30	4.1 x 9mm
<b>CT 3.0</b>	172	140	112	134	R 17m	T 375	C 2	T 335	70	64	1820	798	47	0	-15	-30	4.1 x 9mm
	178	140	112	134	R 20m	T 390	C 2	T 350	70	64	1900	840	50	0	-15	-30	4.1 x 9mm
	184	140	112	134	R 21m	T 400	C 2	T 360	70	64	1990	868	52	0	-15	-30	4.1 x 9mm
	190	140	112	134	R 23m	T 415	C 2	T 370	70	64	2080	897	53	0	-15	-30	4.1 x 9mm
<b>CT 5.0</b>	183	148	122	140	R 22m	T 410	C 0	T 365	72	65	2050	865	50	0	-15	-30	4.1 x 9mm
	190	148	122	140	R 24m	T 410	C 0	T 365	72	65	2150	895	55	0	-15	-30	4.1 x 9mm
<b>CT 2.0 x</b>	166	131	102	127	R 16m	T 330	C 2	T 295	68	62	1690	764	31	0	-15	-30	4.1 x 9mm
	173	131	102	127	R 18m	T 340	C 2	T 305	68	62	1750	798	32	0	-15	-30	4.1 x 9mm
<b>CT 3.0 x</b>	165	140	112	134	R 17m	T 360	C 2	T 330	70	64	1740	798	47	0	-15	-30	4.1 x 9mm
	172	140	112	134	R 20m	T 415	C 2	T 360	70	64	1820	840	50	0	-15	-30	4.1 x 9mm
<b>CT 1.0 JR</b>	125	115	84	111	R 9m	T 220	C 2	T 200	46	40	1140	602	23	0	-15	-30	3.6 x 7mm
	135	115	84	111	R 10m	T 220	C 2	T 200	46	40	1190	650	25	0	-15	-30	3.6 x 7mm
	145	115	84	111	R 12m	T 250	C 2	T 230	46	40	1250	699	26	0	-15	-30	3.6 x 7mm
	155	115	84	111	R 14m	T 250	C 2	T 230	46	40	1310	747	28	0	-15	-30	4.1 x 9mm
<b>CT 2.0 YTH</b>	139	125	94	121	R 11m	T 270	C 2	T 250	56	50	1290	669	26	0	-15	-30	3.6 x 7mm
	149	127	96	123	R 12m	T 270	C 2	T 250	56	50	1350	718	27	0	-15	-30	3.6 x 7mm
	159	129	98	125	R 14m	T 300	C 2	T 280	56	50	1410	766	29	0	-15	-30	4.1 x 9mm
<b>DICTIONATOR 1.0</b>	162	120	86	110	R 14m	T 280	C 4	T 170	64	24	1550	712	98	+30	+15	0	4.1 X 9mm
	170	120	86	110	R 16m	T 290	C 4	T 175	64	24	1650	749	101	+30	+15	0	4.1 X 9mm
	178	120	86	110	R 18m	T 310	C 4	T 180	64	24	1700	786	104	+30	+15	0	4.1 X 9mm
	186	120	86	110	R 20m	T 320	C 4	T 190	64	24	1840	823	107	+30	+15	0	4.1 X 9mm
<b>DICTIONATOR 2.0</b>	163	127	96	117	R 15m	T 320	C 4	T 190	68	25	1660	709	106	+30	+15	0	4.1 X 9mm
	171	127	96	117	R 17m	T 330	C 4	T 200	68	25	1770	745	110	+30	+15	0	4.1 X 9mm
	179	127	96	117	R 19m	T 360	C 4	T 210	68	25	1850	782	113	+30	+15	0	4.1 X 9mm
	187	127	96	117	R 21m	T 360	C 4	T 220	68	25	2000	818	117	+30	+15	0	4.1 X 9mm
<b>DICTIONATOR 3.0</b>	164	134	106	124	R 16m	T 350	C 4	T 210	70	26	1890	715	105	+30	+15	0	4.1 x 9 mm
	172	134	106	124	R 18m	T 370	C 4	T 220	70	26	1970	750	110	+30	+15	0	4.1 X 9 mm
	180	134	106	124	R 21m	T 380	C 4	T 230	70	26	2100	786	114	+30	+15	0	4.1 X 9 mm
	188	134	106	124	R 23m	T 400	C 4	T 240	70	26	2150	823	117	+30	+15	0	4.1 X 9 mm
<b>DICTIONATOR 4.0</b>	179	141	116	131	R 21m	T 410	C 2	T 250	73	27	2080	772	123	+30	+15	0	4.1 X 9 mm
	185	141	116	131	R 23m	T 430	C 2	T 260	73	27	2100	798	127	+30	+15	0	4.1 X 9 mm
	191	141	116	131	R 25m	T 450	C 2	T 270	73	27	2250	825	130	+30	+15	0	4.1 X 9 mm
<b>DICTIONATOR 1.0X</b>	154	120	86	110	R 13m	T 270	C 4	T 160	64	24	1450	675	95	+30	+15	0	4.1 X 9 mm
	162	120	86	110	R 14m	T 280	C 4	T 170	64	24	1550	712	98	+30	+15	0	4.1 X 9 mm
	170	120	86	110	R 16m	T 290	C 4	T 175	64	24	1650	749	101	+30	+15	0	4.1 X 9 mm

SERIES/MODEL	LENGTH (CM)	TIP	WIDTH	TAIL	RADIUS	TIP ROCKER	CAMBER	TAIL ROCKER	TIP HEIGHT (MM)	TAIL HEIGHT (MM)	WEIGHT SKI (G)	BMP	BMP DISTANCE FROM TRUE CENTER (MM)	BMP NEW SCHOOL	BMP PROGRESSIVE	BMP CLASSIC	DRILL SPECIFICATION
<b>DICTATOR 2.0X</b>	155	127	96	117	R 14m	T 300	C 4	T 180	68	25	1580	672	103	+30	+15	0	4.1 X 9 mm
	163	127	96	117	R 15m	T 320	C 4	T 190	68	25	1660	709	106	+30	+15	0	4.1 X 9 mm
	171	127	96	117	R 17m	T 330	C 4	T 200	68	25	1800	745	110	+30	+15	0	4.1 X 9 mm
<b>DICTATOR 3.0X</b>	164	134	106	124	R 16m	T 350	C 4	T 210	70	26	1890	715	105	+30	+15	0	4.1 X 9 mm
	172	134	106	124	R 18m	T 370	C 4	T 220	70	26	1970	750	110	+30	+15	0	4.1 X 9 mm
<b>DICTATOR FG 1.0</b>	154	120	86	110	R 13m	T 270	C 4	T 160	64	24	1580	675	95	+30	+15	0	4.1 X 9 mm
	162	120	86	110	R 15m	T 280	C 4	T 170	64	24	1640	712	98	+30	+15	0	4.1 X 9 mm
	170	120	86	110	R 17m	T 290	C 4	T 175	64	24	1710	749	101	+30	+15	0	4.1 X 9 mm
	178	120	86	110	R 19m	T 310	C 4	T 180	64	24	1700	786	104	+30	+15	0	4.1 X 9 mm
	186	120	86	110	R 21m	T 320	C 4	T 190	64	24	1950	823	107	+30	+15	0	4.1 X 9 mm
<b>DICTATOR FG 2.0</b>	155	127	96	117	R 14m	T 300	C 4	T 180	68	25	1660	672	103	+30	+15	0	4.1 X 9 mm
	163	127	96	117	R 16m	T 320	C 4	T 190	68	25	1720	709	106	+30	+15	0	4.1 X 9 mm
	171	127	96	117	R 18m	T 330	C 4	T 200	68	25	1800	745	110	+30	+15	0	4.1 X 9 mm
	179	127	96	117	R 20m	T 360	C 4	T 210	68	25	1800	782	113	+30	+15	0	4.1 X 9 mm
	187	127	96	117	R 22m	T 360	C 4	T 220	68	25	2010	818	117	+30	+15	0	4.1 X 9 mm
<b>DICTATOR 2.0YTH</b>	137	119	88	109	R 10m	T 240	C 4	T 180	60	23	1400	592	93	+30	+15	0	3.6 X 7 mm
	146	123	92	113	R 12m	T 280	C 4	T 180	63	24	1500	633	97	+30	+15	0	3.6 X 7 mm
	155	127	96	117	R 14m	T 300	C 4	T 180	68	25	1610	672	103	+30	+15	0	4.1 X 9 mm
<b>AGENT 1.0</b>	162	120	86	110	R 14m	T 280	C 4	T 170	64	24	1310	712	98	+30	+15	0	4.1 X 9 mm
	170	120	86	110	R 16m	T 290	C 4	T 175	64	24	1330	749	101	+30	+15	0	4.1 X 9 mm
	178	120	86	110	R 18m	T 310	C 4	T 180	64	24	1490	786	104	+30	+15	0	4.1 X 9 mm
	186	120	86	110	R 20m	T 320	C 4	T 190	64	24	1540	823	107	+30	+15	0	4.1 X 9 mm
<b>AGENT 1.0X</b>	154	120	86	110	R 13m	T 270	C 4	T 160	64	24	1300	675	95	+30	+15	0	4.1 X 9 mm
	162	120	86	110	R 14m	T 280	C 4	T 170	64	24	1390	712	98	+30	+15	0	4.1 X 9 mm
	170	120	86	110	R 16m	T 290	C 4	T 175	64	24	1410	749	101	+30	+15	0	4.1 X 9 mm
<b>AGENT 2.0</b>	163	127	96	117	R 15m	T 320	C 4	T 190	68	25	1410	709	106	+30	+15	0	4.1 X 9 mm
	171	127	96	117	R 17m	T 330	C 4	T 200	68	25	1610	745	110	+30	+15	0	4.1 X 9 mm
	179	127	96	117	R 19m	T 360	C 4	T 210	68	25	1660	782	113	+30	+15	0	4.1 X 9 mm
	187	127	96	117	R 21m	T 360	C 4	T 220	68	25	1760	818	117	+30	+15	0	4.1 X 9 mm
<b>AGENT 2.0X</b>	155	127	96	117	R 14m	T 300	C 4	T 180	68	25	1320	672	103	+30	+15	0	4.1 X 9 mm
	163	127	96	117	R 16m	T 320	C 4	T 190	68	25	1410	709	106	+30	+15	0	4.1 X 9 mm
	171	127	96	117	R 18m	T 330	C 4	T 200	68	25	1610	745	110	+30	+15	0	4.1 X 9 mm
<b>AGENT 3.0</b>	164	134	106	124	R 16m	T 350	C 4	T 210	70	26	1580	715	105	+30	+15	0	4.1 X 9 mm
	172	134	106	124	R 18m	T 370	C 4	T 220	70	26	1680	750	110	+30	+15	0	4.1 X 9 mm
	180	134	106	124	R 21m	T 380	C 4	T 230	70	26	1740	786	114	+30	+15	0	4.1 X 9 mm
	188	134	106	124	R 23m	T 400	C 4	T 240	70	26	1810	823	117	+30	+15	0	4.1 X 9 mm
<b>AGENT 3.0X</b>	164	134	106	124	R 16m	T 350	C 4	T 210	70	26	1580	715	105	+30	+15	0	4.1 X 9 mm
	172	134	106	124	R 18m	T 370	C 4	T 220	70	26	1680	750	110	+30	+15	0	4.1 X 9 mm
	180	134	106	124	R 21m	T 380	C 4	T 230	70	26	1740	786	114	+30	+15	0	4.1 X 9 mm
<b>AGENT 4.0</b>	179	141	116	131	R 21m	T 410	C 4	T 250	73	27	1880	772	123	+30	+15	0	4.1 X 9 mm
	185	141	116	131	R 23m	T 430	C 4	T 260	73	27	1950	798	127	+30	+15	0	4.1 X 9 mm
	191	141	116	131	R 25m	T 450	C 4	T 270	73	27	1990	825	130	+30	+15	0	4.1 X 9 mm

SERIES/MODEL	LENGTH (CM)	TIP	WIDTH	TAIL	RADIUS	TIP ROCKER	CAMBER	TAIL ROCKER	TIP HEIGHT (MM)	TAIL HEIGHT (MM)	WEIGHT SKI (G)	BMP	BMP DISTANCE FROM TRUE CENTER (MM)	BMP NEW SCHOOL	BMP PROGRESSIVE	BMP CLASSIC	DRILL SPECIFICATION
<b>LE MONO</b>	182	235	188	195	R 24m	T 405	C 0	T 40	49	4	3610	776	134	+30	+15	0	4.1 X 9 mm
	190	240	192	199	R 26m	T 455	C 0	T 40	52	4	3760	800	150	+30	+15	0	4.1 X 9 mm
<b>LE MOGUL</b>	140	100	66	90	R 11m	T 220	C 5	T 130	50	15	1450	623	77	+30	+15	0	4.1 X 9 mm
	147	100	66	90	R 12m	T 220	C 5	T 130	50	15	1400	656	79	+30	+15	0	4.1 X 9 mm
	155	100	66	90	R 14m	T 220	C 5	T 130	50	15	1450	692	83	+30	+15	0	4.1 X 9 mm
	163	100	66	90	R 16m	T 220	C 5	T 130	50	15	1500	728	87	+30	+15	0	4.1 X 9 mm
	171	100	66	90	R 17m	T 220	C 5	T 130	50	15	1550	765	90	+30	+15	0	4.1 X 9 mm
	179	100	66	90	R 19m	T 220	C 5	T 130	50	15	1600	802	93	+30	+15	0	4.1 X 9 mm
<b>LA MACHINE</b>	178	151	126	137	R 24m	T 480	C 0	T300	70	35	1890	758	136	+30	+15	0	4.1 X 9 mm
	186	151	126	137	R 26m	T 480	C 0	T300	70	35	1950	794	136	+30	+15	0	4.1 X 9 mm