SolaSpot 1000

The Future is here



Powerful and compact, SolaSpot 1000 is the latest white LED spot fixture in High End Systems' revolutionary new SolaRange. Packed with innovative features and outputting 16,000 lumens, SolaSpot 1000 allows lighting designers complete creative freedom and unprecendented control.

SolaSpot 1000 includes a rotating gobo wheel, a rotating Animation wheel, linear prism, iris, frost, fixed color wheel and a CMY + CTO system which designers have been raving about. Specially designed optics allow sharp focus to be achieved throughout the entirety of the II to 45 degree zoom range.

The fixture includes many other exclusive patented High End Systems' technologies such as Active Thermal Control and Lens Defog System. The future is here ... and brighter than ever before.



FI	ΕA	lΤU	RE	S
LE	D	Тур	е	
LE	D	Eng	jine	e C

Dutput Lumens

Lumens

LED Hours CRI

Colour Temperature

CMY Linear CTO

Fixed Color Wheel

Rotating Gobo Wheel Fixed Gobo Wheel

Iris

Animation Prism

Frost

Zoom Auto Focus Function

Active Thermal Control Fan Modes

Lens Defog System RDM Compatible Roadcase included

OPERATION

Pan Tilt Max Speed Pan [360 Degrees]

Max Speed Tilt (252 Degrees) Auto Switching Power Supply 5 Pin DMX/ RDM Connector

ArtNet

True 1 Connector

CONSTRUCTION

Modular Construction Electronic Cooling System Control Pan and Tilt Locks

Yoke Arm Handles

ELECTRICAL/PHYSICAL/COMPLIANCE

Electrical Power Rating Compliance Operating Temperature Range Storage Temperature Range Fixture Dimensions (inches) Fixture Dimensions (mm) Fixture Weight [lbs] Fixture Weight (kg)

Road Case Dimensions (inches) Road Case Dimensions [mm]

Gross Road Case Weight (lbs)

Gross Road Case Weight (kg)

440 W Bright White Engine

26,000*

16,000*

>70% Luminous output: 50,000 hours >75

6500

Yes Yes

7 + Open

6 + Open

7 + Open Yes

Rotating Linear

Yes

11 to 35 degrees Yes

Yes

Normal, Constant, Studio

Yes Yes

Single

540 265

2.27s 1.31s

Yes

Yes Yes

Yes

Yes

Yes Yes

ETL, CE

63

28.6

150

68

23 x 24 x 37

584x 610x 940

100-240VAC @ 50-60Hz

32 to 113°F/ O to 45°C

0 to 140°F/ -20 to 60°C

15.4 x 12.7 x 28.6 391 x 324 x 726

100-240VAC, 7 - 2.9 amps

Yes





HIGH END SYSTEMS an ETC. Company

highend.com

Patents Pending

Specifications Subject to Change Without Notice

Two year product warranty and technical support

* Lumens as measured by Everfine 2.0 integrating sphere and PMS-80 Spectrophotometer. Calibration date March 3rd 2014