

# avenir<sup>®</sup>

## Technical Specifications

VERSION 2022.03



# Classic

Heated & Non-Heated Towel Rails

## VARIATIONS

| Heated Version | Non-Heated Version | Height x Width | Rails  | Watts/rail |
|----------------|--------------------|----------------|--------|------------|
| TRH8-90        | Use heated version | 900 x 50mm     | 1 to 6 | 24 Watts   |
| TRH8-90RH      | Use heated version | 900 x 145mm    | 1 to 6 | 24 Watts   |




## NOTES

- This is a Low Voltage product - Safe to be installed in Zone 1 (wet areas)
- Transformer required - TRTR100-24V - Max 3 rails (Sold separately)
- Wire specifications: Use flexible multistrand 1mm<sup>2</sup> - Do not exceed 5 meters in length.

## STANDARD FINISHES

|  |   |  |  |  |
|--|---|--|--|--|
| <b>Mirror Polished</b><br>Stainless Steel<br>RRP | <b>Brushed</b><br>Stainless Steel<br>+20% (Stocked) | <b>Matt Black/White</b><br>Painted<br>+40% (Stocked) | <b>Brushed / Polished</b><br>Raw Brass<br>+20% (Stocked) | <b>Brushed Gold</b><br>PVD<br>+60% (Stocked) |
|--|---|--|--|--|

## SPECIFICATIONS

|  |   |  |
|--|---|--|
| <b>Voltage</b><br>24 Volts                                 | <b>Standards</b><br>AS/NZ 60335.2.43                            | <b>DEVELOPED IN AUSTRALIA</b>   |
| <b>Material</b><br>Brass                                   | <b>Electrical Connection</b><br>Concealed Wiring only - top leg | <b>HEATING TIME 30 MINUTES</b>  |
| <b>Finish</b><br>Mirror Polished                           | <b>Heating Method</b><br>Dry Internal Heating Element           | <b>WARRANTY 10 YEAR</b>         |
| <b>Ingress Protection</b><br>IPX5 (Suitable for wet areas) | <b>Required / Sold Separately</b><br>Transformer (TRTR100-24V)  |  |

