

Technical Specifications

VERSION 2022.01





Therm 4

Heated & Non-Heated Towel Rails

VARIATIONS

Heated Version	Non-Heated Version	Height x Width	Rails	Wattage
TLH9-55 x 40	TLN9-55 x 40	550 x 428 mm	4	35 Watts
TLH9-55 x 48	TLN9-55 x 48	550 x 508 mm	4	40 Watts
TLH9-55 x 60	TLN9-55x60	550 x 628 mm	4	45 Watts
TLH9-55 x 75	TLN9-55 x 75	550 x 778 mm	4	50 Watts
TLH9-55 x 90	TLN9-55 x 90	550 x 928 mm	4	60 Watts

NOTES

- This is a 240VAC product Earth connection is ESSENTIAL
- Safe to be installed in Zone 1 (wet areas)
- Concealed wiring available through any of the 4 legs
- Wire specifications: Use flexible multistrand 1.5mm²
- Non Heated version available (Less \$50)
- Plug-In version available (Plus \$50)


STANDARD FINISHES

Mirror Polished	Brushed	Matt Black	Gunmetal	Brushed Gold
Stainless Steel	Stainless Steel	Painted	PVD	PVD
RRP	+20% (Stocked)	+40% (Stocked)	+50% (Stocked)	+60% (Stocked)

SPECIFICATIONS

Voltage 240 Volts	Standards AS/NZ 60335.2.43
Material	Electrical Connection
Stainless Steel 304	Concealed Wiring std - any leg
Finish	Heating Method
Mirror Polished	Dry Internal Heating Element
Ingress Protection	Options
IPX5 (Suitable for wet areas)	Non Heated, Plug-In







VARIATIONS

Heated Version	Non-Heated Version	W1 (Fixings)	W2 (Overall)
TLH9-55x40	TLN9-55x40	400mm	438mm
TLH9-55x48	TLN9-55x48	480mm	518mm
TLH9-55x60	TLN9-55x60	600mm	638mm
TLH9-55x75	TLN9-55x75	750mm	788mm
TLH9-55x90	TLN9-55x90	900mm	938mm