



Xylo | Bathroom Accessories

avenir®



Toilet Roll Holder
Shown here right facing
height 30 / width 130 / depth 75
XYSTRH-LF (Left Facing)
XYSTRH-RF (Right Facing)



Horizontal Toilet Roll Holder
height 36 / width 30 / depth 115
XYSTRH-HZ



Double Toilet Roll Holder
Shown here right facing
height 30 / width 240 / depth 80
XYDTRH-LF (Left Facing)
XYDTRH-RF (Right Facing)



Spare Paper Holder
height 310 / width 30 / depth 80
XYSPH



Horizontal Hand Towel Rail
height 36 / width 30 / depth 300
XYHTR-HZ



Hand Towel Rail
Shown here right facing
height 30 / width 310 / depth 80
XYHTR-LF (Left Facing)
XYHTR-RF (Right Facing)



Robe Hook
height 36 / width 20 / depth 35
XYRH



Single Towel Rail
height 30 / depth 75
XYSTR230 (width 230)
XYSTR350 (width 350)
XYSTR450 (width 450)
XYSTR650 (width 650)
XYSTR900 (width 900)



Double Towel Rail
height 30 / depth 140
XYDTR650 (width 650)
XYDTR900 (width 900)



Towel Rack
height 30 / depth 315
XYTR450 (width 450)
XYTR600 (width 600)




Soap Dish
Polished Solid Surface
height 20 / width 110 / depth 90
XYSD




Shelf
Polished Solid Surface
height 20 / depth 120
XYSH300 (width 300)
XYSH450 (width 450)
XYSH600 (width 600)
XYSH750 (width 750)
XYSH900 (width 900)




Heated Towel Rails
height 30 / depth 75
TRH5-45x3 (width 450)
TRH5-65x3 (width 650)
TRH5-90x3 (width 900)




Through Glass Fixing Kit
XYZTGFK
(10 mm hole required)



Glue Only Fixing Kit
XYZGOFK



Plasterboard Fixing Kit
XYZPLFK



Xylo accessories come standard with our unique Double Fixing System, which includes a precision drilling fixture and a diamond drill bit to effortlessly and accurately drill holes through even the hardest of vitrified tiles. In addition, all products ship with high quality Hilti® wall plugs, stainless steel screws and a tube of epoxy glue for a secure and enduring installation. Standard installation system suitable for tiled or masonry walls only. Optional fixings for Glass, Plasterboard and a Glue-Only installation (No drilling) are available on request.