



# NetVanta 3205

## Modular Access Router Supporting up to Two T1s Worth of Bandwidth

### Product Features

- Modular Network Interface Module (NIM) offering flexibility
- Modular Dial Backup Interface Module (DIM) guaranteeing bandwidth
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay sensitive traffic like VoIP
- Command Line Interface (CLI) mimics industry *de facto* standard
- Optional DSX-1 interface supplies TDM voice transport
- Comprehensive PPP dial backup scheme prevents network downtime
- VLAN Trunking (802.1Q) for routing between VLANs
- Network Address Translation (NAT) for IP Address Concealing
- Optional VPN for secure corporate connectivity across the Internet
- Built-in DSU/CSU for circuit protection
- NetVanta 3205 DC NEBS III compliant
- Feature-rich ADTRAN Operating System (AOS)
- Industry-leading five-year North American warranty

The NetVanta® 3000 Series of modular access routers are designed for cost-effective Internet access, corporate Frame Relay, point-to-point connectivity, ADSL, and Virtual Private Networking (VPN). The NetVanta 3000 Series currently consists of the NetVanta 3200, 3205, and 3305 with a variety of interchangeable Network Interface Modules (NIMs) and Dial Backup Modules (DIMs).

#### Modular Hardware

The NetVanta 3205 is a single-slot, single-Ethernet 1U high, rackmountable metal enclosure. A single slot within any of the NetVanta 3000 Series will house a variety of NIMs and DIMs, which include a 56/64k, T1/FT1, T1/FT1 with DSX-1, Dual T1s, E1/FE1, E1/FE1 with G.703, ADSL, or a Serial interface. For dial backup an Analog Modem, an ISDN BRI, or Serial DIM is available for preventing downtime by dialing around a failed circuit to any PPP compliant device.

#### Standard-based Protocols

The versatile hardware platform of the NetVanta 3205 is further complemented with the ADTRAN® Operating System (AOS). AOS allows for the support of static and default routes, demand routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, and RIP. In addition, AOS terminates Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, and HDLC WAN protocols. Multihoming is also available to provide redundant or backup WAN links to multiple ISPs, guaranteeing a wide-area connection.

#### Security

For added security, AOS provides a powerful, high performance stateful inspection firewall. It will examine all incoming and outgoing packets against the security policies established by the IT manager. In addition, the firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems. With the AOS Enhanced Feature Pack Upgrade, the NetVanta 3000 Series adds the support for IPSec compliant VPN. The NetVanta 3205 supports up to five simultaneous

VPN tunnels, while supporting encryption algorithms like DES, 3DES, and AES. With this upgrade, the NetVanta 3205 is fully compatible with other IPSec VPN equipped NetVanta products.

#### Quality of Service (QoS)

QoS is also supported for delay sensitive traffic like VoIP or video. To prioritize mission critical traffic and control network congestion, the NetVanta 3205 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

#### VoIP Ready

In combination with the QoS features, a specialized SIP Application Layer Gateway (ALG) allows SIP traffic to traverse NAT-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

#### Administration

AOS offers a standard Command Line Interface (CLI) that mimics the widely adopted, industry *de facto* standard. The sequence of commands to configure similar devices is almost identical, virtually eliminating training costs associated with re-learning a new operating system or costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded for a quick and easy recovery mechanism. In addition, an intuitive Web-based GUI provides step-by-step configuration wizards, management capability, and the ability to upload firmware updates.

ADTRAN, the leader in WAN connectivity, offers reliable equipment that increases network performance, lowers cost, and positions networks for the future. The NetVanta 3000 Series is no exception. In addition, these products are backed by an industry-leading five-year North American warranty, free firmware downloads, and world-class 24-hour technical support from ADTRAN.





ADTRAN, Inc.  
Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000 voice  
256 963-8699 fax

**General Information**  
800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales**

**Technical Support**  
800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales**

**Technical Support**  
888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation & Maintenance Service**

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**International Inquiries**

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

**For the regional office nearest you, visit:**

www.adtran.com/regional

For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

61202870L1-8E 14.1 November 2006  
Copyright © 2005 ADTRAN, Inc.  
All rights reserved.

# NetVanta® 3205



## Modular Access Router Supporting up to Two T1s Worth of Bandwidth

### Physical Interface

- **NIM:** 56/64k, T1/FT1, T1/FT1 with DSX-1, Dual T1, E1/FE1, E1/FE1 with G.703, ADSL, and Serial
- **DIM:** Analog Modem, ISDN BRI (U and S/T), and Serial
- **LAN:** Auto-sensing 10/100Base-T Full Duplex (RJ-45)
- Console Port

### Diagnostics LEDs

- Power
- **WAN:** link, transmit, receive
- **LAN:** link, transmit, receive
- **Dial backup:** transmit and receive

### Processor and Memory

- Motorola MPC 866
- 120 MHz

### Security

#### Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

#### Network Address Translation

- Basic NAT (1:1), NAT (Many:1), and 1:1 Port Translation
- NAT compatible SIP ALG

#### Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

#### Optional Virtual Private Network (VPN)

- **IPSec Tunnel Mode:** 5 Tunnels
- **Encryption:** DES, 3DES, and AES
- **Diffie Hellman Group Support:**
  - Group 1: MODP 768
  - Group 2: MODP 1024
- **Hash Algorithms:** MD5-HMAC and SHA1-HMAC
- **Authentication Mechanisms:**
  - XAUTH
  - Secure ID
  - X.509 Digital certificates
  - DSS Signatures
  - Preshared keys

- **Key Management:** IKE (ISAKMP/Oakley)
- **IKE Modes:**
  - Main
  - Aggressive
  - Perfect Forward Secrecy
  - Mode Config

- Dead Peer Detection
- NAT Traversal V2

### Quality of Service (QoS)

- Class-based Weighted Fair Queuing, Low Latency, and Weighted Fair Queuing
- DiffServ Packet Marking and Recognition
- Frame Relay Fragmentation

### Protocols

- eBGP/iBGP
- OSPF
- RIP (v1 and v2)
- Demand Routing
- GRE
- IGMP v2
- ATM (ADSL)
- Frame Relay
- Multilink Frame Relay
- PPP
- PPPoE
- PPPoA
- RFC 1483
- Multilink PPP
- HDLC
- PPP Dial Backup
- PAP and CHAP
- Multihoming

### Frame Relay

- Point-to-point
- RFC 1490 Encapsulation (Multiprotocol Over Frame Relay)
- LMI types: LMI, ANSI (Annex D), CCITT (Annex A) and Static

### DHCP

- Client, Server, and Relay

### Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command® support
- SNMP v3
- SYSLOG logging
- Email alerts (SMTP)
- Policy statistics

### Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

### Physical

- **Chassis:** 1U, rackmountable metal enclosure
- **Dimensions:** 1.25" H, 17.25" W, 7.75" D
- **Weight:** 7 lbs.
- **AC Power:** 100-250 VAC, 50/60 Hz, 6 watts max. (1202870L1)
- **DC Power:** -48 +24 VDC, 6 W max. (1200980L1)

### Agency Approvals

- FCC Part 68
- Industry Canada CS03
- UL and Canadian UL (CUL), IEC/EN, CSA
- CE Mark

## Ordering Information

Equipment	Part #
<b>Systems</b>	
NetVanta 3205 Chassis DC (NEBS III)	1202980L1
NetVanta 3205 Chassis AC	1202870L1
with 56/64k NIM	4200871L1
with T1/FT1 NIM	4200872L1
with T1/FT1+DSX-1 NIM	4200873L1
NetVanta 3205 Chassis with VPN	4200870L2
VPN Software Upgrade	1950860L2

ADTRAN, n-Command, and NetVanta are registered trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Content subject to change without notice.