

ACETONE - SOAK OFF SOLUTION

Page: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: ACETONE - Soak-off Solution

Product code: Acetone Nail Remover

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC39: Cosmetics, personal care products.

## 1.3. Details of the supplier of the safety data sheet

Company name: Glitter Planet Itd

Unit 3b, bridge water court

Bentley wood way, network 65 business park

Hapton BB11 5ST ENGLAND

ENGLAND

web: www.glitterplanetuk.com
Email: info@glitterplanetuk.com

## 1.4. Emergency telephone number

Emergency tel: 24-hour emergency call NHS helpline on 111 or if using outside UK then contact

local emergency services.

# Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; -: EUH066

### Most important adverse effects:

### 2.2. Label elements

Label elements:

Hazard statements:

#### Hazard pictograms:

Causes serious eye irritation. May cause drowsiness or dizziness. Highly flammable liquid and vapour. Repeated exposure may cause skin dryness or cracking.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

#### ACETONE - SOAK-OFF SOLUTION

Page: 2

H225: Highly flammable liquid and vapour.

EUH066: Repeated exposure may cause skin dryness or cracking.

GHS02: Flame

GHS07: Exclamation mark





[cont...]

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

## 3.2. Mixtures

### Hazardous ingredients:

## **ACETONE**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	>75%

Contains: See full INCI listing available for individual shades

### Section 4: First aid measures

# 4.1. Description of first aid measures

#### Skin contact:

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

ACETONE - SOAK-OFF SOLUTION

Page: 3

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Headaches or general

malaise may result. Nausea and stomach pain may occur. The casualty may appear

intoxicated. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing. Drowsiness or mental confusion may occur.

### 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

## Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

### ACETONE - SOAK-OFF SOLUTION

Page: 4

Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from direct sunlight. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

## 7.3. Specific end use(s)

Specific end use(s): PC39: Cosmetics, personal care products.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## **Hazardous ingredients:**

### **ACETONE**

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

Respirable dust

## **DNEL/PNEC Values**

## **ACETONE - VARIOUS**

Туре	Exposure	Value	Population	Effect
DNEL	Dermal; Long term	186mg/kg/day	Workers	-
DNEL	Inhalation; Short term	2420mg/m3	Workers	-
DNEL	Inhalation; Long term	1210mg/m3	Workers	-
DNEL	Oral; Long term	62mg/kg/day	Consumers	-
DNEL	Dermal; Long term	62mg/kg/day	Consumers	-
DNEL	Inhalation; Long term	200mg/m3	Consumers	-
PNEC	Fresh water	10.6mg/l	-	-
PNEC	Marine water	1.06mg/l	-	-
PNEC	Water	21mg/l	-	-
PNEC	Sediment	3.04mg/kg	-	-
PNEC	Soil	33.3mg/l	-	-
PNEC	STP	29.5mg/l	-	-

#### ACETONE - SOAK-OFF SOLUTION

Page: 5

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Butyl gloves. Breakthrough time of the glove material > 8 hours.

**Eye protection:** Safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing, rubber.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Various

Odour: Characteristic odour

Solubility in water: Soluble

Viscosity: Non-viscous

Melting point/range°C: -94.7 Flammability limits %: 2.5

lower:

upper: 14.3 Flash point°C: -17
Part.coeff. n-octanol/water: -0.24 Autoflammability°C: 465

Vapour pressure: 24.1 kPa Relative density: 0.79-0.82

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Hot surfaces. Sources of ignition. Flames.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents. Amines. Alkali metals. Alkali earth

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

# **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

### **Toxicity values:**

TOXIOITY VAIACO.	•			
Route	Species	Test	Value	Units
IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg
VAPOURS	RAT	LC50	76	mg/l

## **Hazardous ingredients:**

### **ACETONE**

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis		
Serious eye damage/irritation	OPT	Hazardous: calculated		
STOT-single exposure	-	Hazardous: calculated		

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Headaches or general

malaise may result. Nausea and stomach pain may occur. The casualty may appear

intoxicated. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing. Drowsiness or mental confusion may occur.

## Section 12: Ecological information

## 12.1. Toxicity

### **Ecotoxicity values:**

Species	Test	Value	Units	
BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l	

ACETONE - SOAK-OFF SOLUTION

Page: 7

Hazardous ingredients:

**ACETONE** 

BLUEGILL (Lepomis macrochirus) LC50 8300 mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

Persistence (P-):

Persistence result: not P-

Bioaccumulation (B-):

Bioconcentration factor (BCF): 3

Bioaccumulation result: not B-

Toxicity (T-):

**Toxicity result:** 

not T-

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1090

14.2. UN proper shipping name

ACETONE - SOAK-OFF SOLUTION

Page: 8

Shipping name: ACETONE (ACETONE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

ACETONE - SOAK OFF SOLUTION

Page: 9

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

## Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.

ACETONE - SOAK OFF SOLUTION

Page: 10 [final page]