

# Indoor / Outdoor VELVET LUXE

## Product Data Sheet



**Overview:** Our range of Velvet Luxe is a beautifully formulated **indoor and outdoor** Hybrid Chalk Paint that provides you with a smooth luxurious feel wrapped up in a contemporary matte velvety finish. A great all round premium paint with a fast dry time, no priming with little to no preparation along with advanced self levelling qualities for a smoother brushed luxurious finish. A self sealing paint with no requirement to wax or lacquer over the top.

It makes any paint project quick fast and easy allowing you to breathe colour and a luxurious finish into spaces quickly with just two coats of our Velvet Luxe. Durable and wipeable. Uniquely formulated for ease of use, it brushes and flows beautifully from the brush for a flat finish using its industry leading 20m<sup>2</sup>/litre coverage. Ideal for those who are after a flat one colour, matte contemporary finish.

### TYPICAL USES:

- For exterior/interior surfaces
- Outdoor Furniture
- Doors & cabinetry
- Furniture
- Decor
- Terracota Pots
- Windows sills, skirting, door jams
- Kitchens
- Metal

**Preparation:** Clean and ensure surface is dust free. For general varnished furniture or outdoor furniture & metals you can apply straight on after cleaning. For glossy surfaces or shiny melamine; key in the surface prior by giving it a quick sand with rough grit sand paper before application. Ensure that there is no wax on the surface, if so, remove all waxes prior to application.

**Application:** Stir well and thoroughly to ensure all quality pigments are evenly dispersed, apply with a flat Staalmester brush that is in proportion to the item being painted, we recommend Staalmester's range of flat brushes for best results. Load your paint up with your brush and spread out. Level off, by taking pressure off your brush and feathering and levelling out the paint. On some surfaces our Velvet Luxe will achieve full coverage after one coat, however we always recommend applying two coats for maximum strength.

**Dry time:** Touch dry in approx 30-40mins depending on climate and environment, do not use if temperature during application or drying is below 10°C. Re coat time of 1-2 hours ( 2 hours in cooler or high humidity environments) Curing time of 7 days .

**Take Care:** If painting for outdoors, paint on a clear day and where possible keep the item out of "heavy" rain during curing period . Be gentle during curing period. Darker colours may scuff during curing but can be wiped away with a damp cloth. If applying over teak test underneath first.

**Coverage:** Approx 20m<sup>2</sup> per litre on average depending on substrate, based on a brushed application.

**Maintenance:** Wipeable surface. Clean with water and damp cloth or with gentle cleaners.

**Wash Up:** Clean brushes immediately after use with warm soapy water.

**First Aid:** If swallowed, continuously rinse mouth with water. With eye contact irrigate eyes with water for 15 minutes and always seek immediate medical advice. Safety data sheets are available on request through our contact details on our website.

Our Velvet Luxe - Hybrid Chalk Paint is low in VOC's, with low toxicity, ensuring environmental issues are not compromised. Formulated using high quality ingredients together with leading technology in NZ for a Hybrid Chalk Paint that requires no waxing or lacquering and is suitable for both indoors and outdoors. Durable and wipeable, allowing you to create stunning decorative paint finishes that are not only beautiful but also highly functional both indoors and outdoors. Proudly designed and manufactured in NZ

**Disclaimer :** All information provided by or on behalf of The Artisan Company Ltd in relation to these products is provided in good faith and to the best of our knowledge and experience. We warrant that the product is fit for purpose however advice provided is without warranty as every substrate and environmental circumstances are different and can alter the final results; as such The Artisan Company Ltd is not responsible for user or application error. It is always recommended to test an area first prior to use. Safety Data Sheet is available upon request through our contact details on our website.