w: www.escapegear.co.za

### **TYPICAL DOUBLE CAB FITTING INSTRUCTIONS**





# **VERY IMPORTANT**

a.) PLEASE READ THESE INSTRUCTIONS CAREFULLY BEFORE COMMENCING WITH ANY FITMENT.

## TOOLS AND MATERIALS REQUIRED TO FIT

Clean hands, short fingernails and no open wounds.

### **CAUTION**

Ensure that your workmanship is of the highest professional standard and that you do not soil, scratch or damage the vehicle or accessory you are about to fit.

Ensure that you make provision for a clean area, to place components removed.



T: +27(21) 706-0440

e: orders@escapegear.co.za

w: www.escapegear.co.za

### INSTALLATION PROCEDURE - Remove all headrests and loosen all webbing straps and buckles on seat covers.



Passenger seat. Pull cover over seat bottom and feed three straps through gap between backrest and seat bottom.



Passenger seat. Feel for the straps at the bottom of the seat, pull it to the front and thread through every alternative buckle.



**Passenger seat.** Pull cover over seat backrest, feed three straps same as in step 1& 2, pull to the front and thread through remaining buckles.



Passenger seat. Position and smooth out covers to line up with the seat and tighten straps to hold seat covers secure.



Passenger seat. Thread left and right side webbing straps underneath the seat and attach to left and right buckles at back of squab cover. Tighten all webbing buckles and smooth out fabric for a neat finish. Driver's seat – as per Passenger's seat.



**Consol cover**. Carefully slide elasticized webbing to fit the underside of console.



**Consol cover**. Now fold the sides of the consol cover over and adjust for a neat fit.



**Rear bench seat**. Feed webbing straps down the back of the backrest.



**Rear bench seat.** Cover the backrest with the seat cover and lift seat bottom.



T: +27(21) 706-0440 e: <u>orders@escapegear.co.za</u>

### w: www.escapegear.co.za

# STEP 9

**Rear bench seat.** Remove safety belt from seat bottom straps and feed buckles through gap in the middle of the backrest and seat bottom.



Rear bench seat. Lift seat bottom completely, feel for the webbing straps behind backrest, thread through buckles and tighten securely. (Do not forget about the 2 side straps – again feel, thread and tighten securely).



Rear bench seat. Lower the seat bottom to cover with seat cover. Align black trim of seat cover with the edge of the seat and feed buckles through the gap in the middle of backrest and seat bottom.

STEP 12



Rear bench seat. Lift bench seat completely and thread webbing straps and buckles. NB. Before lowering the bench seat, be sure to put back the safety belt and clips through new strap on seat covers.



**Headrest covers**. When done fitting the seat covers replace all headrests and cover with headrests covers. Pull down for snug fit.

ENSURE THAT VEHICLE IS LEFT UNSCRATCHED, CLEAN & TIDY AND FREE OF ANY DUST, GRIME OR GREASE