

# SUSPENSION SETUP

## RAZE CARBON RR SL TRAIL

### Fork: Fox 36 29 Float GRIP2 Factory Kashima, 150mm

Follow Fox 36 Float GRIP2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Fox 36 Float GRIP2 Factory Kashima fork settings based on rider weight and Trail application:

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	psi	HSR	LSR	HSC	LSC
<121-128lbs / <55-58 kg	55	9	16	9	16
129,8-136,4lbs / 59-62 kg	59	8-7	15	8-7	15
138,6-145,2lbs / 63-66 kg	63	8-7	14	8-7	14
147,4-154lbs / 67-70 kg	67	7-6	13	7-6	13
156,2-162,8lbs / 71-74 kg	71	7-6	12	7-6	12
165-171,6lbs / 75-78 kg	75	6-5	11	6-5	11
173,8-180,4lbs / 79-82 kg	79	6-5	10	6-5	10
182,6-189,2lbs / 83-86 kg	83	5-4	9	5-4	9
191,4-198lbs / 87-90 kg	87	5-4	8	5-4	8
200,2-206,8lbs / 91-94 kg	91	4-3	7	4-3	7
209-215,6lbs / 95-98 kg	95	4-3	6	4-3	6
217,8-224,4lbs / 99-102 kg	99	3-2	5	3-2	5
226,6-233,2lbs / 103-106 kg	103	3-2	4	3-2	4
235,4-242lbs / 107-110 kg	107	2-1	3	2-1	3
244,2-250,8lbs / 111-114 kg	111	2-1	2	2-1	2
>253-319lbs / >115-145 kg	115	1	1	1	1

\*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

### Rear shock: Fox Float DPS Factory Kashima EVOL LV

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	100	open	11
129,8-136,4lbs / 59-62 kg	108	open	11-10
138,6-145,2lbs / 63-66 kg	116	open	11-10
147,4-154lbs / 67-70 kg	124	open	10-9
156,2-162,8lbs / 71-74 kg	132	open	10-9
165-171,6lbs / 75-78 kg	140	open	9-8
173,8-180,4lbs / 79-82 kg	148	open	9-8
182,6-189,2lbs / 83-86 kg	156	open	8-7
191,4-198lbs / 87-90 kg	164	open	8-7
200,2-206,8lbs / 91-94 kg	172	open	7-6
209-215,6lbs / 95-98 kg	180	open	7-6
217,8-224,4lbs / 99-102 kg	188	mid	6-5
226,6-233,2lbs / 103-106 kg	196	mid	4-3
235,4-242lbs / 107-110 kg	204	mid	3-2
244,2-250,8lbs / 111-114 kg	212	mid	2-1
>253-319lbs / >115-145 kg	220	mid	1

\*Settings based on Downhill application and 30-35% recommended sag