

DISTRIBUTED BY:



**MISSION
READY**
TRAFFIC + SAFETY

www.missionreadysafety.com

Product Specification Sheet

Product Name: **Park-It® Parking Curb**

Manufacturer: NoTrax®, Justrite Safety Group/GNR
5655 West 73rd St.
Bedford Park, IL 60638
Tel.: (800) 621-2802, Fax: (800) 322-7105

Product Description:

The nominal width and height of the Park-It® parking curb are 6 inches and 4 inches respectively. Three models available in the below nominal length and weight

36 inches	17 pounds
48 inches	22 pounds
72 inches	34 pounds

The rubber parking curb is outfitted with molded in reflective yellow or white tape for increased visibility.

Product Specifications:

1. Material: compression molded composite of recycled rubber and polyurethane binder.

2. Physical properties of the rubber composite:

a) Density	1.04 g/cu. cm	(ASTM C642)
b) Durometer Hardness	65A ± 7	(ASTM D2240)
c) Minimum Tensile Strength* (* main structural areas)	1.4 MPa	(ASTM D412)
d) Compression deformation	10% at 0.5 MPa, 68°F	(ASTM D575)
e) Brittleness at Low temperature:	-40°F	(ASTM D746)
f) Freeze and thaw when exposed to deicing chemicals	no loss after 50 cycles	(ASTM C672)
g) Coefficient of thermal expansion:	14.4 x10 ⁻⁶ m/m/°C	(ASTM C531)
h) Weathering 70 hours at 158°F		(ASTM D573)
- hardness retained	100% (± 5%)	
- compressive strength	100% (± 5%)	
- tensile strength	100% (± 5%)	
- elongation retained	100% (± 5%)	

3. Dimensions:

3-Foot Park-It®

width:	6 inches (+/- 0.11 inches)	152mm (+/- 3mm)
length:	36 inches (+/- 0.19 inches)	910mm (+/- 5mm)
height:	4 inches (+/- 0.11 inches)	102mm (+/- 3mm)

DISTRIBUTED BY:



**MISSION
READY**
TRAFFIC + SAFETY

www.missionreadysafety.com

4-Foot Park-It®

width:	6 inches (+/- 0.11 inches)	152mm (+/- 3mm)
length:	48 inches (+/- 0.19 inches)	1219mm (+/- 5mm)
height:	4 inches (+/- 0.11 inches)	102mm (+/- 3mm)

6-Foot Park-It®

width:	6 inches (+/- 0.11 inches)	152mm (+/- 3mm)
length:	72 inches (+/- 0.19 inches)	1929mm (+/- 5mm)
height:	4 inches (+/- 0.11 inches)	102mm (+/- 3mm)

4. Finishing: Black with molded in yellow or white durable reflective tape

5. Product contains: 95% of post- consumer materials and
5% of pre-consumer materials

Installation Method:

Installation on asphalt surfaces with rebar spikes 14" long (minimum diameter ½") (recommended installation).

36 inch (910mm) model	– 2 spikes for installation
48 inch (1219mm) model	– 3 spikes for installation
72 inch (1829mm) model	– 4 spikes for installation

For installation with spikes the 0.5 inch (12.5mm) diameter holes are drilled through the holes in the product into a paved road than the spikes are hammered in.

Installation on concrete surfaces with lag bolts 6" long (minimum diameter ½"), washer and shield

36 inch (910mm) model	– 2 lag bolts and shields for installation
48 inch (1219mm) model	– 3 lag bolts and shields for installation
72 inch (1829mm) model	– 4 lag bolts and shields for installation

For installation with lag bolts pilot holes 0.5 inch (12.5mm) are drilled through the product installation holes. The holes are re-drilled for a size required by the shields and the shields are installed. The product is then repositioned over the mounting holes and bolted down.

Warranty:

A three (3) years warranty is provided on the rubber composite and 1 year on the reflective tape if the product is installed as per manufacturer's installation instructions.

The rubber parking curbs are intended to be used for indoor or outdoor parking lots. Any other applications could be considered outside manufacturer warranty.

Please verify with the distributor or the manufacturer if the intended installation location is covered by warranty of the product.

Any warranty claims will be assessed by the product manufacturer after adequate information is provided.