

QUICK GUIDE

Installation

Your USPA comes with a U.S. standard 1/2" T valve with 3/8" compression optional conversion nut. A universal 7/8" T valve designed to fit directly to your toilet fill valve is also available by request. Please call customer support for assistance.

Silent Mode

Press & Hold on side panel for 3 sec to enable/disable beeping

- For detailed information, please refer to the Operating Instruction Manual.
- When you sit on the seat, the deodorizer will start automatically.
 - Please remove the plastic protective film on the remote before use

Drv

Press after wash cycle to blow warm air for 3 minutes



Starts Feminine wash. Double press to oscillate

Cleansing

Starts Posterior wash. Double press to oscillate

User Setting

Stop

Stop current function

Economy

To activate/deactivate the Power saving function





Water

Change water temperature

Seat

Change seat temperature

Massage

Press during wash cycle for massage

Kids

Defaults to low water pressure and extended nozzle position

A Auto

Press to initiate auto wash and dry sequence

Aerated spray, during wash cycle

: LED

Night light

Deodorization

When the appliance is in use, the deodorizer will work maximum 20 minutes automatically. Press on/off

■ Sound

Press the button to enable the beeping sound

REV.V1

Thank you for choosing Bio Bidet.

Our goal is to provide you with the highest-quality products and services possible.

If there is anything we can do to assist with your purchase, we have trained customer service professionals waiting to assist you. Connect with us! Email, chat, and phone are all available.

Also, if you have any suggestions or comments, I am also here to personally assist you.

Thank you again,





James Amburgey

Marketing Director at BioBidet









Address 7900 S IL Route 31 Crystal Lake IL 60014 Phone 847-458-2334 Fax 847-854-1296 Email James@biobidet.com

Website www.biobidet.com


Water Does It Better

Quick Installation Guide

Installation

■ How to mount the plate

Place the plate and guides over each mounting hole. Insert the mounting bolts through the plate and mounting holes, and slide cone packings and washers onto the bolts.




How to attach and detach the unit



Toilet size (elongated & round front)

■ The toilet dimensions must be within those shown below. Do not install this appliance on a toilet that does not meet those dimensional requirements.




Occupied sensor

■ This appliance is equipped with occupied sensor.

■ Unit will not work unless seat is occupied



Connecting the water hose



- Close the shutoff valve by turning it clockwise.
- Flush the water tank completely to empty.
- Remove the existing water supply hose from the tank.
- Install the T-valve on the top of stop valve.
- 5 Connect one end of the flexible hose from the T-valve to the water tank.
- 6 Connect the other end of the flexible hose from the T-valve to the main appliance.
- Connect L-Valve to the main unit.
- 8 Open the shutoff valve by turning it counter clockwise.
- Oheck for any water leaking or dripping.