CRC

SAFETY DATA SHEET

1. Identification

Product identifier Syntha-Tech™ Lubricant with PTFE

Other means of identification

Product code 03054

Recommended use Synthetic general purpose lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc. Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical
 800-521-3168

Assistance

Customer Service 800-272-4620 **24-Hour Emergency** 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2

Gases under pressure Compressed gas

Health hazards Acute toxicity, inhalation Category 4

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Harmful if inhaled. Harmful to aquatic life.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas. Avoid breathing mist or vapor. Avoid

release to the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled:

Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you

feel unwell.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

1.6% of the mixture consists of component(s) of unknown acute inhalation toxicity. 94.51% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

Material name: Syntha-Tech™ Lubricant with PTFE 1737 Version #: 01 Issue date: 02-25-2014

3. Composition/information on ingredients

Common name and synonyms	CAS number	%
	68649-11-6	30 - 40
	151006-58-5	30 - 40
	151006-62-1	5 - 10
	67-64-1	3 - 5
	124-38-9	1 - 3
	9002-84-0	< 1
	Common name and synonyms	68649-11-6 151006-58-5 151006-62-1 67-64-1 124-38-9

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Provide oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water.

Unsuitable extinguishing None known.
media

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Collect spillage. Dike far ahead of spill for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing vapor. Avoid breathing gas. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection

US. OSHA Table Z-1 Lim Components	Ty	•	-	alue	
Acetone (CAS 67-64-1)	PE	:L		-00 mg/m3	
0	DE	•1		000 ppm	
Carbon dioxide (CAS 124-38-9)	PE	:L	90	000 mg/m3	
121 00 0)			50	000 ppm	
US. ACGIH Threshold Li	mit Values				
Components	Ту	pe	Va	alue	
Acetone (CAS 67-64-1)	ST	EL	75	60 ppm	
	TV	٧A	50	00 ppm	
Carbon dioxide (CAS 124-38-9)	ST	EL	30	0000 ppm	
,	TV	VA	50	000 ppm	
US. NIOSH: Pocket Guid	e to Chemical Hazard	s			
Components	Ту	pe	Va	alue	
Acetone (CAS 67-64-1)	TV	VA	59	00 mg/m3	
			25	60 ppm	
Carbon dioxide (CAS 124-38-9)	ST	EL	54	000 mg/m3	
•			30	0000 ppm	
	TV	٧A	90	000 mg/m3	
			50	000 ppm	
ogical limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	

	· ·	-	_		
* .	- For sampling	details,	please see	the source	document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

Skin protection

Wear protective gloves such as: Viton®. Hand protection Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to Respiratory protection

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary. **General hygiene** considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Physical state Aerosol. **Form** Color White. Mild solvent. Odor Odor threshold Not available.

-138.5 °F (-94.7 °C) estimated Melting point/freezing point Initial boiling point and boiling 132.9 °F (56.1 °C) estimated

range

pН

253 °F (122.8 °C) Tag Closed Cup Flash point

Evaporation rate Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits 2.6 % estimated

Flammability limit - lower

(%)

Flammability limit - upper

12.8 % estimated

Not available.

(%)

1096.9 hPa estimated Vapor pressure

Vapor density 9 (air = 1)0.82 estimated Relative density Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature

590 °F (310 °C) estimated

Not available. **Decomposition temperature Viscosity (kinematic)** Not available. Percent volatile 97.1 % estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Hazardous decomposition

products

May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

May be fatal if swallowed and enters airways. Ingestion

Harmful if inhaled. Inhalation

Skin contact Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

May be fatal if swallowed and enters airways. Harmful if inhaled. **Acute toxicity**

Material name: Syntha-Tech™ Lubricant with PTFE 1737 Version #: 01 Issue date: 02-25-2014

Product Species Test Results

Syntha-Tech™ Lubricant with PTFE

Acute Dermal

LD50 Rabbit 2158.0562 mg/kg estimated

Inhalation

LC50 Rat 1.5086 mg/l, 4 hours estimated

Oral

LD50 Rat 2128.7759 mg/kg estimated TDL0 Human 59.1208 g/kg estimated

Chronic

Oral

NOEL Rat 1998.6731 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Polytetrafluoroethylene (CAS 9002-84-0) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Harmful to	o aquatic life.	
Product		Species	Test Results
Syntha-Tech™ Lubric	ant with PTFE		
Acute			
Crustacea	EC50	Daphnia	238.4485 mg/l, 48 hours estimated
Fish	LC50	Fish	2229.2813 ppm, 96 hours estimated
Components		Species	Test Results
Acetone (CAS 67-64-	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal of waste from residues / unused products The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in

accordance with all applicable regulations. Not regulated.

Contaminated packaging

Hazardous waste code

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. **Packing group**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 306 Packaging exceptions None Packaging non bulk Packaging bulk None

IATA

UN1950 **UN** number

UN proper shipping name Transport hazard class(es) Aerosols, flammable, Limited Quantity

2.1 Class Subsidiary risk

Not applicable. Packing group

Environmental hazards No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only

IMDG

UN number UN1950

UN proper shipping name Transport hazard class(es)

AEROSOLS, LIMITED QUANTITY

Class 2

Subsidiary risk Not applicable.

Packing group Environmental hazards

Marine pollutant No. F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

CERCLA Hazardous Substances: Reportable quantity

Acetone (CAS 67-64-1) 5000 lbs

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

US state regulations

US. New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1) Carbon dioxide (CAS 124-38-9)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Carbon dioxide (CAS 124-38-9)

US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1) Carbon dioxide (CAS 124-38-9) Polytetrafluoroethylene (CAS 9002-84-0)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

 Benzene (CAS 71-43-2)
 Listed: February 27, 1987

 Cumene (CAS 98-82-8)
 Listed: April 6, 2010

 Ethanal (CAS 75-07-0)
 Listed: April 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 93.1 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products This product is regulated as a Multi-Purpose Lubricant. This product is compliant in all 50 states.

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date02-25-2014Prepared byAllison Cho

Version # 01

country(s).

Further information CRC # 847A

HMIS® ratings Health: 1
Flammability: 2
Physical hazard

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 2 Instability: 0

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries.

Material name: Syntha-Tech™ Lubricant with PTFE 1737 Version #: 01 Issue date: 02-25-2014