CRO

SAFETY DATA SHEET

1. Identification

GHS product identifier 2-26 Multi-Purpose Precision Lubricant

Not available.

Product Code No. 92005 (Item# 1006872)

Version # 01

Issue date 04-05-2018

Recommended use Multi-purpose lubricant

Recommended Restrictions

Manufacturer

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

Customer Service 800-272-4620 **24-Hour Emergency** 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazards identification

GHS classification

Physical hazardsAerosolsCategory 2Health hazardsSkin corrosion/irritationCategory 3Aspiration hazardCategory 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

GHS label elements

Signal word Danger





Hazard statement Flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and

enters airways. Causes mild skin irritation. Toxic to aquatic life.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Avoid release to the environment.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If skin

irritation occurs: Get medical advice/attention.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information None.

3. Composition/information on ingredients

Material name: 2-26 Multi-Purpose Precision Lubricant

Components	CAS#	Percent
distillates (petroleum), hydrotreated light	64742-47-8	30 - 40
distillates (petroleum), hydrotreated middle	64742-46-7	30 - 40

No. 92005 (Item# 1006872) Version #: 01 Issue date: 04-05-2018

Components	CAS#	Percent
white mineral oil	8042-47-5	10 - 20
carbon dioxide	124-38-9	1 - 3
petrolatum	8009-03-8	1 - 3
sorbitan monooleate	1338-43-8	1 - 3
sorbitan monotallate	61791-48-8	1 - 3

4. First aid measures

First aid procedures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Wash off with soap and water. If skin irritation occurs: Get medical advice/attention. Take off Skin

contaminated clothing and wash before reuse.

Eye Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Mild skin irritation.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Notes to physician

Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to General advice

protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Protective equipment and precautions for firefighters

Protection of fire-fighters

General fire hazards

Specific methods

Water fog. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Containers should be cooled with water to prevent vapor pressure build up.

Flammable aerosol. Pressurized container may rupture when exposed to heat or flame.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods for containment

Methods for cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Ventilate the contaminated area. Wear appropriate protective equipment and clothing during clean-up. Prevent product from entering drains. Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Scrub the area with detergent and water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Wash contaminated clothing before reuse.

Storage

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls / personal protection

Control parameters

US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
white mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Color Amber.

Form Aerosol.

Odor Mild petroleum.
Odor threshold Not available.
pH Not available.

Melting point/Freezing point-56.2 °F (-49 °C) estimatedBoiling point212 °F (100 °C) estimatedFlash point> 212 °F (> 100 °C)

Evaporation rate Slow.

Flammability (solid, gas) Not available.
Flammability limits in air, 0.6 % estimated lower, % by volume

Material name: 2-26 Multi-Purpose Precision Lubricant

No. 92005 (Item# 1006872) Version #: 01 Issue date: 04-05-2018

Flammability limits in air,

upper, % by volume

5.5 % estimated

Vapor pressure

2463.4 hPa estimated

Vapor density Relative density

0.85 estimated

> 1 (air=1)

Solubility(ies)

Negligible. Solubility (water) Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature

428 °F (220 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available. 88.3 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Toxicological data				
Components	Species	Test Results		
distillates (petroleum), hydro	treated light (CAS 64742-47-8)			
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Inhalation				
LC50	Rat	> 20 mg/l, 4 hours		
Oral				
LD50	Rat	> 5000 mg/kg		
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)				
<u>Acute</u>				
Dermal				
LD50	Rat	> 2000 mg/kg		
Oral				
LD50	Rat	> 5000 mg/kg		
petrolatum (CAS 8009-03-8)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Inhalation				
LC50	Rat	> 20 mg/l, 4 hours		
Oral				
LD50	Rat	> 2000 mg/kg		
sorbitan monooleate (CAS 1	338-43-8)			
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Inhalation				
LC50	Rat	> 20 mg/l, 4 hours		

Material name: 2-26 Multi-Purpose Precision Lubricant

SDS GHS UN No. 92005 (Item# 1006872) Version #: 01 Issue date: 04-05-2018

Components **Species Test Results**

Oral

LD50 Rat 39800 mg/kg

sorbitan monotallate (CAS 61791-48-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 20 mg/l. 4 hours

Oral

LD50 Rat 39800 mg/kg

white mineral oil (CAS 8042-47-5)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 5 mg/l, 4 hours

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Toxicological information Occupational exposure to the substance or mixture may cause adverse effects.

Acute toxicity May be fatal if swallowed and enters airways.

Causes mild skin irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitizer Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

distillates (petroleum), hydrotreated middle (CAS

64742-46-7)

A4 Not classifiable as a human carcinogen.

petrolatum (CAS 8009-03-8) A4 Not classifiable as a human carcinogen. white mineral oil (CAS 8042-47-5) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

white mineral oil (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

Symptoms Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting.

Diarrhea. Mild skin irritation.

12. Ecological information

Ecotoxicological data Components **Test Results Species**

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Water flea (Daphnia pulex) Crustacea EC50 2.7 - 5.1 mg/l, 48 hours

Material name: 2-26 Multi-Purpose Precision Lubricant No. 92005 (Item# 1006872) Version #: 01 Issue date: 04-05-2018 Components **Species Test Results**

sorbitan monooleate (CAS 1338-43-8)

Aquatic Acute

LC50 Rainbow trout, donaldson trout Fish > 1000 mg/l, 96 hours

(Oncorhynchus mykiss)

Ecotoxicity Toxic to aquatic life.

Toxic to aquatic organisms. An environmental hazard cannot be excluded in the event of **Environmental effects**

unprofessional handling or disposal.

Persistence / degradability

Bioaccumulation

No data is available on the degradability of any ingredients in the mixture.

Toxic to aquatic organisms. **Aquatic toxicity Mobility** No data available for this product.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used

container.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

IATA

1950 **UN** number

Aerosols, flammable, Limited Quantity **UN proper shipping name**

Transport hazard class(es)

2.1 Class Subsidiary risk

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number

UN proper shipping name

Transport hazard class(es)

AEROSOLS, Limited Quantity

Class 2

Subsidiary risk Packing group

Environmental hazards

Not applicable.


Marine pollutant No. F-D. S-U

EmS

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code



15. Regulatory information

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Toxic Chemical Substances (TCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Further information

Disclaimer

CRC # 848A/1002826

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Material name: 2-26 Multi-Purpose Precision Lubricant
No. 92005 (Item# 1006872) Version #: 01 Issue date: 04-05-2018