

## **PRODUCT DATA SHEET**

Marine Boat Trailer and 4x4 Wheel Bearing Grease, 14 Wt Oz Part Number: SL3120

Product Description	A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.
Applications	Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Marine Grease for Boat Trailer
Net Fill	14 Wt Oz
UPC Code	072213312003
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	11 lbs
I 2 of 5 Code	30072213312004
Appearance	Blue Semi-Solid to Solid Grease
Base Type	Aluminum Complex
Flashpoint	>450°F
CPSC Flammability Class	None
Specific Gravity	0.9 at 60°F
NLGI Grade	2
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)
Working Temp	0 to 325°F

Last revised: 7/15/2015 Page 1 of 2



**BOAT TRAILER & MARINE EQUIPMENT** 

TI-PURPOS

Π

CRC \* Part No. SL3120 \* Net Wt. 14 oz. (3979) \*

Net we

Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com




 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$  and  $^{m}$  are trademarks of CRC Industries, Inc.



## **PRODUCT DATA SHEET**

Sta-Lube	
BOAT TRAILER & MARINE EQUIPMENT	

Drop Point	500°F
Leakage	5
Oxidation Stability	5
Pour Point	0°F
ISO Viscosity Grade	180
Water Washout	5
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0
VOC g/L (Federal)	0
VOC Lbs./Gal. (Federal)	0
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.
Worked Penetration Propellant DOT Proper Shipping Name VOC % (Federal) VOC g/L (Federal) VOC Lbs./Gal. (Federal) VOC Category	265 to 295 None Not Regulated O O O Not Regulated





Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



of CRC Industries, Inc.