

Specs

DETAILS

Platform Moterra Neo

Model Name Moterra 4

Model Code C65411U

FRAMESET

Frame 150mm travel, SmartForm C2 Alloy, Cannondale Tuned Suspension, removable downtube battery, internal cable routing, 148x12mm thru-axle, post mount

WHEELS

Rims WTB STX i25 TCS, 32h, tubeless ready

Spokes Stainless steel, 14g

Tire Size 2.6

Wheel Size 29

Hubs (F) Shimano MT400, 15x110mm thru-axle / (R) Shimano MT400, 12x148mm thru-axle

Tires Maxxis Rekon, 29x2.6", 60TPI Exo

Front Tire Maxxis Rekon, 29x2.6", 60TPI

	brake, tapered headtube
Fork	RockShox 35 Silver R, 150mm, Solo Air, 15x110mm stealth thru-axle, tapered steerer, 51mm offset
Headset	Integrated Sealed Bearing, Tapered
Rear Shock	RockShox Deluxe Select R, DebonAir

	Exo
Rear Tire	Maxxis Rekon, 29x2.6", 60TPI Exo

COMPONENTS

E-SYSTEM

Drive Unit	Shimano EP8
Battery	Shimano BT-E8036, 630Wh
Charger	Shimano Battery Charger 2A
Display	Shimano SC-EM800, Bluetooth enabled

Handlebar	Cannondale 3 Riser, 6061 Alloy, 15mm rise, 8° sweep, 4° rise, 780mm
Stem	Cannondale 3, 3D Forged 6061 Alloy, 1-1/8", 31.8, 7°
Grips	Fabric Funguy
Saddle	Cannondale Ergo XC
Seatpost	TranzX dropper, internal routing, 31.6, 100mm (S), 120mm (M), 130mm (L-XL)

DRIVETRAIN

Rear Derailleur	SRAM SX Eagle
Shifters	SRAM NX Eagle, 12-speed

Chain	SRAM SX Eagle, 12-speed
Crank	FSA E-Bike, 165mm, SRAM Eagle, 34T Steel
Rear Cogs	SRAM PG-1210, SX Eagle, 11-50, 12-speed

BRAKES

Brakes	TRP Slate G4 4 Piston hydraulic disc, 200/200mm rotors
Brake Levers	TRP hydraulic disc

PLEASE NOTE THAT, BASED ON COMPONENT
AVAILABILITY AND OTHER FACTORS,
SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT
NOTICE.