

Technical Specifications

Frameset

Frame

Alloy chassis and rear-end, asymmetrical design, 29 Trail Geometry, horst pivot BB adjustment, threaded BB, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel

Seat Binder

Alloy, 38.6mm

Suspension

Fork

RockShox 35 Silver, Solo Air, 44mm offset, rebound adjust, TurnKey lockout, 15x110mm Boost™ Maxle® Lite thru-axle, 140mm of travel

Rear Shock

X-Fusion 02 Pro RL, Rx Trail Tune, rebound adjust, lockout S1:190x42.5mm, S2-S6: 190x45mm

Cockpit

Stem

Alloy Trail Stem, 35mm bar bore

Saddle

Body Geometry Bridge Saddle, steel rails

Handlebars

Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width

SeatPost

TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm. S4-S5: 170mm, S6- 200mm

Grips

Specialized Trail Grips

Brakes

Rear Brake

Tektro Gemini Comp, hydraulic disc, resin pad, 180mm

Front Brake

Tektro Gemini Comp, hydraulic disc, resin pad, 200mm

Drivetrain

Chainrings

30T

Cassette

SRAM PG-1210 Eagle, 11-50t

Bottom Bracket

SRAM Powerspline

Rear Derailleur

SRAM SX Eagle, 12-speed

Chain

SRAM SX Eagle, 12-speed

Crankset

SRAM SX Eagle, S1:165mm, S2-S5: 170mm, S6: 175mm

Shift Levers

SRAM SX Eagle, trigger, 12-speed

Wheels & Tires

Rear Hub

Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h

Front Tire
Butcher, GRID casing, GRIPTON® T7 compound, 29x2.3"

Rims
Double-wall alloy, 27mm internal width, 28h

Rear Tire
Purgatory, GRID casing, GRIPTON® T7 compound, 29x2.3"

Front Hub
Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h

Spokes
Stainless, 14g

Inner Tubes
Standard, Presta Valve

Weight

Weight
15.93kg (35 lb, 1.9 oz)

Weight Size
S4

* Weights based on production painted frames as pictured. Actual weights will vary based on colourway, frame size, and component variation. Specifications are subject to change without notice.