

# Technical Specifications

## Drivetrain

Chainrings  
32T

Bottom Bracket  
SRAM DUB, BSA 73mm, Threaded

Cassette  
SRAM NX Eagle, 12-speed, 11-50t

Rear Derailleur  
SRAM NX Eagle, 12-speed

Chain  
SRAM NX Eagle, 12-speed

Crankset  
SRAM NX Eagle, DUB, S1:165mm, S2-S5: 170mm, S6: 175mm

Shift Levers  
SRAM NX Eagle, trigger, 12-speed

---

## Cockpit

Stem  
Alloy Trail Stem, 35mm bar bore

Saddle  
Bridge Comp, Hollow Cr-mo rails, 155/143mm

Tape  
Specialized Trail Grips

Handlebars  
Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width

SeatPost  
X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm

---

## Frameset

Frame  
Alloy chassis and rear-end, asymmetrical design, 29 Trail Geometry, horst pivot BB adjustment, threaded BB, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel

Seat Binder  
Alloy, 38.6mm

---

## Wheels & Tires

Rear Hub  
Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h

Front Hub  
Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h

Front Tire  
Butcher, GRID casing, GRIPTON® T7 compound, 29x2.3"

Spokes  
DT Swiss Industry

Rear Tire  
Purgatory, GRID casing, GRIPTON® T7 compound, 29x2.3"

Rims  
Specialized 29, hookless alloy, 30mm inner width, tubeless ready

Inner Tubes  
Standard, Presta valve

---

## Suspension

Fork  
FOX FLOAT 34 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm axle, 44mm offset, 140mm of travel

Rear Shock  
FOX FLOAT DPS Performance, Rx Trail Tune, rebound and 3-position compression adjust, S1:190x42.5mm, S2-S6: 190x45mm

---

## Brakes

Rear Brake