

## Safety Data Sheet

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product name: SP-004J PE-LINE ACTIVE SPRAY  
Number : 744333\_Eng

#### Company Identification

Manufacture & Distributor : SHIMANO NORTH AMERICA FISHING, INC.  
Address : 9560 Palmetto Commerce Parkway Ladson, South Carolina 29456 U.S.A.  
Emergency Phone number : +1-949-951-5003

Manufacture & Distributor : SHIMANO EUROPE B.V.  
Address : High Tech Campus 92, 5656 AG Eindhoven, The Netherlands  
Emergency Phone number : +31-40-2612222

Manufacture & Distributor : SHIMANO INC.  
Address : 3-77 Oimatsu-cho Sakaiku Sakai OSAKA 5908577, JAPAN  
Emergency Phone number : 0570-031961

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

<Physical hazards>	Aerosols	Category 1
	Flammable liquids	Category 2
<Health hazards>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity following single exposure	Category 3
	Specific target organ toxicity following repeated exposure	Category 1
	Aspiration hazard	Category 1
<Environmental hazards>	Hazardous to the aquatic environment, short-term (Acute)	Category 2

#### <Hazards symbol>



#### <Signal word>

- DANGER
- Extremely flammable aerosol
  - Highly flammable liquid and vapor
  - Causes skin irritation
  - Causes serious eye damage
  - Suspected of damaging fertility or the unborn child
  - May cause respiratory irritation
  - May cause drowsiness or dizziness
  - Causes damage to organs (Nervous system) through prolonged or repeated exposure
  - May be fatal if swallowed and enters airways
  - Toxic to aquatic life

\*When there is not mention by the GHS classification, perform enough consideration about the safety measures / emergency measures / storage / disposal in reference to following information.

### Cautions

- <Safety measurements>
- Do not handle until all safety precautions have been read and understood.
  - Keep away from ignition sources such as heat, sparks, or open flame.
  - Use only non-sparking tools.
  - Do not breath mist and vapor.
  - Use only in a outdoor or well-ventilated area.
  - Avoid release to the environment.
  - Do not eat, drink or smork when using this product.
  - To avoid thermal decomposition, do not overheat. Abnormally long processing time or high temperatures can produce irritating and toxic fumes.
  - Wear appropriate protective gloves, glasses, clothes, face shield, or mask.
  - Wash hands thoroughly after handling.
- <First-aid measures>
- If inhaled : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical treatment if you feel unwell.
  - If swallowed : Rinse mouth, do not induce vomiting. Immediately get medical treatment.
  - If eye contact : Rinse cautiously with water for at least 15 minutes. Get medical treatment.
  - If skin contact : Wash hands thoroughly after handling. Remove contaminated clothing and the substance. Get medical treatment, if you feel unwell.
- <Storage>
- Store in cool, dry, well-ventilated location. Keep away from heat and all possible source of ignition (temperature below 40°C) and keep away from sunlight.
  - Follow all regulation in your country.
- <Disposal>
- Follow all regulation in your country.

### 3. HAZARDS IDENTIFICATION

Substance or Mixture : Mixture  
Chemical Product Name : AEROSOL TYPE LUBRICATING OIL  
Composition

	CAS.No.	Chemical formulae	Composition Mass%
Silicone oil	Confidential	Unspecified	10 ~ 20%
P.T.F.E.	9002-84-0	(C2F4)n	< 1%
Iso-hexane	107-83-5, 96-14-0	C6H14	20 ~ 30%
Liquefied petroleum(Propellant) Propane	74-98-6	C3H8	50 ~ 60%
Liquefied petroleum(Propellant) Butane	106-97-8, 75-28-5	C4H10	50 ~ 60%

### 4. FIRST AID MEASURES

- Eye Contact : Gently rinse the affected eyes with clean water for at least 15 minutes. And Rrefer for medical attention.
- Skin Contact : Remove all contamination with clothes and wash the affected area with water and soap. If irritation persists, or abnormal conditions are found, arrange examination and treatment by a physician.
- Inhalation : In case of large inhalation, remove the victim from the contamination to fresh air. Keep the victims warm and quiet. If breathing is weak, irregular or has stopped, administer artificial respiration.  
Arrange examination and treatment by a physician as soon as possible. In case of vapor, gas, remove the victim from the contamination to fresh air and arrange examination and treatment by a physician as soon as possible.

Most important signs and condition

- : The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Symptoms usually appear after several hours and resolve within 1-2 days.

## 5. FIRE FIGHTING MEASURES

- Fire-Fighting : 1. Shut off fuel to fire.  
2. In case of small fire, use dry chemical powder or carbon dioxide.  
3. In case of large fire, foam spray is effective to stop flow-in of air.  
4. Watering may enlarge fire and increase risks.  
5. Water the neighbors for cooling.  
6. Keep personnel removed from and upwind fire.  
7. Firefighters should wear proper protective equipment.  
8. Evacuate personnel to safe area.

Special hazards with regards to Fire-Fighting measures

- : Toxic gases (Tetrafluoroethylene, Hexafluoropropylene, Perfluoroisobutylene) will foam upon combustion. Pay attention to burst of container due to heat.

- Extinguishing media : Dry chemical powder, foam or carbon dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : 1. Provide advice related to accidental spills and release of the substance or mixture such as: the wearing of suitable protective equipment (including personal protective equipment, see Section 8 of the SDS) to prevent any contamination of skin, eyes and personal clothing;
- 2. Provide advice related to accidental spills and release of the substance or mixture such as: removal of ignition sources and provision of sufficient ventilation;
- 3. Provide advice related to accidental spills and release of the substance or mixture such as: emergency procedures such as the necessity to evacuate the danger area or to consult an expert.

- Environmental precautions : Provide advice on any environmental precautions related to accidental spills and release of the substance or mixture, such as keeping away from drains, surface and ground water

Methods and materials for containment and clean up

- : 1. Provide appropriate advice on how to contain and clean up a spill. Appropriate containment techniques may include: bonding, covering of drains; and capping procedures.
- 2. Appropriate clean up procedures may include: equipment required for containment/clean up (include the use of non-sparking tools and equipment where applicable).

**Provide any other issues relating to spills and releases. For example, including advice on inappropriate containment or clean up techniques.**

## 7. HANDLING AND STORAGE

### Handling

- Precautions for safehandling :
1. For personal protection see section 8. Protect from contamination. When opening containers, avoid breathing vapors that may be emanating. Avoid breathing dust. Avoid contamination of cigarettes or tobacco with dust from this material.
  2. Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated. In case of insufficient ventilation, wear suitable respiratory equipment. Do not use a torch to clean this material from equipment without local exhaust ventilation and respirator. Wash hands and face before breaks and immediately after handling the product.
  3. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

### Storage

Conditions for safe storage, including any incompatibilities

- : Keep container tightly closed in a dry and well-ventilated place. Protect from contamination.  
Stable under recommended storage conditions

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering measures :
1. For prolonged works inside, provide ventilation equipment or close the source of ignition.
  2. For use of large quantity outside, electric equipment shall be of explosion-proof and earthed.
  3. Make available in work area emergency shower, hand wash, eye wash and clearly indicate the location thereof.

Control parameters :

	TLV-TWA	TLV-STEL
Iso-hexane	500 ppm	1,000 ppm

Personal protective equipment (PPE)

Eye/face protection : Specify the type of eye protection and/or face shield required, based on the hazard of the substance or mixture and potential for contact;

Skin protection : Specify the protective equipment to be worn (e.g. type of gloves, boots, bodysuit) based on the hazards associated with the substance or mixture and the potential for contact;

Respiratory protection : Specify appropriate types of respiratory protection based on the hazard and potential for exposure, including air-purifying respirators and the proper purifying element (cartridge or canister) or breathing apparatus;

Thermal hazards : When specifying protective equipment to be worn for materials that represent a thermal hazard, special consideration should be given to the construction of the PPE.

**Consistent with good occupational hygiene practices, personal protective equipment (PPE) should be used in conjunction with other control measures, including engineering controls, ventilation and isolation. See also Section 5 – Fire-fighting measures of the SDS for specific fire/chemical PPE advice.**

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state, form : Suspension liquid  
Color : White  
Odor : Few aromatic smells  
pH : None  
Boiling point : No Data  
Melting point : No Data  
Flash point : -30°C (Iso-hexane)  
Auto-ignition point : No Data  
Exposition characteristicexposition limit  
: Upper:7.7 , Lower:1.2 vol% (Iso-hexane)  
Density : 0.76  
Solubility in organic solvent : Miscible with many kind of organic solvents  
Solubility in water : Insoluble

## 10. STABILITY/REACTIVITY

Reactivity : Stable under normal conditions.  
Conditions to Avoid : To avoid thermal decomposition, do not overheat. Abnormally long processing time or high temperatures can produce irritating and toxic fumes.  
Stable under normal conditions.  
Incompatibility : Finely divided aluminum Powdered metals, potent oxidizers like fluorine (F2), and, related compounds, Contact with incompatible materials can cause fire and explosion.  
Hazardous Decomposition Products  
: Hazardous thermal decomposition products:: Hydrogen fluoride, Carbonyl fluoride, acid fluorides  
Hazardous reactions : During drying, cleaning and molding, small amounts of hazardous gases and / or particulate matter may be released.  
These may irritate eyes, nose and throat.  
Large molten masses may give off hazardous gases.

## 11. TOXICOLOGICAL INFORMATION

Corrosively and irritant properties

: No relevant information found

Allergenic and sensitizingeffects : No relevant information found

Acute toxicity :	COMPOSITION	LD <sub>50</sub>
	Iso-hexane	20-30 g/kg

Chronic toxicity : No relevant information found

Carcinogenic effects : No relevant information found

Mutagenic effects : No relevant information found

Effects on thepreproductive syste: No relevant information found

Teratogenic effects : No relevant information found

Other information : Other relevant information on adverse health effects should be included

- Germ Cell Mutagenicity : The mutagenic potential of the product category 'other lubricant base oils' has been extensively studied in a range of "in vivo" and "in vitro" assays. The majority of the studies showed no evidence of mutagenic activity.<sup>(3)</sup>
- Carcinogenicity: : Product contains mineral oils of types shown to be no carcinogenic in animal skin painting studies.<sup>(3)</sup>  
Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC monographs: Group 3)<sup>(4)</sup>, ACGIH<sup>(5)</sup> and EU Directives.<sup>(6)</sup>
- Reproductive and Developmental Toxicity : Results of developmental and reproductive toxicity studies showed no evidence of developmental or reproductive toxicity in rats.<sup>(3)</sup>
- Specific target organ toxicity - single exposure : Acute studies do not indicate any specific organ toxicity following single exposure.<sup>(3)</sup>
- Specific target organ toxicity - repeated exposure : The repeat dose toxicity has been investigated by dermal and inhalation routes for periods between 4 weeks and up to 2 years. No systemic effects showed.<sup>(3)</sup>
- Aspiration Hazard : Classified as a hydrocarbon with kinetic viscosity  $\leq 20.5\text{mm}^2/\text{s}$  measured at 40°C. To be regarded as if they cause human aspiration toxicity hazard.
- Other information: : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

## **12. ECOLOGICAL INFORMATION**

- Bio degradability : This substance is not biodegradable.  
Bio accumulation : No relevant information found  
Fish toxicity : No relevant information found

## **13. DISPOSAL CONSIDERATIONS**

- 1 Do not throw the container into fire.
- 2 Do not dump into sewers, on the ground or into any body of water.
- 3 Disposal shall be in accordance with the concerned rules and regulation.
- 4 Follow all regulation in your country.

## **14. TRANSPORT INFORMATION**

UN Class : Class 2 ,Division 2.1 Flammable gases  
UN Number : 1950 AEROSOLS (maximum 1 liter)

Specific precautionary transport measures and conditions.

Follow all regulation in your country.

## **15. REGULATORY INFORMATION**

Follow all regulation in your country.

## **16. OTHER INFORMATION**

All materials may present unknown hazard and should be used in caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Complied by : NICHIMOLY Div. DAIZO CORPORATION  
Shimano Inc.

Reference : NICHIMOLY Div. DAIZO CORPORATION. , 1 Nov 2016,  
"SP-004J PE-LINE ACTIVE SPRAY 【OEM Product for SHIMANO】",  
Safety Data Sheet, 11162G-(2)E, NICHIMOLY Div. DAIZO CORPORATION.

### Disclaimer

The information above is believed to be accurate and represents the best information currently available to us. We have reviewed any information contained herein which we received from sources outside SHIMANO INC.. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license.

SHIMANO INC. shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.