





uPVC Drainage System

TECHNICAL MANUAL



BS EN 1329/1401



الهيئة السعودية للمواصفات والمقاييس والجودة
Saudi Standards, Metrology and Quality Org.



ISO 9001 : 2015

Since it was established in 1976 Cosmoplast has become the market leading manufacturer of plastic piping systems in the Middle East. Through extensive product development, long term planning and substantial capital investment, Cosmoplast offers one of the most comprehensive and highest quality range of uPVC pipes and fittings for drainage applications.

Today the company has a turnover of more than \$ 100 million and supplies its products not only to the Gulf region but also throughout the Middle East, and specifically designed product ranges into Europe, Africa and the Far East.

Cosmoplast drainage systems include an extensive range of soil and waste pipes and fittings for commercial, industrial, housing and public sector developments.


Cosmoplast drainage systems include both solvent welded and push fit types applicable for wide and comprehensive range of

pipes and accessories. Having been pioneers in the development of drainage systems, Cosmoplast drainage systems represent the benchmark for quality product innovation and outstanding services.

Complete Solutions

With the wide range of pipes and fittings covering the size range from 20mm up to 1400mm, Cosmoplast now offers the most complete choice for its customers. The product range covers all the items required to complete any domestic and industrial drainage system.

Cosmoplast soil and drainage system is fully compatible with its above the ground and underground systems. This enables integrated above and below ground drainage systems to be designed, specified, and supplied from a single reliable source with confidence.



Advantages of Cosmoplast uPVC Drainage System

Advantages of Cosmoplast uPVC Drainage System:

All products supplied by Cosmoplast come with additional advantages like

- Proven research to suit customer's application needs.
- Precise manufacturing according to International Standards.
- ISO 9001 Quality System Accredited Manufacturing environment.
- Stringent testing to international standards.
- Technical service and consulting back up.
- Installation and jointing advice and services.
- Assured timely deliveries.
- Maintenance-free system and long-term reliability.



BS EN 1329/1401



ISO 9001 : 2015

KITE MARKED PIPES AND FITTINGS QUALITY ASSURED PRODUCTS

Cosmoplast drainage systems are manufactured according to the latest European Standards, and are subject to very strict Quality Policy supervised by BSI which enabled Cosmoplast systems to be approved by the most prestigious International Institutes.

Cosmoplast Underground and Above Ground Drainage Pipes & Fittings are approved by the British BSI and are awarded the Kite Mark Quality Certificate where applicable.



NEW EUROPEAN STANDARDS (EN STANDARDS)

COSMOPLAST uPVC drainage pipes and fittings are manufactured and tested in accordance with the new British - European Standards BS EN which have replaced the old British Standards for drainage applications. The new BS EN standards cover all the sizes and applications of the BS Standards.

BS EN 1329-1

applies to uPVC piping systems for soil and waste discharge (low and high temperature) within the building structure. This standard replaces the British Standards BS5255 and BS4514. Products made to BS EN1329 are fully compatible with the products made to BS5255 and BS4514.

BS EN1401-1

applies to uPVC piping systems for underground drainage and sewerage. This standard has replaced most of BS4660 and all of BS5481. Products made to BS EN1401-1 are fully compatible dimensionally with the products manufactured to BS 4660 and BS 5481.



BS EN 1329/1401




ISO 9001 : 2015

Joining Techniques


SOLVENT CEMENT JOINTING

To achieve effective reliable joints:

1. Cut the pipe at right angle using appropriate cutter or saw.



2. Chamfer the pipe and remove the burrs and filings.



3. Clean the spigot and socket with a dry cloth it is recommended to roughen the mating surface using emery paper and apply the cleaner to internal surface of the fitting and external surface of the pipe



4. Apply thin layer of solvent cement first to inner surface of the socket and then on the spigot to the mating surfaces using suitable brush.



5. While the solvent cement is still wet, insert the pipe inside the fitting until it reaches the socket end. It is recommended to twist the pipe a ¼ turn while inserting it inside the fitting for better distribution of the cement.



6. Wipe the excess cement and leave the joint to dry.



Note :

Applying excessive quantity of solvent cement should be avoided as it creates pool of cement on the internal surface of the pipe that will continue to corrode the surface and weaken the pipe and fitting and might cause the joint to fail at high pressure.

PUSH FIT JOINTING

1. Cut the pipe at right angle using appropriate cutter or saw.



2. Chamfer the pipe and remove the burrs and filings.

3. Clean the pipe and fitting with dry cloth



4. Apply thin layer of appropriate lubricant on the rubber ring using suitable brush.



5. Insert the pipe inside the fitting until it reaches the socket end, then withdraw the pipe 5 – 10mm (depending on the size) to allow for expansion / contraction.



6. Wipe the excess lubricant.



CUTTING THE PIPES

While cutting Cosmoplast uPVC pipes, the following instructions should be followed:

- Appropriate pipe cutter or saw should be used.
- Cut pipes square and perpendicular to its axis.
- After cutting pipes, remove all burrs from the cut end, and bevel the sharp cutting edge.





SOLVENT WELDING IN HOT WEATHER CONDITIONS :

During hot weather conditions of 35°C and above, special consideration should be given to the process of solvent Welding of UPVC pipes and fittings to ensure a leak proof joint.

Solvent cements contain high strength chemical solvent which evaporate faster at elevated temperatures and in windy conditions.

When PVC pipes are stored in open areas or under direct sunlight, the pipe surface temperature will be around 15°C higher than the ambient temperature. The solvent cement attacks the hot surface faster and deeper. Therefore, it is very important to avoid using excess cement during the jointing process to avoid creating pools of cement inside the fitting and pipe sockets. Excess solvent cement should be wiped off the joined surface quickly.

Recommendations for the solvent welding during hot weather confitions:

1. Solvent cement and cleaners should be stored in a cool or shady areas.
2. Pipes and Fittings should be stored in a shady area before solvent welding
3. The surfaces to be joined should be cooled by wiping with a wet cloth. The surfaces should be dry before applying the solvent cement.
4. Solvent welding is recommended to be done during the cooler morning hours.
5. The two surface should be joined quickly while they are still wet with cement.
6. Shake or stir the solvent cement well before use.
7. Allow at least 24 hours for the joints to cure before pressurizing the system. For sizes above 8" you should allow at least 48 hours.



BS EN 1329/1401



ISO 9001 : 2015

SUPPORT AND EXPANSION

- All pipework must be adequately supported whether vertical or horizontal.
- Plastic pipework expands and contracts with changes in temperature - whether ambient temperature or from the nature of the discharge through the pipework. Expansion joints must therefore be provided to accommodate such thermal movement.
- Horizontal pipework requires more frequent support than vertical pipework (for example, soil stacks)
- Suitable sound absorbing brackets with rubber lining should be used to support pipes. Those brackets must be dimensionally compatible to the pipe diameter. The fixed bracket creates fixed point in the pipe system.
- With fixed brackets the pipe or fitting can not be moved through the bracket after screws are tightened. In order to prevent sliding down of vertical pipes, each individual pipe must be secured on one point by a fixed bracket.
- Every horizontally installed pipe should always be fixed with one fixed bracket. All remaining pipe brackets in horizontal as well as in vertical installation must be tightened in such a way to allow sliding.
- Fixed brackets must be installed directly above the fitting at the bottom of the pipe end. The sliding bracket must be installed at a distance of maximum of two meters above the fixed bracket.
- Pipe brackets should not be installed in areas of diameter reduction and change of directions in the system, this is required to allow for the thermal expansion.
- Pipe brackets should be fixed on building materials with high strength in order to assure strong and durable pipe fixing.
- It is recommended that only steel brackets (ie. not plastic brackets) be used on interior soil stacks which are subjects to fire regulations
- Any point where pipework passes through a floor or wall and is made as a fire stop, it must be treated as a fixed point for the purposes of determining positions of expansion joints.



SUPPORT DISTANCES

	Maximum Support Distance	
	Vertical	Horizontal
Pipe Size - Soil		
82 mm	2 m	1 m
110 mm	2 m	1 m
160 mm	2 m	1.2 m
Pipe Size - Waste		
32 mm	1.2 m	0.5 m
40 mm	1.2 m	0.5 m
50 mm	1.2 m	0.5 m

EXPANSION IN uPVC PIPES

The PVC piping systems expand and contract with changes in temperature, both from ambient temperature and from the temperature of the fluid passing through the pipework.

The following sections explain the techniques of estimating and treating the expansion in PVC pipes.

Calculation of Expansion

The co-efficient of linear expansion of PVC pipes is relatively small compared to other plastic materials. However, the effects of thermal expansion in the system should be compensated wherever necessary.

The thermal expansion in PVC straight sections can be calculated using the below formula:

$$\Delta L = \alpha \times L \times \Delta T$$

Where:

ΔL = expansion (mm)

α = co-efficient of linear expansion (mm/m/°C) = 0.08

L = length of the pipe (m)



ΔT = temperature difference (°C)

Support and Expansion Distances

In general, rubber ring pipework (Push Fit) do not require expansion joints, as the rubber sockets in the fittings and pipes are acting as expansion joints to absorb the expansion and contraction.

While in solvent welding pipework, the expansion should be calculated and compensated as described below.

After calculating the thermal expansion in the PVC pipes, expansion couplers (Rubber ring couplers) should be installed in proper locations to absorb the change in pipe length.




support & expansion distance

Pipe work should be provided with expansion couplers installed at an appropriate locations within the piping network

VERTICAL INSTALLATIONS


Vertical Installations can be done in two ways:

- a) Fixed Installation
- b) Free Installation



HORIZONTAL INSTALLATIONS


In horizontal Installations, pipe clamps should be placed at intervals which are approximately ten times bigger than the pipe diameter. This will ensure that the installation is fixed and will not bend.




FP= Fixed point
 SP= Sliding point
 Ø = Pipe Diameter

VENTILATION


Ventilation is essential in every drainage system. In order to prevent traps being emptied by suction or pressure, both overpressure and underpressure should not exceed 300 Pa (30 mm water column). Air should be able to escape from the system (venting) and to enter the system (admittance). A ventilated discharge pipe is used for this purpose.



Technique (1)




Technique (2)



Technique (3)

CROSS-FLOW PREVENTION

When connecting small waste pipes to vertical discharge stacks, attention should be given to avoid the cross-flow from one branch to the other. The restricted entry zone (L) for the opposite waste pipe varies depending on the stack diameter, within which no connections should be made. However, connections are allowed at right angles of the boundary center line or directly opposite.



Stack Dia.	L (mm)
82	90
110	110
160	250

In case of cross flow from a large diameter to a small waste pipe, the cross flow should be prevented by connecting the waste pipe at or above the center line of larger branch. Connections are not allowed at right angles of boundary center line or directly opposite. In this case the restricted entry zone is always 200mm regardless of stack diameter.

RAINWATER OUTLETS (ROOF DRAINS)

Cosmoplast product range includes different models and options of rainwater outlets like the dome type, corner type, flat type...etc. they are all suitable for roofs with and without waterproofing systems.

All Cosmoplast roof drains are connected to the rainwater pipes without traps.



The corner type rainwater outlet enables both side and bottom connections to the rainwater pipes.

The gratings of all Cosmoplast rainwater outlets are connected to the uPVC body by screws which allow easy access to the rainwater pipes in case of maintenance or cleaning.

ACCESS FITTINGS

Access fittings should be installed at proper accessible locations in the system to enable cleaning and discharging any blockage that may occur in the system due to solid deposits.

These access fittings enable the insertion of cleaning hoses and springs whenever blockage occurs.

Access pipes are recommended to be installed on stack pipes at every 3 to 4 stories to enable multiple access points to the stack and allow the whole stack to be cleaned if needed.



Access fittings are also recommended to be installed at the points of connection between underground and above ground pipework, after pipework sections that include multiple bends and long pipe runs and on pipeworks which are casted in concrete.

TESTING DRAINAGE SYSTEMS

Drainage installations should be tested for leaks and defects in new installations and whenever the existing installation is altered, extended or repaired.

All new installations or modified portions should be left uncovered until the testing is successfully completed and approved.

Drainage systems are commonly tested by water and in some cases air test is done.

The following are some guidelines for testing drainage systems, while the local codes of practice for each country should be also noted and applied.

WATER TEST

- All pipe ends and connections must be plugged using suitable testing plugs.
- Install vertical pipe length to the drain to provide the necessary testing water head.
- Fill the system with water to maximum height of 3m (30 kPa).
- The maximum head at the lower parts of the system should never exceed 4.0m, therefore in case of steep gradients the system should be tested in sections.
- The filled system should be left 2 hours under testing, during which the system should be inspected by measuring the drop in water height.
- The pipe work should be inspected for any leakage and all defected installations should be repaired and tested again.



GOOD SITE PRACTICE

Handling

- Take all reasonable care when handling uPVC, particularly in very cold conditions when the impact strength of the material is reduced.
- Do not throw or drop pipes, or drag them along hard surfaces.
- In case of mechanical handling, use protective slings and padded supports. Metal chains and hooks should not make direct contact with the pipe.

On-site Storage

- Stack pipe lengths:
 - » either on a flat base
 - » or on a level ground
 - » or on 75mm x 75mm timber at 1m max. centers.

- Provide side support with 75mm wide battens at 1m centers.
- Maximum stack (normal conditions): seven layers high.
- Ideally, stacks should contain one diameter pipe size only. Where this is not possible, stack largest diameter pipes at base of stack. Small pipes may be nested inside larger pipes.
- If stored in the open for long periods or exposed to strong sunlight, cover the stack with opaque sheeting.
- Store fittings under cover. Do not remove from cartons or packaging until required.
- Store solvent cement and cleaning fluid in a cool place out of direct sunlight and away from any heat source.



Storage in hot climates

- Ultra-violet light can affect pipes and fittings: pipe colour may change and rubber seals may be degraded
- Accordingly:
 - » store all materials in well-ventilated, shady conditions
 - » do not expose to direct sunlight
 - » keep fittings in original packaging until required for use
- Maximum stack (hot conditions) six layers high .

Transport


While transport, pipes should be arranged safely on trucks avoiding crossing, bending and over stacking.

The pipes should also be fully supported over their total length.





RECOMMENDATIONS


a) The pipe must be cut with a fine saw. Big saw teeth would damage the pipes. The cut has to be vertical.




b) The pipe ends should be smoothly chamfered to an angle of 15° to ensure better jointing and avoid damaging the rubber ring.





c) It is not recommended to shorten the fittings as it could result in defective joints.






d) Connected pipes and fittings need to be fitted straight. Otherwise it could result in leakage at sealing points.



e) Before covering the pipes with concrete, it is recommended to cover the joints so that cement d'nt enter the joint.



f) Pipes must be correctly connected considering the expansion. Too shallow connections into the cap do not guarantee a safe joint, while too deep connections do not allow expansion.



MATERIAL PROPERTIES

The following table shows the main physical and thermal properties of the uPVC material:

Property	Value	Conditions and Remarks
Physical properties		
Molecular weight (resin)	140,000	cf: K57 PVC 70,000
Relative density	1.42 - 1.48	cf: PE 0.92 - 0.96, GRP 1.4 - 2.1, CI 7.20, Clay 1.8 - 2.6
Water absorption	0.12%	23°C, 24 hours cf: AC 18 - 20% AS1711
Hardness	80	Shore D Durometer, Brinell 15, Rockwell R 114, cf: HDPE 60
Impact strength - 20°C	20 kJ/m ²	Charpy 250 µm notch tip radius
Impact strength - 0°C	8 kJ/m ²	Charpy 250 µm notch tip radius
Coefficient of friction	0.4	PVC to PVC cf: PE 0.25, PA 0.3
Mechanical properties		
Ultimate tensile strength	50 MPa	AS 1175 Tensometer at constant strain rate cf: PE 12-20
Elongation at break	≥ 80%	AS 1175 Tensometer at constant strain rate cf: PE 500-900
Short term creep rupture	44 MPa	Constant load 1 hour value cf: PE 10-16
Long term creep rupture	28 MPa	Constant load extrapolated 50 year value cf: PE 6-12
Elastic tensile modulus	2.7 - 3.0 GPa	1% strain at 100 seconds cf: PE 0.6-0.8
Elastic flexural modulus	2.7 - 3.0 GPa	1% strain at 100 seconds cf: PE 0.5-0.7
Long term creep modulus	0.9 - 1.2 GPa	Constant load extrapolated 50 year secant value cf: PE 0.1 - 0.3
Shear modulus	1.0 GPa	1% strain at 100 seconds
Bulk modulus	4.7 GPa	G=E/2(1+µ) cf: PE 0.2
Poisson's ratio	0.4	1% strain at 100 seconds K=E/3(1-2µ) cf: PE 2.0 Increases marginally with time under load. cf: PE 0.45
Electrical properties		
Dielectric strength (breakdown)	14 - 20 kV/mm	Short term, 3 mm specimen
Volume resistivity	2 x 10 ¹⁴ Ω.m	AS 1255.1
Surface resistivity	10 ¹³ - 10 ¹⁴ Ω	AS 1255.1
Dielectric constant (permittivity)	3.9 (3.3)	50 Hz (10 ⁶ Hz) AS 1255.4
Dissipation factor (power factor)	0.01 (0.02)	50 Hz (10 ⁶ Hz) AS 1255.4
Thermal properties		
Softening point	80 - 84°C	Vicat method AS 1462.5 (min. 75°C for pipes)
Max. continuous service temp.	60°C	cf: PE 80, PP 110
Coefficient of thermal expansion	0.08	mm/m°C cf: PE 18 - 20 x 10 ⁻⁵ , CI 1.2 x 10 ⁻⁶
Thermal conductivity	0.16 W/(m.K)	0 - 50°C
Specific heat	1,000 J/(kg.K)	0 - 50°C
Thermal diffusivity	1.1 x 10 ⁻⁷ m ² /s	0 - 50°C
Fire performance		
Flammability (oxygen index)	45%	ASTM D2683 Fennimore Martin test, cf: PE 17.5, PP 17.5
Ignitability index	10 - 12 (/20)	cf: 9 - 10 when tested as pipe AS 1530 Early Fire Hazard Test
Smoke produced index	6 - 8 (/10)	cf: 4 - 6 when tested as pipe AS 1530 Early Fire Hazard Test
Heat evolved index	0	
Spread of flame index	0	Will not support combustion. AS 1530 Early Fire Hazard Test

1 - Corrosion resistance:

uPVC being a non-conductor is totally resistant to all types of galvanic and electromechanical influences which might corrode it. Being non-metallic, uPVC is resistant to any type of corrosion caused by water as well as a large range of industrial liquids and chemicals. Seepage from high sulphate soils as well as low hardness waters also do not threaten it. This in turn translates into a longer installed life of the uPVC pipe systems.

2 - Resistance to Abrasion:

uPVC pipes are highly resistant to abrasion due to stress from abrasion fluids of excessive pressure. Tests have shown that uPVC pipes are up to 2.5 times more resistant to abrasions when compared to steel.



3 - Resistance to biological attack and growth:

uPVC is completely resistant to any microscopic life that it might be exposed to. It does not offer a nourishing source to any bacterial life form and is completely guaranteed to withstand any such growth.

4 - Reaction with Building Materials:

uPVC does not react with any of the normal building materials like cements and paints. However, information about the chemical resistance of uPVC to a wide range of chemicals can be found in the tables of Chemicals Resistance listed in this catalogue.

5 - Thermal Expansion

The coefficient of linear expansion for uPVC is 0.08 mm/m/°K which means less than 1mm per each 1m length in case of a temperature rise of 10°C.

The thermal expansion in drainage systems should be treated by using push fit (rubber rings) fittings and sockets which should be located in suitable locations (BSEN 12056 - Code of Practice for Sanitary Pipework).

6 - Effect of sunlight:

Long exposure to sunlight causes the colour of uPVC to fade, in addition to the reduction of impact strength. The effect of sunlight does not seriously affect the performance of the system, however it is always advisable to protect the system from the direct exposure to sunlight by painting the exposed parts with any exterior glass paint (paint specialists can recommend the suitable types).

7 - Effect of frost:

The uPVC is not affected by frost, however sub-zero temperatures reduce the impact strength of the uPVC system. Therefore, extra care is to be given while handling and installing uPVC during sub-zero temperatures.

8 - Fire Hazard of uPVC Material:

uPVC pipes and fittings as finished products are not classified as hazardous to health as they exhibit no chemical hazards when used under normal conditions and applications.

uPVC pipes and fittings should be stored in dry and covered places and protected from direct sources of heat and sunlight. It should be noted that the packing cartons and pallets can form a fire risk and may participate in fire spread.

9 - Flammability

uPVC is self-extinguishing material as per BS2782 and fire rated as Class 1 as per BS476 - Part 7 and Class 0 to Part 6.

Due to its flame retardant property, uPVC finished products do not participate in fire. uPVC products have a higher ignition temperature than most of the other thermoplastic and organic materials.

When burns, uPVC form a protective char layer, which in turn act as an insulation layer that stops oxygen.

10 - Fire Fighting

All common fire extinguishers can be used effectively for fighting fires involving PVC.

Chemical Resistance of uPVC

The uPVC material has a high resistance to a wide range of chemicals which makes the uPVC as an ideal option for many residential and industrial applications.

Detailed tables for the chemical resistance of uPVC material can be provided upon request.



BS EN 1329/1401



ISO 9001 : 2015



uPVC Soil, Waste and Above Ground Discharge System

Cosmoplast soil, waste and above ground drainage pipes and fittings are manufactured according to the latest European Standard BS EN 1329-1 from grey unplasticised polyvinyl chloride uPVC in sizes 36 mm to 315 mm.

Size 36 mm to 56 mm according to BS 5255 are manufactured from mUPVC or ABS.

Cosmoplast soil, waste and above ground drainage systems are available in two options:

1. Solvent Welding Type: with sizes from 36 mm up to 200 mm.
2. Rubber Ring (Push Fit) Type: with sizes from 40 mm up to 315 mm.

Both options are suitable for domestic drainage and particular requirements of commercial, industrial and public installations.

BSEN 1329 - 1 uPVC Drainage Pipes for Above Ground Drainage

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
* 32	3.00	32.00	32.20	3.00	3.50
36	3.00	36.20	36.45	3.00	3.50
40	3.00	40.00	40.20	3.00	3.50
43	3.00	42.75	43.05	3.00	3.50
50	3.00	50.00	50.20	3.00	3.50
56	3.00	55.80	56.05	3.00	3.50
75	3.00	75.00	75.30	3.00	3.50
82	3.00	82.00	82.30	3.00	3.50
110	3.20	110.00	110.30	3.20	3.80
160	3.20	160.00	160.40	3.20	3.80
200	4.90	200.00	200.50	4.90	5.60
250	6.20	250.00	250.50	6.20	7.10
* 315	7.70	315.00	315.60	7.70	8.70

* Produced upon request only.

BS 5255 - mUPVC and ABS Waste Pipes

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
1¼" / 36mm	1.80	36.15	36.45	1.80	2.20
1½" / 43mm	1.90	42.75	43.05	1.90	2.30
2" / 56mm	2.00	55.75	56.05	2.00	2.40

DIN19531 - 10; uPVC Pipes for Drainage Systems Inside Buildings

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
50 mm	1.80	50.00	50.20	1.80	2.20
75 mm	1.80	75.00	75.30	1.80	2.20




BS EN 1329/1401



ISO 9001 : 2015


Solvent Welding Joints

uPVC Drainage Pipe




Nominal O.D. (mm)	Length (m)
* 36	4
40	4
* 43	4
50	5.8 / 6
* 56	4
75	5.8 / 6
82	5.8 / 6
110	5.8 / 6
160	5.8 / 6
200	5.8 / 6

Straight Coupler




D (mm)	L (mm)
* 36	45
* 43	45
50	52
* 56	56
75	83
82	96
110	112
160	161
200	140

87.5° Elbow




D (mm)	L (mm)
* 36	77
* 43	90
50	101
* 56	100
75	137
82	170
110	190
160	329
200	305

45° Elbow




D (mm)	L (mm)
* 36	67
* 43	83
50	86
* 56	94
75	128
82	139
110	170
160	269
200	290

45° Y Branch




D (mm)	L (mm)
* 36	102
* 43	115
50	125
* 56	144
75	192
82	205
110	268
160	337
200	400

45° Reducer Y Branch




D (mm)	d (mm)	L (mm)
75	50	156
82	56	179
110	50	175
110	56	187
110	75	209
110	82	224
160	110	283
200	160	400

87.5° Tee Branch



D (mm)	L (mm)
* 36	90
* 43	109
50	106
* 56	132
75	167
82	176
110	250
160	358
200	365

87.5° Reduced Tee



D (mm)	d (mm)	L (mm)
75	50	143
82	56	162
110	50	156
110	56	167
110	75	187
110	82	201
160	110	250
200	160	360

* Available in UPVC and ABS




BS EN 1329/1401




ISO 9001 : 2015

Reducer Bush




D (mm)	d (mm)	L (mm)
* 43	36	27
56	36	27
* 56	43	27
75	50	43
82	43	37
82	56	37
110	50	52
110	56	50
110	75	52
110	82	50
160	110	62
200	160	60

45° Access Elbow




D (mm)	L (mm)
43	83
56	94
82	139
110	170

87.5° Access Elbow




D (mm)	L (mm)
43	93
50	94
56	100
75	133
82	170
110	190
160	329

87.5° Access Tee




D (mm)	L (mm)
43	109
56	132
82	205
110	250
160	358

Access Pipe




D (mm)	L (mm)
50	102
75	160
82	212
110	219
160	256

Access Plug



D (mm)	L (mm)
40	75
* 43	50
50	75
* 56	50
75	89
82	77
110	88
160	95
200	100

Pipe Access Plug




D (mm)	L (mm)
36	47
43	52
50	51
56	55
75	69
82	75
110	80
160	95

Double Tee with Access



D (mm)	d (mm)	L (mm)
110	110	219



* Available in UPVC and ABS



BS EN 1329/1401




ISO 9001 : 2015

uPVC Deep Seal Floor Trap



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	56	175




75mm Seal Depth

uPVC Floor Trap with Removable Separator



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	43	170




70 mm seal depth

Body Material can be:
- UPVC
- ABS

ABS Deep Seal Floor Trap



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	56	175




75mm Seal Depth

Metric Floor Trap



D (mm)	d1 (mm)	d2 (mm)	H (mm)	H1 (mm)
110	75	50	162	56.5




70mm Seal dept

Body Material can be:
- UPVC
- ABS

Short Floor Trap



D1 (mm)	d2 (mm)	d3 (mm)	H (mm)
110	82	43	108
110	82	56	108




40mm Seal Depth

uPVC Floor Trap 160 mm



D1 (mm)	d2 (mm)	d3 (mm)	H (mm)
160	110	50	160
160	110	56	160




70mm Seal Depth

Boss Pipe MXF




D (mm)	d1 (mm)	d2 (mm)	L (mm)
110	56	43	209




Boss Pipe FXF




D (mm)	d1 (mm)	d2 (mm)	L (mm)
110	56	43	209



Boss Connector




∅	D (mm)	L (mm)
160	56	43
160	43	36
110	56	50
110	43	40



AC to Drainage Boss



D (mm)	d	L (mm)	F (mm)
43	1"	41	52




BS EN 1329/1401




ISO 9001 : 2015

AC to Drainage Boss




D (mm)	d1	d2	L (mm)
56	1"	3/4"	34



45° Double Y Branch




D (mm)	d (mm)	L (mm)
50	50	128
75	75	193
110	110	260
160	160	260



87.5° Double Tee Branch





D (mm)	d (mm)	L (mm)
50	50	106
75	75	166
110	110	219
160	160	219



Flat Roof Drain




d (mm)	D (mm)	L (mm)
82	178	40



Vent Cowl





D (mm)	L (mm)
50	63
56	70
75	84
82	85
110	105
160	138



Rainwater Outlet





d (mm)	D (mm)	L (mm)
82	180	115
110	343	117



Dome Type Rainwater Outlet (HD)





d (mm)	D (mm)	L (mm)
82	405	168
110	405	168



Rain Water Outlet With Extension





D (mm)	d (mm)	H (mm)
110	270	146



Corner Roof Outlet



D (mm)	H (mm)	W (mm)
82	154	194
110	154	194





Balcony Drain With Side Outlet



Z (mm)	D (mm)	d (mm)	L (mm)
100	56	50	68
150	56	50	70

Material : ABS



BS EN 1329/1401




ISO 9001 : 2015

Female Adapter




D (mm)	L (mm)	T
36	47	1½"
43	52	1½"
43	57	2"



Male Adapter




D (mm)	L (mm)	T
36	47	1½"
43	52	1½"
43	57	2"



Shower Elbow




D (mm)	d	L (mm)
43	1½"	56



Reducer For Shower Elbow




D (mm)	d (mm)	L (mm)	L1 (mm)	L2 (mm)
56	43	52.5	25	25



Pipe Plug




D (mm)	H (mm)
43	20
50	50
56	25
75	60
82	35
110	40
160	50



End Cap





D (mm)	H (mm)
36	20
43	20
56	23
82	28
110	30
160	32
200	40



uPVC Floor Trap Cover Model(1)





D (mm)	Z (mm)	L(mm)
110	150	27.5



uPVC Floor Trape Cover - Model (2)





L (mm)	Z (mm)	D (mm)
150	22	110



Floor Trap Mesh





L (mm)	Z (mm)	D (mm)
150	27	98



uPVC Floor Clean Out



D (mm)	Z (mm)	L (mm)
110	150	27.5



BS EN 1329/1401




ISO 9001 : 2015

Rodding Eye Cover




D (mm)	W (mm)
82	146
110	146



Stainless Steel Floor Clean Out




D (mm)	Z (mm)	L (mm)	t (mm)
110	150	27.5	2m
110	150	27.5	3m




available in SS 304 & 316

Stainless Steel Drain Cover



D (mm)	Z (mm)	L (mm)	t (mm)
110	150	27.5	2m
110	150	27.5	3m




available in SS 304 & 316

SS Balcony Drain Cover



Z (mm)	D (mm)	L (mm)	t (mm)
79	50	16	2



Rubber Ring (Push-Fit) Joints

Cosmoplast pipes and fittings with rubber ring (push-fit) joints present many advantages, like the ease of installation especially in tight places. It also gives the connections the freedom to expand and contract without affecting the joint quality.


The sealing rings used in producing Cosmoplast push fit joints are made of natural / synthetic rubber, offering chemical resistance to wide range of chemicals. The rings also provide an effective seal against internal and external water pressure and against penetration by tree roots.

uPVC Drainage Pipe




D (mm)	L (mm)
* 40	5.8 / 6m
50	5.8 / 6m
56	5.8 / 6m
75	5.8 / 6m
82	5.8 / 6m
110	5.8 / 6m
160	5.8 / 6m
200	5.8 / 6m
250	5.8 / 6m
315	5.8 / 6m

87.5° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
* 40	40	113
50	50	125
56	56	133
75	75	170
82	82	168
110	110	225
160	160	308
200	200	373
250	250	430

87.5° Long Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	219
110	110	276

45° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
* 40	40	130
50	50	137
56	56	174
75	75	146
82	82	168
110	110	220
160	160	287
200	200	325
250	250	440

45° Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
* 40	40	164
50	50	183
56	56	203
75	75	238
82	82	235
110	110	290
160	160	421
200	200	490
250	250	660

45° Reduced Y Branch "Push Fit"



D (mm)	d (mm)	L (mm)
75	50	212
110	75	276
110	82	256
160	110	325
200	110	360
200	160	490
250	160	490
250	200	540

87.5° Tee "Push Fit"



D (mm)	d (mm)	L (mm)
* 40	40	164
50	50	174
56	56	169
75	75	215
82	82	168
110	110	280
160	160	407
200	200	410
250	250	560



* Manufactured on special order

87.5° Reduced Tee "Push Fit"



D (mm)	d (mm)	L (mm)
75	50	191
110	50	188
110	75	236
110	82	224
160	110	325
200	160	370
250	200	560

Coupler "Push Fit"



D (mm)	L (mm)
* 40	110
50	110
56	108
75	131
82	113
110	159
160	168
200	230
250	270

Repair Coupler "Push Fit"



D (mm)	L (mm)
50	110
56	108
75	131
82	115
110	159
160	168
200	230
250	270

Expansion Socket / Single Socket "Push Fit"



D (mm)	d (mm)	L (mm)
82	82	110
110	110	129
160	160	151

Reducer "Push Fit"



D (mm)	d (mm)	L (mm)
* 50	40	124
75	50	143
82	56	110
110	50	143
110	56	133
110	75	175
110	82	133
160	110	173
200	160	275
250	200	260
250	160	370

87.5° Double Tee "Push Fit"



D (mm)	d (mm)	L (mm)
56	56	173
82	82	206
110	110	280
160	160	360

45° Double Y Branch "Push Fit"



D (mm)	d (mm)	L (mm)
56	56	195
82	82	235
110	110	287
160	160	401

Floor Trap "Push Fit"




D (mm)	D1 (mm)	d (mm)	L (mm)
110	82	56	175
* 110	75	50	171
* 110	75	40	171

75mm Seal Depth




* Manufactured on special order

Access Pipe "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	214
110	110	320
160	160	350

87.5° Access Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	219
110	110	276
160	160	263

87.5° Access Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	223
110	110	269
160	160	374

Access Plug "Push Fit"




D (mm)	L (mm)
* 40	75
43	50
50	75
56	50
75	89
82	77
110	88
160	95
200	100

Pipe Access Plug




D (mm)	L (mm)
36	47
43	52
50	50
56	55
75	72
82	75
110	80
160	95

Pipe Plug




D (mm)	L (mm)
* 40	48
43	20
50	50
56	25
75	60
82	35
110	40
160	50

End Cap



D (mm)	H (mm)
56	23
82	28
110	30
160	32
200	40
250	50

HDPE Aerator with Rubber Ring Socket & Extension



D	H (mm)	L (mm)
110	270	920
160	280	970



BS EN 1329/1401

* Manufactured on special order



ISO 9001 : 2015

Underground Drainage And Sewerage System

Cosmoplast underground drainage and sewerage system is manufactured from Golden Brown unplasticised polyvinyl chloride uPVC Material.

Cosmoplast underground drainage system is available in two options:

1. Solvent Welding Type: with sizes from 75 mm up to 200 mm.
2. Rubber Ring (Push Fit) Type: with sizes from 40 mm up to 1000 mm.

Cosmoplast underground uPVC pipes and fittings are manufactured according to the latest European Standard BS EN 1401 BSEN 1401 - 1 uPVC Pipes for Underground Drainages :


Mean Outside Diameter		SN 2 SDR 51		SN 4 SDR 41		SN 8 SDR 34	
min	max	e _{min}	e _{m, max}	e _{min}	e _{m, max}	e _{min}	e _{m, max}
110	110.3	-	-	3.2	3.8	3.2	3.8
125.0	125.3	-	-	3.2	3.8	3.7	4.3
160.0	160.4	3.2	3.8	4.0	4.6	4.7	5.4
200.0	200.5	3.9	4.5	4.9	5.6	5.9	6.7
250.0	250.5	4.9	5.6	6.2	7.1	7.3	8.3
315.0	315.6	6.2	7.1	7.7	8.7	9.2	10.4
*355.0	355.7	7.0	7.9	8.7	9.8	10.4	11.7
400.0	400.7	7.0	8.9	9.8	11.0	11.7	13.1
*450.0	450.8	8.8	9.9	11.0	12.3	13.2	14.8
500.0	500.9	9.8	11.0	12.3	13.8	14.6	16.3
630.0	631.1	12.3	13.8	15.4	17.2	18.4	20.5
*710.0	711.2	13.9	15.5	17.4	19.4	-	-
800.0	801.3	15.7	17.5	19.6	21.8	-	-
*900.0	901.5	17.6	19.6	22.0	24.4	-	-
1000.0	1001.6	19.6	21.8	24.5	27.2	-	-

Note : 40mm, 50mm, 75mm & 82mm sizes according to BSEN1329 can be produced in orange colour.

* Pipes to these nominal sizes are not normally available in stock.


Push Fit Fittings

uPVC "Push Fit"




D (mm)	L (m)
*40	5.8/6
50	5.8/6
*56	5.8/6
75	5.8/6
82	5.8/6
110	5.8/6
160	5.8/6
200	5.8/6
250	5.8/6
315	5.8/6
400	5.8/6
500	5.8/6

87.5° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
*40	40	113
50	50	125
*56	56	133
75	75	140
82	82	168
110	110	225
160	160	308
200	200	373
250	250	430
315	315	510
**400	400	640
500	500	Fabricated

87.5° Long Elbow "Push Fit"



D (mm)	d (mm)	L (mm)
82	82	219
110	110	276

45° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
*40	40	130
50	50	137
*56	56	174
75	75	146
82	82	168
110	110	220
160	160	287
200	200	325
250	250	440
315	315	520
**400	400	650
500	500	Fabricated



* Manufactured on special order
** Not Manufactured by Cosmoplast




45°Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
* 40	40	164
50	50	183
* 56	56	203
75	75	238
82	82	235
110	110	290
160	160	421
200	200	490
250	250	660
315	315	820
* 400	400	1030
500	500	Fabricated

45° Reduced Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	212
110	75	276
110	82	256
160	110	325
200	160	490
200	110	360
250	200	520
250	160	470

87.5° Tee "Push Fit"




D (mm)	d (mm)	L (mm)
* 40	40	164
50	50	174
* 56	56	169
75	75	215
82	82	168
110	110	280
160	160	407
200	200	410
250	250	560
315	315	680
* 400	400	880
500	500	Fabricated

87.5° Reduced Tee "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	191
110	75	236
110	82	224
160	110	325
200	160	370
250	200	560

Coupler "Push Fit"




D (mm)	L (mm)
* 40	110
50	110
* 56	108
75	131
82	113
110	159
160	168
200	230
250	270

Repair Coupler Push Fit




D (mm)	L (mm)
50	110
75	131
82	115
110	159
160	168
200	230
250	270
315	310
* 400	440
500	Fabricated
630	Fabricated

Expansion Socket / Single Socket "Push Fit"



D (mm)	d (mm)	L (mm)
82	82	110
110	110	129
160	160	151

Reducer "Push Fit"



D (mm)	d (mm)	L (mm)
* 50	40	124
75	50	143
82	56	110
* 110	56	133
110	75	175
110	82	133
160	110	173
200	160	275
250	160	370
250	200	260
315	250	300
** 400	315	—
** 500	400	—




* Manufactured on special order
 ** Not Manufactured by Cosmoplast



45° Double Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	235
110	110	287
160	160	401



87.5° Double Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	206
110	110	280
160	160	360



87.5° Access Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	223
110	110	269
160	160	374



Access Pipe "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	214
110	110	320
160	160	350



87.5° Access Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	219
110	110	276
160	160	263



Access Plug




D (mm)	L (mm)
*40	75
50	75
*56	50
75	89
82	77
110	88
160	95
200	100



End Cap



D (mm)	H (mm)
82	28
110	30
160	32
200	40
250	55
315	58



Pipe Plug




D (mm)	L (mm)
*40	48
50	50
*56	25
75	60
82	35
110	40
160	50




Solvent Welding Joints

uPVC Drainage Pipe (ss)




D (mm)	L (m)
50	5.8/6
75	5.8/6
82	5.8/6
110	5.8/6
160	5.8/6
200	5.8/6

87.5° Elbow




D (mm)	L (mm)
50	101
75	137
82	170
110	190
160	329
200	305

45° Elbow




D (mm)	L (mm)
50	86
75	128
82	139
110	170
160	269
200	290

Coupler




D (mm)	L (mm)
50	52
75	83
82	96
110	112
160	161
200	140

87.5° Tee Branch




D (mm)	L (mm)
50	106
75	167
82	205
110	250
160	358
200	365

87.5° Reduced Tee




D (mm)	d (mm)	L (mm)
82	56	162
110	50	156
110	56	167
110	75	187
110	82	201
160	110	250
200	160	360

45° Y Branch



D (mm)	L (mm)
50	125
75	192
82	205
110	268
160	337
200	400

45° Reduced Y Branch




D (mm)	d (mm)	L (mm)
82	56	179
110	50	175
110	82	223
160	110	380
200	160	400

Double Y Branch




D (mm)	d (mm)	L (mm)
110	110	260



Double Tee Branch




D (mm)	d(mm)	L(mm)
110	110	219
160	160	217



Reducer Bush




D (mm)	d (mm)	L (mm)
75	50	42
110	75	52
110	82	223
160	110	380
200	160	600



Access Plug & Cap




D (mm)	L (mm)
50	75
75	86
82	77
110	88
160	95
200	100



Pipe Access Plug




D (mm)	L (mm)
75	69
82	75
110	80
160	95



Access Pipe (Socket)




D (mm)	L (mm)
110	219
160	259



87.5° Access Elbow




D (mm)	L(mm)
110	190
160	329




45° Access Elbow



D (mm)	L(mm)
82	139
110	170
160	269




87.5° Access Tee




D (mm)	L (mm)
82	205
110	250
160	358

Bottle Trap




D (mm)	d (mm)	L (mm)
160	110	290

Gully Trap




D (mm)	d (mm)	L (mm)	H (mm)
160	110	290	150

Bottle Gully Trap




D (mm)	D1 (mm)	d (mm)	d1 (mm)	L (mm)
160	110	110	50	270

P Trap




D (mm)	d (mm)	L (mm)
110	110	290

Long P Trap Rubber




D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	240	276	466

V-Type P Trap Rubber




D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	303	216	245

V-Type P Trap Solvent



D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	303	216	245

Square Hopper Grating



D (mm)	L (mm)	H (mm)	H1 (mm)
110	164	98	25

Pipe Cleaner



Size (L)
½ L
1 L

Solvent Cement



Size (L)
¼ L
½ L
1 L

Rubber Joint Lubricant



Size (L)
1 L

Rubber Lined Pipe Clamp



Size (mm)
36
43
56
82
110
160
200

Unlined Pipe Clamp



Size (mm)
36
43
56
82
110
160

Testing Plug




Size (mm)
43 (38-48)
56 (49-60)
82 (73-85)
110 (94-110)
160 (146-163)
200 (191-211)

Straight W-Connector




D (mm)	D1(mm)	H(mm)
110	110	128



Offset WC Connector



D (mm)	D1(mm)	H(mm)	F(mm)
110	110	128	20
110	110	128	40



COSMOPLAST UPVC INSPECTION CHAMBERS



Inspection chambers are necessary in every drainage installation for inspection, testing and removal of solids from the drainage system. Cosmoplast Inspection Chamber provides access to the drainage system allowing rodding in both directions.

DEPTH ADJUSTMENT:

The chamber depth can easily be accommodated by installing the chamber risers one over the other to achieve the desired height. The last chamber riser can be trimmed to suit the finished ground level.


COMPONENTS :

Inspection Chamber Base




DIMENSIONS (mm)						
D	C	L	L1	H	H1	H2
110	330	450	440	80	130	237


Inspection Chamber Riser




DIMENSIONS (mm)				
D	D1	D2	H	
328	335	320	156	




Inspection Chamber Cover




DIMENSIONS (mm)				
L	L1	L3	H	
312	312	338	130	



Inspection Chamber Blanking Plug



DIMENSIONS (mm)					
D	D1	D2	L	T	
116	110	102	66	2	



Inspection Chamber Rubber Seal




Perforated & Slotted Pipes

a) Perforated Pipes


Cosmoplast produces wide range of perforated uPVC pipes for Sub-soil drainage applications. The below sketches show the general configurations which may vary depending on size and class of pipe to be perforated.

Parameters		Limits of Variation
Outside diameter	D	32mm to 630mm in standard sizes
Wall thickness	t	In accordance with the class of pipes selected
Longitudinal pitch of holes	p	30mm to 200mm depending on size and class of pipe
Hole Diameter	d	3mm to 10mm depending on size and class of pipe
Number of rows	n	1 to 4
Angular pitch of holes	a	40 degrees for 3 or 4 rows 40, 80 or 120 degrees for 2 rows

Straight rows




Staggered rows



b) Slotted pipes

Cosmoplast produces wide range of SLOTTED uPVC pipes for Sub-soil and Land drain

Cosmoplast uPVC slotted pipes have two rows of circumferential slots which are machine cut and staggered, the slots are cut at an angle of 45° to give a large open area free to carry water. Pipes are slotted to give maximum infiltration as detailed below.



SECTION- AA

SIZES	SLOT LENGTH		SLOT WIDTH		Min.No.of slot per MTR/ROW	Min.slot Area mm ² /m	PITCH mm
	Min. mm	Max. mm	Min. mm	Max. mm			
110	63	65	2	4	13	4914	75
160	63	65	2	4	13	4914	75
200	76	78	2	4	13	5928	75
225	86	88	2	4	13	6864	75
250	98	100	2	4	13	7644	75
315	120	125	2	4	13	9360	75

Note:

The number of slot, slot width, length, pitch and pattern can be altered to suit specific requirements



WARRANTY

Cosmoplast uPVC pipes and fittings are subjected to continuous tests during production in order to guarantee high quality and reliability.

Cosmoplast Industrial Co. LLC guarantees that its uPVC Pipes & Fittings are free from manufacturing and material defects.

In witness hereof, Cosmoplast issues this warranty for its system of uPVC Pipes and Fittings which shall be valid for a period of ten years starting from the date of installation.

However, Cosmoplast will not accept, and will not be held liable or responsible for damage to these products, or any consequential losses under the following conditions:

1. If working conditions are different than those prescribed in this catalogues.
2. If the components are used in installations where the fluid is not compatible with the material as per the related international standards.
3. If the components present defects when installed, due to incidental factors easily recognizable at the time of installation or when the system is submitted to pressure test.
4. If Cosmoplast components are installed with other items not manufactured by Cosmoplast.
5. In case of poor or inappropriate storage.
6. In case of poor or inappropriate installation, use or operation.

WARRANTY COVERAGE:

This Warranty is limited only to the replacement of the material with manufacturing defects. Cosmoplast will not be liable for any direct or indirect consequential losses or damages.



BS EN 1329/1401



ISO 9001 : 2015

CERTIFICATE OF REGISTRATION

COSMOPLAST INDUSTRIAL COMPANY LLC
BAGHDAD, AL-DIKR, AL-DIWA, AL-DIKR 1, P.O. Box 9534, Al-Diwia, Salah Al-Din Governorate, Iraq

ISO 9001:2015

intertek

This is to certify that the quality management system of Cosmoplast Industrial Company LLC has been registered by Intertek in accordance with the requirements of ISO 9001:2015.

The management system is applicable to: Manufacturing and Sale of Polypropylene Products (Polypropylene Pipes, Pipes and Fittings, Polypropylene (PP) Pipes and Fittings, Cross-linked Polypropylene (PPC) Pipes and Fittings, High Pressure Polyethylene (HDPE) Pipes and Fittings, Polyethylene Glycol (PEG) Pipes and Fittings.

Product Code: 02 EN 1461-1
Product Name: Polypropylene systems for rain-water underground drainage and sewerage - unperforated polypropylene (PPC-0)

Issue Date: 18/08/2014
Valid Until: 18/08/2015

For and on behalf of: **Cosmoplast Industrial Co. LLC**
Label Date: 12/11/2014

Page 1 of 4

bsi.
Kitemark Licence

This is to certify that: **Cosmoplast Industrial Co LLC**
BAGHDAD, AL-DIKR 1
Iraq
United Arab Emirates

HSE Kitemark Licence Number: **KM 590423**

In respect of: **ISO 9001:2015**
Polypropylene systems for rain-water underground drainage and sewerage - unperforated polypropylene (PPC-0)

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions appearing on one of the Kitemarks, in order to indicate that your ISO 9001:2015 Certified Organisation has been certified in accordance with the requirements of ISO 9001:2015.

The use of the Kitemark is authorised in respect of the Product(s) detailed on this Certificate provided as from the above address.

For and on behalf of: **Cosmoplast Industrial Co. LLC**
Label Date: 12/11/2014

Page 1 of 4

No. KM 590423

Fitting	Dimension	Type of socket
10mm	10mm	10mm
15mm	15mm	15mm
20mm	20mm	20mm
25mm	25mm	25mm
32mm	32mm	32mm
40mm	40mm	40mm
50mm	50mm	50mm
63mm	63mm	63mm
75mm	75mm	75mm
90mm	90mm	90mm
110mm	110mm	110mm
125mm	125mm	125mm
150mm	150mm	150mm
175mm	175mm	175mm
200mm	200mm	200mm
225mm	225mm	225mm
250mm	250mm	250mm
280mm	280mm	280mm
315mm	315mm	315mm
350mm	350mm	350mm
380mm	380mm	380mm
420mm	420mm	420mm
450mm	450mm	450mm
500mm	500mm	500mm
550mm	550mm	550mm
600mm	600mm	600mm
650mm	650mm	650mm
700mm	700mm	700mm
750mm	750mm	750mm
800mm	800mm	800mm
850mm	850mm	850mm
900mm	900mm	900mm
950mm	950mm	950mm
1000mm	1000mm	1000mm

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

No. KM 590423

Fitting	Dimension	Type of socket
10mm	10mm	10mm
15mm	15mm	15mm
20mm	20mm	20mm
25mm	25mm	25mm
32mm	32mm	32mm
40mm	40mm	40mm
50mm	50mm	50mm
63mm	63mm	63mm
75mm	75mm	75mm
90mm	90mm	90mm
110mm	110mm	110mm
125mm	125mm	125mm
150mm	150mm	150mm
175mm	175mm	175mm
200mm	200mm	200mm
225mm	225mm	225mm
250mm	250mm	250mm
280mm	280mm	280mm
315mm	315mm	315mm
350mm	350mm	350mm
380mm	380mm	380mm
420mm	420mm	420mm
450mm	450mm	450mm
500mm	500mm	500mm
550mm	550mm	550mm
600mm	600mm	600mm
650mm	650mm	650mm
700mm	700mm	700mm
750mm	750mm	750mm
800mm	800mm	800mm
850mm	850mm	850mm
900mm	900mm	900mm
950mm	950mm	950mm
1000mm	1000mm	1000mm

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

No. KM 590423

ISO 9001:2015 - Plastic piping systems for rain-water underground drainage and sewerage - unperforated polypropylene (PPC-0)

Pipes: 10mm, 15mm, 20mm, 25mm, 32mm and 40mm diameter unperforated pipes.
Fittings are designated in ISO 6451-1 in accordance with the following:
Fittings manufactured from unperforated polypropylene (PPC-0).

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

bsi.
Kitemark Licence

This is to certify that: **Cosmoplast Industrial Co LLC**
BAGHDAD, AL-DIKR 1
Iraq
United Arab Emirates

HSE Kitemark Licence Number: **KM 590422**

In respect of: **ISO 12128-1**
Plastic piping systems for soil and waste drainage (low and high temperature) within the building structure - unperforated polypropylene (PPC-0)

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions appearing on one of the Kitemarks, in order to indicate that your ISO 12128-1 Certified Organisation has been certified in accordance with the requirements of ISO 12128-1.

The use of the Kitemark is authorised in respect of the Product(s) detailed on this Certificate provided as from the above address.

For and on behalf of: **Cosmoplast Industrial Co. LLC**
Label Date: 12/11/2014

Page 1 of 4

No. KM 590422

ISO 12128-1:2004 - Plastic piping systems for soil and waste drainage (low and high temperature) within the building structure - unperforated polypropylene (PPC-0)

Pipes: 50mm, 63mm, 75mm, 90mm, 110mm, 125mm, 150mm, 175mm, 200mm, 225mm and 250mm diameter unperforated pipes.

For and on behalf of: **Cosmoplast Industrial Co. LLC**
Label Date: 12/11/2014

Page 1 of 4

No. KM 590422

Fitting	Dimension	Type of socket
10mm	10mm	10mm
15mm	15mm	15mm
20mm	20mm	20mm
25mm	25mm	25mm
32mm	32mm	32mm
40mm	40mm	40mm
50mm	50mm	50mm
63mm	63mm	63mm
75mm	75mm	75mm
90mm	90mm	90mm
110mm	110mm	110mm
125mm	125mm	125mm
150mm	150mm	150mm
175mm	175mm	175mm
200mm	200mm	200mm
225mm	225mm	225mm
250mm	250mm	250mm

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

No. KM 590422

Fitting	Dimension	Type of socket
10mm	10mm	10mm
15mm	15mm	15mm
20mm	20mm	20mm
25mm	25mm	25mm
32mm	32mm	32mm
40mm	40mm	40mm
50mm	50mm	50mm
63mm	63mm	63mm
75mm	75mm	75mm
90mm	90mm	90mm
110mm	110mm	110mm
125mm	125mm	125mm
150mm	150mm	150mm
175mm	175mm	175mm
200mm	200mm	200mm
225mm	225mm	225mm
250mm	250mm	250mm

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

No. KM 590422

Fitting	Dimension	Type of socket
10mm	10mm	10mm
15mm	15mm	15mm
20mm	20mm	20mm
25mm	25mm	25mm
32mm	32mm	32mm
40mm	40mm	40mm
50mm	50mm	50mm
63mm	63mm	63mm
75mm	75mm	75mm
90mm	90mm	90mm
110mm	110mm	110mm
125mm	125mm	125mm
150mm	150mm	150mm
175mm	175mm	175mm
200mm	200mm	200mm
225mm	225mm	225mm
250mm	250mm	250mm

Issue Date: 18/08/2014
Label Date: 12/11/2014

Page 1 of 4

bsi.
Kitemark Certificate

This is to certify that: **Cosmoplast Industrial Co LLC**
BAGHDAD, AL-DIKR 1
Iraq
United Arab Emirates

HSE Kitemark Certificate Number: **KM 65943**

In respect of: **ISO 22818**
Thermoplastic waste pipes and fittings

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions appearing on one of the Kitemarks, in order to indicate that your ISO 22818 Certified Organisation has been certified in accordance with the requirements of ISO 22818.

The use of the Kitemark is authorised in respect of the Product(s) detailed on this Certificate provided as from the above address.

For and on behalf of: **Cosmoplast Industrial Co. LLC**
Label Date: 20/10/2019

Page 1 of 2

Kitemark Certificate
No. KM 65943

ISO 22818:2019 - Thermoplastic waste pipes and fittings.

The scope of this Certificate covers the following products:

Material Size	Description
110 (SD40)	Non Ended / Sockled Pipe - White colour
110 (SD40)	Non Ended / Sockled Pipe - White colour
7 (SD40)	Non Ended / Sockled Pipe - White colour

Issue Date: 20/10/2019
Label Date: 20/10/2019

Page 2 of 2

SASO Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

SASO Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Exovo Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019


MDL Certificate of Conformity

Product Name: **Thermoplastic waste pipes and fittings**

Product Description: **Non Ended / Sockled Pipe - White colour**

Issue Date: 20/10/2019
Label Date: 20/10/2019

Pipeline Systems



www.cosmoplast.com

Cosmoplast Industrial Co. LLC

Sharjah

Sales Off. Tel: +971 6 5331212
 Fax: +971 6 5331917 / 5332901
 P.O. Box: 6032

Dubai

Tel: +971 4 8850500
 Fax: +971 4 8850700
 P.O. Box: 50488

Abu Dhabi

Sales Off. Tel: +971 2 5515364
 Fax: +971 2 5515365
 P.O. Box: 8593

Saudi Arabia-Riyadh

Tel: +966 11 265 4501
 Fax: +966 11 471 4669
 Email: pipeline@interplast-ksa.com

Email: pipeline@cosmoplast.com

