

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval:		

Pass Thru Half Solid Door Heated Cabinet

Pass-Thru PRO Series

Model: PRO-50-4H-PT(-AL)/(-AR)

___ FEATURES & BENEFITS =__

■ Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures.
- · Alarm beeps when doors are not sealed.
- Early warning alarm program detects issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- · Sensitive touch display.

■ Ducted fan air distribution system

Maintains temperature within the food zone

On/Off switch

ON/OFF switch is located on control panel

All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting


■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Half length stainless steel solid doors with locks
- Self-closing doors with stay open feature at 120 degrees
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles

• PRO-50-4H-PT: Right hinged + Left hinged

• PRO-50-4H-PT-AR: All Right hinged













PRO-50-4H-PT(-AL)/(-AR)	8	50.2	6	3000	15	547	513/4 x 361/4 x 78
Model	Swing Door	CU./FT.	#of Shelves	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D*x H†

(unit: inch)

Model: PRO-50-4H-PT(-AL)/(-AR)

ELECTRICAL DATA						
Voltage	208/115/60/1					
Plug Type	③NEMA L14-20P					
Full Load Amperes	15					
Wattage (W)	3000					
Feed Wires with Ground	4					
Cord Length (ft.)	8					
DIMENSIONAL DATA						
# of Doors	8					
# of Racks Accepted	2					
Net Capacity (cu. ft.)	50.2					
Ext. Length Overall (in.)	513/4 (1314mm)					
Ext. Depth Overall (in.)*	361/4 (920mm)					
Ext. Height Overall (in.)†	78 (1982mm)					
Int. Length Overall (in.)	421/4 (1073mm)					
Int. Depth Overall (in.)	275/8(702mm)					
Int. Height Overall (in.)	58 _{3/4} (1493mm)					
# of Shelves	6					
Shelf Size (L x D) (in.)	223/4 x 263/8					
Net Weight (lbs.)	499					
Gross Weight (lbs.)	547					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty

Standard features

- · Door locks standard
- Standard 4" dia. swivel casters with locks on the front set
- · Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design


OPTIONAL ACCESSORIES


- 5" caster, 1/2" diameter & 13 TPI:
- M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- · Additional stainless steel shelf: (L, R) H50R901700
- · Half door bun tray rack: TSP-2224

(each holds up to six 18"L x 26"D sheet pans)

• Tray slides kits: TS23-N1LR(#1), TS23-N4LR(#4), TS23-UNLR-H(Universal)

PLAN VIEW





SIDE VIEW

Ver 20190612











lurbo air









^{*} Depth does not include 2-1/4" for door handles.

[†] Height does not include 5" for caster height.