

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model # :	
Item # :	Qty:
Available W/H :	
Approval :	

# Half Solid Door Freezer

Reach-In Top Mount M3 Series

# Model: M3F72-6-N

### \_\_\_ FEATURES & BENEFITS =\_\_

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- · Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
- Early warning alarm program detects issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo Freeze).
- · Smart defrost system will defrost as needed.
- · Automatic evaporator fan motor delays.

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Stainless steel cabinet construction

The Turbo Air M3 freezer model boasts a stainless steel exterior (galvanized steel top, bottom and back) and AL interior with stainless steel floor. It guarantees the utmost in cleanliness and long product life. Sharp corners and edges have been rounded to reduce the risk of injury. The M3 adds a touch of style to the most refined setting.

#### ■ Adjustable, heavy duty, PE (polyethylene) coated wire shelves

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

## ■ Door pressure release device

Pressure relief doors are designed to eliminate vacuum pressure and allow easy, instant door opening.

#### ■ LED interior lighting

- Top mount compressor
- Freezer holds -10°F ~ 0°F for the best in frozen food preservation



# Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.













ENERGY STAR®

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
M3F72-6-N	6	65.6	9	1	7.9	644	773/4 x 303/4 x 78

(unit: inch)

# Half Solid Door Freezer

# **Model: M3F72-6-N**

ELECTRICAL DATA	ELECTRICAL DATA				
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	7.9				
Compressor HP	1				
Feed Wires with Ground	4				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
# of Doors	6				
# of Racks Accepted	3 65.6				
Net Capacity (cu. ft.)					
Ext. Length Overall (in.)	773/4 (1975mm)				
Ext. Depth Overall (in.)*	30 <sub>3/4</sub> (780mm)				
Ext. Height Overall (in.) †	78 (1981mm)				
Int. Length Overall (in.)	737/8 (1877mm) 261/2 (675mm)				
Int. Depth Overall (in.)					
Int. Height Overall (in.)	60 <sub>5/8</sub> (1539mm)				
Gross Weight (lbs.)	644				
# of Shelves	9				
Shelf Size (L x D) (in.)	23 x 231/2 (Left/Right)				
GIIGII GIZE (L X D) (III.)	251/4 x 231/2 (Middle)				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


## 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor WARRANTY:

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Door locks standard
- Magnetic door gaskets
- Solid and sturdy grille design
- Legs available (optional)
- Half size pan racks available (optional)


#### ■ OPTIONAL ACCESSORIES:

- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf G8F1800101 (Left/Right), G8F1800201 (Middle)
- ☐ Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)

**PLAN VIEW** 



**PLAN VIEW** 



**SIDE VIEW** 

Ver.20171006











**ENERGY STAR®** 

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Depth does not include 2" for rear condensate enclosure.

<sup>†</sup> Height does not include 5" for caster height.