



DM-200B 02/02/18 Item # 13051



Model	Exterior Dimensions	Interior Dimensions	Agitator	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Shipping Weight
DM-200B	30 ^{3/10} " x 28" x 36 ^{3/8} "	23" x 22 ^{3/8} " x 22 ^{1/2} "	14.5" diameter	15A	4.1A	115V/60/1	240 lbs.

Operating Limits

- Ambient Temp Range
- Water Temp Range 45 - 90°F 10 - 113 PSIG
- Water Pressure
- Voltage Range

Options

- 4" leg kit
- Top Kit (HS-2036) to accommodate KM-340, KM-515M, or KM-650M ice machines

45 - 100°F

104 - 132V

Service

- If dispenser is to be permanently installed, allow a minimum clearance of 6" (15 cm) on the right side, for access to service the drive mechanism. Allow a minimum clearance of 24" (60 cm) above the dispenser for easy filling with ice.
- Panels easily removed and all components accessible for service.

Plumbing

- Water supply line: Minimum 1/8" Nominal ID Copper Water Tubing or Equivalent
- Drain line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Printed in the U.S.A.

Hoshizaki reserves the right to change specifications without notice.





