



Stainless design.
Stellar performance.
Superior value.

Project name: _____

Location: _____

Item #: _____ QTY: _____

Model #: _____

AUC27R REFRIGERATOR

SINGLE DOOR UNDER-COUNTER WORKTOP REFRIGERATOR



AUC27R

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full two year parts and labor warranty and a five year compressor warranty.
- ▶ Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- ▶ All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.
- ▶ Energy Star approved.



COMMERCIAL FREEZERS & REFRIGERATORS

Division of Broich Enterprises, Inc. 7550 Market Place Dr Eden Prairie, MN 55344
952-941-2270 Fax: 952-941-3066 www.arcticairco.com info@arcticairco.com



Intertek



Intertek



AUC27R

REFRIGERATOR

SINGLE DOOR UNDER-COUNTER WORKTOP REFRIGERATOR

All units come standard with heavy-duty worktop surface.

Exterior cabinet construction consists of full stainless steel front and sides.

One adjustable, heavy-duty epoxy coated wire shelves.

Interior cabinet is bright white epoxy coated steel liner with full stainless steel floor white cover corners.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Electronic thermostat with external digital LED display for accurate control and easy reading.

Easy to mount casters (two lockable) are standard with all units.



Vaulted self closing doors that remain open at 90 degrees.

Solid door construction with foamed-in-place recessed handle.

Magnetic door gaskets are removable and replaceable without tools.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Self-contained capillary tube system using environmentally friendly R600a Hydrocarbon gas.

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full two year parts and labor warranties and a five year compressor warranty.

STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

Model Number	External Dimensions			Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	HP	AMPS	REF	NEMA Plug	Crate Weight
	Width	Depth	Height*										
AUC27R	27.875"	30"	35.625"	1	1	5.4	33°F to 41°F	8'	3/8	1.5	R600a	5-15P	185Lbs

Depth with door open 90° = 56.50"
 *Height includes 3" for casters
 Height with worktop removed = 34.125"

