



# COUNTERTOP - CATERING/OUTDOOR RANGE

## Gas Modular Countertop Ranges

HDO-12-316L

### Standard Features

- 33,000 BTU NAT (24,000 BTU LP) open top non-clogging burner
- Hi/Low burner controls
- 316L stainless steel front, rear, sides, and bottom panels
- 3/4" rear gas connection and pressure regulator
- 12" enamel coated cast flush top grates
- 4" stainless steel legs
- 316L stainless steel full width crumb tray
- One year limited Parts and Labor Warranty



Model HDO-12-316L

Job \_\_\_\_\_  
Item# \_\_\_\_\_

### STANDARD CONSTRUCTION SPECIFICATIONS

**Exterior Finish:** Front, rear, sides and bottom panels are constructed of 316L stainless steel.


**Range Top:** Each burner is a 33,000 BTU NAT (24,000 BTU LP) cast iron non-clogging burner. Removable flush top grates. Center-to-center measurements between burners not less than 12", side-to-side or front-to-back. Removable one piece, full width crumb tray provided under burners.

**Gas Heat Control System:** Each burner is controlled by a gas valve for independent control of flame. One standing pilot services each burner. A 3/4" rear gas connection is standard.

**Legs:** Stainless steel 4" adjustable legs.





Models:  HDO-12-316L



SHIPPING CRATE DIMENSIONS & WEIGHT					
MODEL	WIDTH	BURNERS @BTU (NAT/LP)	CRATED WIDTH	CRATED DEPTH	CRATED WEIGHT
HDO-12-316L	12.125" (308)	2(33K/24K)	31" (788)	39" (991)	165 lbs (75 kg)

Dimensions shown in inches and (millimeters). All values are estimated.



### UTILITY INFORMATION

**GAS:** Each unit has a 3/4" rear gas connection with a male NPT connector. Minimum supply pressure is 7" W.C. for natural gas and 11" W.C. for propane. All units require a regulated gas supply. Pressure regulator included. If using a flexible hose gas connection, the I.D. of the hose must not be smaller than the connector on the unit and must comply with ANSI Z21.69, providing an adequate means of restraint to prevent undue strain on the gas connection.

MODEL	GAS (BTU/HR)	
	NATURAL	PROPANE
HDO-12	66,000	48,000

### MISCELLANEOUS

- If casters are used with flex hose, a restraining device should be used to eliminate undue strain on the flex hose.
- Minimum clearance from noncombustible construction is zero. Minimum clearance from combustible construction is 10" on sides and 6" on rear.
- Install under vented hood.
- Check local codes for fire and sanitary regulations.

**NOTICE:** Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

### OPTIONS AND ACCESSORIES

- 316L Stainless steel stand
- All Terrain 10" casters
- 2" high insulator base for mounting on refrigerated base
- Battery spark ignition

**INTENDED FOR COMMERCIAL USE ONLY.  
NOT FOR HOUSEHOLD USE.**



1100 Old Honeycutt Road, Fuquay-Varina, NC 27526  
(919) 762-1000 www.southbendnc.com