

Standard Features

- Commercial gas range 73" wide with a 37" high cooking top
- 4" Stainless steel front rail, stainless steel front and sides
- (2) Front located, manual, gas shut-off valves for each side of the range
- One year No Quibble, 24/7 parts and labor warranty
- Factory installed Regulator
- Four (4) removable, cast iron grate tops (rear holds up to 14" stock pot)
- Standing pilot for open top burners
- Battery spark ignition for oven bases

Optional 33K Non-clog Burners (Burner Option 1)

- (10) patented, one piece, lifetime clog free, cast iron burners
- 33,000 BTU NAT

Optional 5 Burner configuration (Burner Option 5)

- Combine (2) Pyromax burners in the rear with (3) standard 33K burners in the front

Optional Griddle Top (L or R)

- 36" Available
- 1/2" thick cold rolled steel griddle plate
- Manual or thermostatically controlled

Optional Charbroiler (L or R)

- 36" Available
- Removable, cast iron grates

Refer to AutoQuotes for list pricing.



(4721DD shown with optional casters)

Job _____
Item# _____

CONSTRUCTION SPECIFICATIONS

Exterior Finish: Stainless steel front, sides and shelf standard.

RangeTop: 27" deep cooking surface. Center-to-center measurements between burners not less than 12", side-to-side or front-to-back. Two (2) removable one piece drip trays are provided under burners to catch grease drippings.

Flue Riser: 22.5" flue riser standard with heavy duty shelf. Optional 10" and 5" flue riser available without shelf.

Oven Door: Spring assisted door.

Oven Interior: Double sided, full porcelain enamel oven cavity for superior cleanability and corrosion protection. Covered corners for easy cleaning and enhanced airflow eliminating hot/cold spots.

Legs: (6) total 6" stainless steel adjustable legs standard (casters optional)

Pressure Regulator: Factory installed.

Standard Oven Models (D)

45,000 BTU NAT oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior measuring 14" high x 26" wide x 26.5" deep. Full sized pans fit both ways. One rack with two position side rails.

Convection Oven Models (A):


32,000 BTU NAT convection oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior measuring 14" high x 26" wide x 24" deep. Three racks with five position side rails. 1/2 hp, 1710 rpm, 60 cycle, 115V AC, high efficiency, permanent split phase motor with permanent lubricated ball bearings, overload protection and Class "B" insulation. On/Off switch to allow CO base to operate as a standard oven.

Available Base Combinations

AA, DD



Dimensions -in (mm)



MODELS	EXTERIOR											COOK TOP	DOOR OPENING	OVEN BOTTOM	3/4" GAS CONN.		ELECTRIC	
	WIDTH A	DEPTH B	C	D	E	F	G	H	J	K	L				M	N	O	P
472_DD	73" (1854)	34.00" (864)	29.75" (756)	31.00" (787)	10.00" (254)	2.75" (70)	59.50" (1511)	22.50" (572)	31.00" (787)	6.00" (152)	-	37.00" (940)	15.50" (394)	13.00" (330)	3.25" (83)	30.25" (768)	-	-
472_AA	73" (1854)	42.13" (1070)	29.75" (756)	31.00" (787)	10.00" (254)	2.75" (70)	59.50" (1511)	22.50" (572)	31.00" (787)	6.00" (152)	8.25" (210)	37.00" (940)	15.50" (394)	13.00" (330)	3.25" (83)	30.25" (768)	24.00" (610)	6.00" (152)

MODELS	OVEN INTERIOR			CRATE SIZE			CUBIC VOLUME	CRATED WEIGHT
	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
472_DD	26.00" (660)	26.50" (673)	14.00" (356)	78" (1981)	48.00" (1219)	74.00" (1880)	160.3 cu. ft 4.54 cu.m.	1320 lbs. 600 kg.
472_AA	26.00" (660)	24.00" (610)	14.00" (356)					

UTILITY INFORMATION

BTUs EACH BURNER	STD NON-CLOG	PYROMAX	(A) CNV OVEN PER CAVITY	(D) STD OVEN PER CAVITY	GRIDDLE 36"	CHARBROILER 36"	HOT TOP 12"	HOT TOP 24"
NAT	33K	40K	32K	45K	64K	96K	24K	48K
LP	24K	31K	30K	40K	64K	96K	24K	48K

GAS:

- One 3/4" female connection.
- Required minimum inlet pressure
 - Natural gas 7" W.C.
 - Propane gas 11" W.C.

ELECTRICAL: (for models with convection ovens)

- Standard -115/60/1 furnished with 6' cord with 3-prong plug. Total max amps 5.9 per convection oven base.
- Optional -208/60/1, 50/60/1 phase. Supply must be wired to junction box with terminal block located at rear. Total max amps 2.7

MISCELLANEOUS

- If using Flex-Hose, the I.D. should not be smaller than 3/4" and must comply with ANSI Z 21.69
- If casters are used with flex hose, a restraining device should be used to eliminate undue strain on the flex hose
- For installation on combustible floors 6" high legs or casters are required. Minimum clearance from combustible construction is 10" on sides and rear for all units except charbroilers. Charbroiler units are for use in noncombustible locations ONLY.
- Rear clearance to noncombustible construction is 10" for charbroilers and 0" for all other tops and bases. Side clearance to noncombustible constructions is 0" on all units.
- Recommended - Install under vented hood
- Check local codes for fire, installation and sanitary regulations.
- If the unit is connected directly to the outside flue, an A.G.A approved down draft diverter must be installed at the flue outlet of the oven.
- Two speed motors are not available on Restaurant Range Convection Ovens.

NOTICE: Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

OPTIONS AND ACCESSORIES

- | | |
|---|--|
| <ul style="list-style-type: none"> <input type="checkbox"/> 5" flue riser <input type="checkbox"/> 10" Flue Riser <input type="checkbox"/> 3/4" quick disconnect with flexible hose complies with ANSI Z 21.69 (specify 3ft, 4ft, 5ft) <input type="checkbox"/> Hot Top plate - plate replaces 2 Open burners 1, 2 or 3 <input type="checkbox"/> Various salamander & cheesemelter mounts available. (salamanders and cheesemelters mounts cannot be interperped to a 72" range) | <ul style="list-style-type: none"> <input type="checkbox"/> Rear step up burners (4721AA & 4721DD ONLY) <input type="checkbox"/> Flame Failure available (4721AA, 4721DD, 4721AA-3GL, 4721DD-3GL, 4721AA-3GR & 4721DD-3GR) <input type="checkbox"/> Battery spark ignition for open tops, charbroilers, griddles and hot tops. <input type="checkbox"/> Extra Oven Racks <input type="checkbox"/> Casters-all swivel-front with locks |
|---|--|

INTENDED FOR COMMERCIAL USE ONLY.

NOT FOR HOUSEHOLD USE.

1100 Old Honeycutt Road, Fuquay-Varina, NC 27526
(919) 762-1000 www.southbendnc.com

