

U.S.A FOODSERVICE DIVISION

TRUE MANUFACTURING CO., INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

Model:

TBR32-RISZ1-L-S-S-1

True Bar Refrigerator:

Reach-In Single Zone Refrigerator



Project Name	LOCATION	
Ітем #	Q TY	AIA#
Model #		SIS#

FEATURES

- ▶ R290 Hydrocarbon refrigerant.
- Temperatures of 33°F to 38°F (.5°C to 3.3°C)
- ▶ Exterior: Stainless steel
- Interior: Stainless steel
- RCU Technology
- ▶ White LED interior lighting
- NSF/ANSI standard 7 compliant for open food product
- ▶ UL Rated for outdoor use
- ▶ Three (3) interior access ports
- ▶ Field reversible doors
- Zero clearance (side and back)
- Front air intake / front air discharge
- ▶ Electronic temperature control with exterior digital display

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Cabinet Dimensions Cord Crated Capacity (inches) 115V/60/1 Length‡ Weight (mm) Voltage 12 oz. (total ft.) (lbs.) W Н HP NEMA Model **Doors Shelves** 12 oz. Cans **Bottles** D† **Amps** (total m) (kg) TBR32-RISZ1-L-S-S-1 3 21 6-pks 32 24% 343/4 5-15P 38 6-pks 1/5 1.8 10 280 813 631 881 3.04 127

- † Depth does not include $1\frac{1}{2}$ " (35 mm) for door handles. * Height does not include $\frac{1}{2}$ " (7 mm) for leg levelers
- ‡ Cord length listed represents usable cord length.



Model:

TBR32-RISZ1-L-S-S-1

True Bar Refrigerator:

Reach-In Single Zone Refrigerator



ADDITIONAL FEATURES

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system
- Environmentally friendly R290 hydrocarbon refrigerant
- Forced air refrigeration system which maintains 33°F to 38°F (.5°C to 3.3°C) product temperatures
- Exclusive RCU technology allows for the reversing of the condensor fan motor, helping to keep the condensing coil clean and reduce the negative effects of a

CABINET CONSTRUCTION

- Exterior: Stainless steel front, sides, and countertop
- Interior: Stainless steel floor and sides with ABS plastic ceiling
- Insulation: Entire cabinet is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion and zero global warming potential
- Base fitted with leg levelers

DOORS

- Door locks standard
- Field Reversible Doors standard (reverse hinge kit included)

- Three (3) adjustable, gray PVC coated wire shelves. 17 11/16 "W x 18"D (450 mm x 458 mm). Four (4) chrome plated shelf clips included per shelf.
- Aluminum shelf support pilasters. Shelves are adjustable on ½" (13 mm)

MODEL FEATURES

- NSF/ANSI Standard 7 compliant for open food
- UL approved for outdoor use
- Electronic temp control with exterior digital display
- Three (3) access ports standard (see drawing for locations)

ELECTRICAL


• Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.




OPTIONAL FEATURES/ACCESSORIES Upcharge and lead times may apply.

- ☐ TruLumina® 14-Color LED lighting
- ☐ Castors: % " (23 mm) rollers, 2" (51mm), 3" (77mm), 4" (102mm), 5" (127mm) castors
- ☐ 6" (153mm) legs
- ☐ 6" (153mm) seismic legs
- ☐ Alternative temperature zones available (contact factory)
- ☐ Right side compressor


PLAN VIEW




FRONT VIEW



BACK VIEW





TOP VIEW

PLAN VIEW NOTES

- Dimensions in brackets are in millimeters.
- Depth does not include 1 ½ " (35 mm) for door handles.
- Height does not include ¼ " (7 mm) for leg levelers

SIDE VIEW COMPRESSOR WARRANTY (U.S.A. only)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER